DATASHEET - FAZ6-B6/4



Miniature circuit breaker (MCB), 6 A, 4p, characteristic: B, 6 kA

Part no.FAZ6-B6/4Catalog No.239180Alternate CatalogFAZ6-B6/4



Design verification as per IEC/EN 61439

No.

standard's requirements.
standard's requirements.
standard's requirements.
standard's requirements.
standard's requirements.
ce the entire switchgear needs to be evaluated.
ce the entire switchgear needs to be evaluated.
standard's requirements.
ce the entire switchgear needs to be evaluated.
standard's requirements.
ce the entire switchgear needs to be evaluated.
ce the entire switchgear needs to be evaluated.
r's responsibility.
r's responsibility.
r's responsibility.
r's responsibility.
r's responsibility.
s responsible for the temperature rise calculation. Eaton will lation data for the devices.
r's responsibility. The specifications for the switchgear must be
r's responsibility. The specifications for the switchgear must be
the requirements, provided the information in the instruction

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Miniature circuit breaker (MCB) (EC000042)

Electric engineering, automation, process control engineering / Electrical installation, device / Miniature circuit breaker system (MCB) / Miniature circuit breaker (MCB) (ecl@ss10.0.1-27-14-19-01 [AAB905014])				
Release characteristic		В		
Number of poles (total)		4		
Number of protected poles		4		
Rated current	А	6		
Rated voltage	V	400		
Rated insulation voltage Ui	V	440		
Rated impulse withstand voltage Uimp	kV	4		
Rated short-circuit breaking capacity Icn EN 60898 at 230 V	kA	6		
Rated short-circuit breaking capacity Icn EN 60898 at 400 V	kA	6		
Rated short-circuit breaking capacity Icu IEC 60947-2 at 230 V	kA	10		
Rated short-circuit breaking capacity Icu IEC 60947-2 at 400 V	kA	10		

Voltage type		AC
Frequency	Hz	50 - 60
Current limiting class		3
Suitable for flush-mounted installation		No
Concurrently switching N-neutral		No
Over voltage category		3
Pollution degree		2
Additional equipment possible		Yes
Width in number of modular spacings		4
Built-in depth	mm	70.5
Degree of protection (IP)		IP20
Ambient temperature during operating	°C	-25 - 75
Connectable conductor cross section multi-wired	mm²	1 - 25
Connectable conductor cross section solid-core	mm²	1 - 25

Additional product information (links)

Temperature dependency, derating

https://www.eaton.com/content/dam/eaton/technicaldocumentation/technical-data-tables/Derating table FAZ6.pdf