

DC Axial Fans


Series 4400 F 119 x 119 x 25 mm

- DC fans with electronically commutated external rotor motor. Fully integrated commutation electronics.
- With electronic protection against reverse polarity, blocking and overloading by PTC-resistor; partially impedance protected.
- Fan of fibreglass reinforced plastic. PBTP housing, PA impeller.
- Air exhaust over struts. Rotational direction CCW looking at rotor.
- Electrical connection via 2 leads AWG 24, TR 64. Stripped and tinned ends.
- Mass 175 g.

ebm-papst • St. Georgen



Nominal Data	Air Flow		Nominal Voltage	Voltage Range	Noise	Sinter-Sleeve Bearings	Ball Bearings	Power Input	Nominal Speed	Temperature Range	Service Life L ₁₀ at 40 °C		Curve	Specials
	m ³ /h	CFM									V DC	V DC		
4412 FGL	94	55.3	12	7...14	26	3.9	□	1.25	1 600	-20...+75	80 000 / 35 000		1	/2
4412 FGML	114	67.1	12	7...12.6	32	4.3	□	2.0	1 950	-20...+75	75 000 / 32 500		2	/2; /12
4412 FML	114	67.1	12	7...12.6	32	4.3	■	2.0	1 950	-20...+75	75 000 / 32 500		2	
4412 FGM	140	82.4	12	7...12.6	38	4.8	□	3.2	2 400	-20...+75	70 000 / 30 000		3	/12
4412 FM	140	82.4	12	7...12.6	38	4.8	■	3.2	2 400	-20...+75	70 000 / 30 000		3	/2
4412 FG	170	100.1	12	8...12.6	43	5.3	□	5.3	2 900	-20...+60	60 000 / 37 500		4	
4412 F	170	100.1	12	8...12.6	43	5.3	■	5.3	2 900	-20...+60	60 000 / 37 500		4	/2
4414 FL	94	55.3	24	18...28	26	3.9	■	1.0	1 600	-20...+75	80 000 / 35 000		1	/2
4414 FM	140	82.4	24	12...28	38	4.8	■	3.2	2 400	-20...+75	70 000 / 30 000		3	/2
4414 FG	170	100.1	24	12...28	43	5.3	□	5.0	2 900	-20...+60	60 000 / 37 500		4	/2
4414 F	170	100.1	24	12...28	43	5.3	■	5.0	2 900	-20...+60	60 000 / 37 500		4	/2; /12
4418 FG	170	100.1	48	28...53	43	5.3	□	5.5	2 900	-20...+60	60 000 / 37 500		4	
4418 F	170	100.1	48	28...53	43	5.3	■	5.5	2 900	-20...+60	60 000 / 37 500		4	/2; /12; /39



Available on request:
Fan housing with moulded-in
spacers. For mounting over
both flanges.

