



Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 23

LOCTITE GC 50 SAC305 T5 84V 62K

SDS No. : 597997
V003.1

Revision: 08.04.2020

printing date: 08.06.2020

Replaces version from: 28.02.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE GC 50 SAC305 T5 84V 62K

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Solder Paste

1.3. Details of the supplier of the safety data sheet

Henkel Belgium N.V.

Esplanade 1

1020 Brussels

Belgium

Phone: +32 (2) 421 2711

Fax-no.: +32 (2) 420 7025

ua-productsafety.uk@henkel.com

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Serious eye damage

Category 1

H318 Causes serious eye damage.

Skin sensitizer

Category 1

H317 May cause an allergic skin reaction.

Chronic hazards to the aquatic environment

Category 2

H411 Toxic to aquatic life with long lasting effects.

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Contains

2-(2-hexyloxyethoxy)ethanol

rosin

Dodecane-1-thiol

Signal word: Danger

Hazard statement: H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statement: P261 Avoid breathing fume.
Prevention P273 Avoid release to the environment.
P280 Wear protective gloves/eye protection.

Precautionary statement: P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
Response P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

2.3. Other hazards

Avoid breathing fumes given out during soldering.

After handling solder wash hands with soap and water before eating, drinking or smoking.

Keep out of reach of children.

This product contains modified rosin.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

Flux fumes may irritate the nose, throat and lungs and may after prolonged/repeated exposure give an allergic reaction (asthma).

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

| Hazardous components CAS-No. | EC Number REACH-Reg No. | content | Classification |
|---|--|---------------|--|
| Tin 7440-31-5 | 231-141-8 01-2119486474-28 | 50- 100 % | |
| 2-(2-hexyloxyethoxy)ethanol 112-59-4 | 203-988-3 01-2119945815-28 | 1- < 5 % | Acute Tox. 4; Dermal H312 Eye Dam. 1 H318 |
| Modified rosin 144413-22-9 | 434-230-1, 434- 230-1 01-2120117087-62 | 2,5- < 25 % | Aquatic Chronic 4 H413 |
| Silver >= 99,9 % Ag in powder (>100nm<1mm) 7440-22-4 | 231-131-3 01-2119555669-21 | 2,5- < 25 % | Aquatic Acute 1 H400 Aquatic Chronic 1 H410 M factor (Acute Aquat Tox): 10 M factor (Chron Aquat Tox): 10 |
| rosin 8050-09-7 | 232-475-7 01-2119480418-32 | 1- < 5 % | Skin Sens. 1 H317 |
| Copper 7440-50-8 | 231-159-6 01-2119480154-42 | 0,25- < 2,5 % | Aquatic Acute 1 H400 Aquatic Chronic 3 H412 |
| Dodecane-1-thiol 112-55-0 | 203-984-1 01-2119491318-31 | 0,1- < 1 % | Skin Corr. 1C H314 Aquatic Chronic 1 H410 Skin Sens. 1A H317 Eye Dam. 1 H318 Aquatic Acute 1 H400 M factor (Acute Aquat Tox): 10 M factor (Chron Aquat Tox): 10 |
| 2-hexyloxyethanol 112-25-4 | 203-951-1 01-2119486575-24 | 0,1- < 1 % | Acute Tox. 4; Oral H302 Acute Tox. 3; Dermal H311 Skin Corr. 1B H314 |

**For full text of the H - statements and other abbreviations see section 16 "Other information".
Substances without classification may have community workplace exposure limits available.**

| |
|--------------------------------------|
| SECTION 4: First aid measures |
|--------------------------------------|

4.1. Description of first aid measures**Inhalation:**

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Do not induce vomiting.

Seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

SKIN: Rash, Urticaria.

After eye contact: Corrosive, may cause permanent damage to eyes (impairment of vision).

Prolonged or repeated skin contact with silver and its salts may cause a blue-gray discoloration of the skin and mucous membranes that is irreversible (Argyria).

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media:**

Carbon dioxide, foam, powder
Fine water spray

Extinguishing media which must not be used for safety reasons:

Do not use water on fires where molten metal is present.

5.2. Special hazards arising from the substance or mixture

High temperatures may produce heavy metal dust, fumes or vapours.
The flux medium will give rise to irritating fumes.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Avoid contact with skin and eyes.
Ensure adequate ventilation.
Wear protective equipment.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Scrape up spilled material and place in a closed container for disposal.
Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Use only in well-ventilated areas.
Avoid skin and eye contact.
Extraction is necessary to remove fumes evolved during reflow.
When using do not eat, drink or smoke.
Wash hands before breaks and immediately after handling the product.
Avoid breathing fumes given out during soldering.
See advice in section 8

Hygiene measures:

Good industrial hygiene practices should be observed.
Do not eat, drink or smoke while working.
After handling solder wash hands with soap and water before eating, drinking or smoking.

7.2. Conditions for safe storage, including any incompatibilities

Refer to Technical Data Sheet

7.3. Specific end use(s)

Solder Paste

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Great Britain

| Ingredient [Regulated substance] | ppm | mg/m ³ | Value type | Short term exposure limit category / Remarks | Regulatory list |
|--|-----|-------------------|-----------------------------------|--|-----------------|
| Silver 7440-22-4 [SILVER (METALLIC)] | | 0,1 | Time Weighted Average (TWA): | | EH40 WEL |
| Silver 7440-22-4 [SILVER, METALLIC] | | 0,1 | Time Weighted Average (TWA): | Indicative | ECTLV |
| Rosin 8050-09-7 [ROSIN-BASED SOLDER FLUX FUME] | | 0,05 | Time Weighted Average (TWA): | | EH40 WEL |
| Rosin 8050-09-7 [ROSIN-BASED SOLDER FLUX FUME] | | 0,15 | Short Term Exposure Limit (STEL): | | EH40 WEL |
| Copper 7440-50-8 [COPPER, FUME] | | 0,2 | Time Weighted Average (TWA): | | EH40 WEL |
| Copper 7440-50-8 [COPPER, INHALABLE DUSTS AND MISTS (AS CU)] | | 1 | Time Weighted Average (TWA): | | EH40 WEL |
| Copper 7440-50-8 [COPPER, INHALABLE DUSTS AND MISTS (AS CU)] | | 2 | Short Term Exposure Limit (STEL): | | EH40 WEL |

Occupational Exposure Limits

Valid for
Ireland

| Ingredient [Regulated substance] | ppm | mg/m ³ | Value type | Short term exposure limit category / Remarks | Regulatory list |
|---|-----|-------------------|-----------------------------------|--|-----------------|
| Tin 7440-31-5 [TIN, METAL (AS SN)] | | 2 | Time Weighted Average (TWA): | Indicative OELV | IR_OEL |
| Tin 7440-31-5 [TIN (INORGANIC COMPOUNDS AS SN)] | | 2 | Time Weighted Average (TWA): | Indicative | ECTLV |
| Silver 7440-22-4 [SILVER (METALLIC)] | | 0,1 | Time Weighted Average (TWA): | Indicative OELV | IR_OEL |
| Silver 7440-22-4 [SILVER, METALLIC] | | 0,1 | Time Weighted Average (TWA): | Indicative | ECTLV |
| Rosin 8050-09-7 [ROSIN CORE SOLDER PYROLYSIS PRODUCTS (AS AIRBORNE TOTAL RESIN ACID)] | | 0,05 | Time Weighted Average (TWA): | | IR_OEL |
| Rosin 8050-09-7 [ROSIN CORE SOLDER PYROLYSIS PRODUCTS (AS AIRBORNE TOTAL RESIN ACID)] | | 0,15 | Short Term Exposure Limit (STEL): | 15 minutes | IR_OEL |
| Copper 7440-50-8 [COPPER (AS CU), DUSTS AND MISTS] | | 1 | Time Weighted Average (TWA): | | IR_OEL |
| Copper 7440-50-8 [COPPER (AS CU), FUME] | | 0,2 | Time Weighted Average (TWA): | | IR_OEL |
| Dodecane-1-thiol | 0,1 | | Time Weighted Average | | IR_OEL |

| | | | | | |
|---------------------------------|--|--|--------|--|--|
| 112-55-0 [DODECYL MERCAPTAN] | | | (TWA): | | |
|---------------------------------|--|--|--------|--|--|

Predicted No-Effect Concentration (PNEC):

| Name on list | Environmental Compartment | Exposure period | Value | | | | Remarks |
|--|------------------------------------|-----------------|-----------------|-----|-----------------|--------|-------------------------------------|
| | | | mg/l | ppm | mg/kg | others | |
| Tin 7440-31-5 | aqua (freshwater) | | | | | | no hazard identified |
| Tin 7440-31-5 | aqua (marine water) | | | | | | no hazard identified |
| Tin 7440-31-5 | sewage treatment plant (STP) | | | | | | no hazard identified |
| Tin 7440-31-5 | sediment (freshwater) | | | | | | no hazard identified |
| Tin 7440-31-5 | sediment (marine water) | | | | | | no hazard identified |
| Tin 7440-31-5 | Air | | | | | | no hazard identified |
| Tin 7440-31-5 | Soil | | | | | | no hazard identified |
| Tin 7440-31-5 | Predator | | | | | | no potential for bioaccumulation |
| 2-(2-Hexyloxyethoxy)ethanol 112-59-4 | aqua (freshwater) | | 1,963 mg/l | | | | |
| 2-(2-Hexyloxyethoxy)ethanol 112-59-4 | aqua (marine water) | | 0,196 mg/l | | | | |
| 2-(2-Hexyloxyethoxy)ethanol 112-59-4 | aqua (intermittent releases) | | 1 mg/l | | | | |
| 2-(2-Hexyloxyethoxy)ethanol 112-59-4 | Sewage treatment plant | | 10 mg/l | | | | |
| 2-(2-Hexyloxyethoxy)ethanol 112-59-4 | sediment (freshwater) | | | | 10,7 mg/kg | | |
| 2-(2-Hexyloxyethoxy)ethanol 112-59-4 | sediment (marine water) | | | | 1,07 mg/kg | | |
| 2-(2-Hexyloxyethoxy)ethanol 112-59-4 | Soil | | | | 0,995 mg/kg | | |
| Silver >= 99,9 % Ag as powder (>100nm<1mm) classified for environment 7440-22-4 | aqua (freshwater) | | 0,00004 mg/l | | | | |
| Silver >= 99,9 % Ag as powder (>100nm<1mm) classified for environment 7440-22-4 | aqua (marine water) | | 0,00086 mg/l | | | | |
| Silver >= 99,9 % Ag as powder (>100nm<1mm) classified for environment 7440-22-4 | sewage treatment plant (STP) | | 0,025 mg/l | | | | |
| Silver >= 99,9 % Ag as powder (>100nm<1mm) classified for environment 7440-22-4 | sediment (freshwater) | | | | 438,13 mg/kg | | |
| Silver >= 99,9 % Ag as powder (>100nm<1mm) classified for environment 7440-22-4 | sediment (marine water) | | | | 438,13 mg/kg | | |
| Silver >= 99,9 % Ag as powder (>100nm<1mm) classified for environment 7440-22-4 | Air | | | | | | no hazard identified |
| Silver >= 99,9 % Ag as powder (>100nm<1mm) classified for environment 7440-22-4 | Soil | | | | 1,41 mg/kg | | |
| rosin 8050-09-7 | aqua (freshwater) | | 0,002 mg/l | | | | |
| rosin 8050-09-7 | aqua (marine water) | | 0,0002 mg/l | | | | |
| rosin 8050-09-7 | sediment (freshwater) | | | | 0,007 mg/kg | | |
| rosin 8050-09-7 | sediment (marine water) | | | | 0,001 mg/kg | | |
| rosin 8050-09-7 | Soil | | | | 0 mg/kg | | |
| rosin 8050-09-7 | sewage treatment plant (STP) | | 1000 mg/l | | | | |
| rosin 8050-09-7 | aqua (intermittent releases) | | 0,016 mg/l | | | | |

| | | | | | | | |
|-------------------------------|------------------------------------|--|------------|--|-----------------|--|--|
| Copper 7440-50-8 | Soil | | | | 65 mg/kg | | |
| Copper 7440-50-8 | sewage treatment plant (STP) | | 230 µg/l | | | | |
| Copper 7440-50-8 | sediment (marine water) | | | | 676 mg/kg | | |
| Copper 7440-50-8 | aqua (freshwater) | | 7,8 µg/l | | | | |
| Copper 7440-50-8 | aqua (marine water) | | 5,2 µg/l | | | | |
| Copper 7440-50-8 | sediment (freshwater) | | | | 87 mg/kg | | |
| 2-Hexyloxyethanol 112-25-4 | aqua (freshwater) | | 0,14 mg/l | | | | |
| 2-Hexyloxyethanol 112-25-4 | aqua (marine water) | | 0,014 mg/l | | | | |
| 2-Hexyloxyethanol 112-25-4 | aqua (intermittent releases) | | 1,4 mg/l | | | | |
| 2-Hexyloxyethanol 112-25-4 | sediment (freshwater) | | | | 0,644 mg/kg | | |
| 2-Hexyloxyethanol 112-25-4 | sediment (marine water) | | | | 0,0644 mg/kg | | |
| 2-Hexyloxyethanol 112-25-4 | Soil | | | | 0,0467 mg/kg | | |
| 2-Hexyloxyethanol 112-25-4 | sewage treatment plant (STP) | | 75 mg/l | | | | |

Derived No-Effect Level (DNEL):

| Name on list | Application Area | Route of Exposure | Health Effect | Exposure Time | Value | Remarks |
|---|--------------------|-------------------|--|---------------|------------------------|----------------------|
| Tin 7440-31-5 | General population | dermal | Long term exposure - systemic effects | | 80 mg/kg | no hazard identified |
| Tin 7440-31-5 | Workers | inhalation | Long term exposure - systemic effects | | 71 mg/m ³ | no hazard identified |
| Tin 7440-31-5 | Workers | dermal | Long term exposure - systemic effects | | 10 mg/kg | no hazard identified |
| Tin 7440-31-5 | General population | inhalation | Long term exposure - systemic effects | | 17 mg/m ³ | no hazard identified |
| Tin 7440-31-5 | General population | oral | Long term exposure - systemic effects | | 5 mg/kg | no hazard identified |
| 2-(2-Hexyloxyethoxy)ethanol 112-59-4 | worker | inhalation | Long term exposure - systemic effects | | 16,3 mg/m ³ | |
| 2-(2-Hexyloxyethoxy)ethanol 112-59-4 | Workers | dermal | Long term exposure - systemic effects | | 50 mg/kg | |
| 2-(2-Hexyloxyethoxy)ethanol 112-59-4 | General population | inhalation | Long term exposure - systemic effects | | 4,1 mg/m ³ | |
| 2-(2-Hexyloxyethoxy)ethanol 112-59-4 | General population | dermal | Long term exposure - systemic effects | | 25 mg/kg | |
| 2-(2-Hexyloxyethoxy)ethanol 112-59-4 | General population | oral | Long term exposure - systemic effects | | 1,25 mg/kg | |
| Silver >= 99,9 % Ag as powder (>100nm<1mm) classified for environment 7440-22-4 | Workers | inhalation | Long term exposure - systemic effects | | 0,1 mg/m ³ | no hazard identified |
| Silver >= 99,9 % Ag as powder (>100nm<1mm) classified for environment 7440-22-4 | General population | inhalation | Long term exposure - systemic effects | | 0,04 mg/m ³ | no hazard identified |
| Silver >= 99,9 % Ag as powder (>100nm<1mm) classified for environment 7440-22-4 | General population | oral | Long term exposure - systemic effects | | 1,2 mg/kg | no hazard identified |
| rosin 8050-09-7 | Workers | inhalation | Long term exposure - local effects | | 10 mg/m ³ | |
| rosin 8050-09-7 | Workers | dermal | Long term exposure - systemic effects | | 2131 mg/kg | |
| rosin 8050-09-7 | General population | dermal | Long term exposure - systemic effects | | 1065 mg/kg | |
| rosin 8050-09-7 | General population | oral | Long term exposure - systemic effects | | 1065 mg/kg | |
| Copper 7440-50-8 | Workers | dermal | Acute/short term exposure - systemic effects | | 273 mg/kg | |
| Copper 7440-50-8 | General population | inhalation | Acute/short term exposure - local effects | | 1 mg/m ³ | |
| Copper 7440-50-8 | General population | inhalation | Long term exposure - local effects | | 1 mg/m ³ | |
| Copper 7440-50-8 | General population | dermal | Acute/short term exposure - systemic effects | | 273 mg/kg | |
| Copper 7440-50-8 | Workers | dermal | Long term exposure - systemic effects | | 137 mg/kg | |
| Copper 7440-50-8 | General population | dermal | Long term exposure - systemic effects | | 137 mg/kg | |
| Copper 7440-50-8 | General population | oral | Long term exposure - | | 0,041 mg/kg | |

| | | | | | | |
|-------------------------------|--------------------|------------|---------------------------------------|--|------------------------|--|
| | | | systemic effects | | | |
| 2-Hexyloxyethanol 112-25-4 | Workers | dermal | Long term exposure - systemic effects | | 9,3 mg/kg | |
| 2-Hexyloxyethanol 112-25-4 | Workers | inhalation | Long term exposure - systemic effects | | 18,4 mg/m ³ | |
| 2-Hexyloxyethanol 112-25-4 | General population | dermal | Long term exposure - systemic effects | | 4,63 mg/kg | |
| 2-Hexyloxyethanol 112-25-4 | General population | inhalation | Long term exposure - systemic effects | | 2,9 mg/m ³ | |

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure adequate ventilation, especially in confined areas.

Extraction is necessary to remove fumes evolved during reflow.

Respiratory protection:

Use only in well-ventilated areas.

In case of insufficient ventilation, wear suitable respiratory equipment.

Suitable respiratory protection:

Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.

Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

paste
solid

Odor

grey
mild

Odour threshold

No data available / Not applicable

| | |
|--|--------------------------------------|
| pH | No data available / Not applicable |
| Melting point | 217 °C (422.6 °F) |
| Solidification temperature | No data available / Not applicable |
| Initial boiling point | 259 °C (498.2 °F) |
| Flash point | 126 °C (258.8 °F)Product is a solid. |
| Evaporation rate | No data available / Not applicable |
| Flammability | No data available / Not applicable |
| Explosive limits | No data available / Not applicable |
| Vapour pressure | < 0,1 hPa |
| Relative vapour density: | No data available / Not applicable |
| Density | 3,68 g/cm ³ |
| () | |
| Bulk density | No data available / Not applicable |
| Solubility | No data available / Not applicable |
| Solubility (qualitative) | No data available / Not applicable |
| Partition coefficient: n-octanol/water | No data available / Not applicable |
| Auto-ignition temperature | No data available / Not applicable |
| Decomposition temperature | No data available / Not applicable |
| Viscosity | 110.000 mPa.s |
| () | |
| Viscosity (kinematic) | No data available / Not applicable |
| Explosive properties | No data available / Not applicable |
| Oxidising properties | No data available / Not applicable |

9.2. Other information

No data available / Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

Solder alloy will react with concentrated nitric acid to produce toxic fumes of nitrogen oxides.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

No decomposition if stored and applied as directed.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 11: Toxicological information

General toxicological information:

Prolonged or repeated contact may cause skin irritation.

11.1. Information on toxicological effects

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Species | Method |
|---|---------------|---------------|---------|--|
| Tin 7440-31-5 | LD50 | > 2.000 mg/kg | rat | OECD Guideline 423 (Acute Oral toxicity) |
| 2-(2-hexyloxyethoxy)ethanol 112-59-4 | LD50 | 3.488 mg/kg | rat | OECD Guideline 401 (Acute Oral Toxicity) |
| Modified rosin 144413-22-9 | LD50 | > 2.000 mg/kg | rat | OECD Guideline 423 (Acute Oral toxicity) |
| Silver >= 99,9 % Ag in powder (>100nm<1mm) 7440-22-4 | LD50 | > 2.000 mg/kg | rat | OECD Guideline 401 (Acute Oral Toxicity) |
| rosin 8050-09-7 | LD50 | 2.800 mg/kg | rat | not specified |
| Copper 7440-50-8 | LD50 | > 2.500 mg/kg | rat | OECD Guideline 423 (Acute Oral toxicity) |
| Dodecane-1-thiol 112-55-0 | LD50 | > 5.000 mg/kg | rat | not specified |
| 2-hexyloxyethanol 112-25-4 | LD50 | 738 mg/kg | rat | OECD Guideline 401 (Acute Oral Toxicity) |

Acute dermal toxicity:

Prolonged or repeated skin contact with silver and its salts may cause a blue-gray discoloration of the skin and mucous membranes that is irreversible (Argyria).

| Hazardous substances CAS-No. | Value type | Value | Species | Method |
|---|---------------|---------------|---------|---|
| Tin 7440-31-5 | LD50 | > 2.000 mg/kg | rat | OECD Guideline 402 (Acute Dermal Toxicity) |
| Modified rosin 144413-22-9 | LD50 | > 2.000 mg/kg | rat | OECD Guideline 402 (Acute Dermal Toxicity) |
| Silver >= 99,9 % Ag in powder (>100nm<1mm) 7440-22-4 | LD50 | > 2.000 mg/kg | rat | OECD Guideline 402 (Acute Dermal Toxicity) |
| rosin 8050-09-7 | LD50 | > 2.000 mg/kg | rat | OECD Guideline 402 (Acute Dermal Toxicity) |
| Copper 7440-50-8 | LD50 | > 2.000 mg/kg | rat | OECD Guideline 402 (Acute Dermal Toxicity) |
| Dodecane-1-thiol 112-55-0 | LD50 | > 2.000 mg/kg | rat | equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity) |
| 2-hexyloxyethanol 112-25-4 | LD50 | 757 mg/kg | rabbit | OECD Guideline 402 (Acute Dermal Toxicity) |

Acute inhalative toxicity:

Fumes evolved at soldering temperatures will irritate the nose, throat and lungs. Prolonged or repeated exposure to flux fumes may result in sensitisation in sensitive workers.

| Hazardous substances CAS-No. | Value type | Value | Test atmosphere | Exposure time | Species | Method |
|------------------------------|------------|-------------|-----------------|---------------|---------|--|
| Copper 7440-50-8 | LC50 | > 5,11 mg/l | dust/mist | 4 h | rat | OECD Guideline 436 (Acute Inhalation Toxicity: Acute Toxic Class (ATC) Method) |

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Exposure time | Species | Method |
|---|-------------------------|---------------|---------|---|
| Tin 7440-31-5 | not irritating | | rabbit | OECD Guideline 404 (Acute Dermal Irritation / Corrosion) |
| 2-(2-hexyloxyethoxy)ethanol 112-59-4 | slightly irritating | 4 h | rabbit | EU Method B.4 (Acute Toxicity: Dermal Irritation / Corrosion) |
| Modified rosin 144413-22-9 | not irritating | 4 h | rabbit | OECD Guideline 404 (Acute Dermal Irritation / Corrosion) |
| rosin 8050-09-7 | not irritating | 4 h | rabbit | OECD Guideline 404 (Acute Dermal Irritation / Corrosion) |
| Copper 7440-50-8 | not irritating | | rabbit | EU Method B.4 (Acute Toxicity: Dermal Irritation / Corrosion) |
| Dodecane-1-thiol 112-55-0 | Category 1C (corrosive) | 4 h | rabbit | OECD Guideline 404 (Acute Dermal Irritation / Corrosion) |
| 2-hexyloxyethanol 112-25-4 | corrosive | | rabbit | not specified |

Serious eye damage/irritation:

Solder pastes may be abrasive to the eyes and the fumes are irritating.

| Hazardous substances CAS-No. | Result | Exposure time | Species | Method |
|---|--|---------------|---------|---|
| Tin 7440-31-5 | not irritating | | rabbit | OECD Guideline 405 (Acute Eye Irritation / Corrosion) |
| 2-(2-hexyloxyethoxy)ethanol 112-59-4 | Category 1 (irreversible effects on the eye) | | rabbit | not specified |
| Modified rosin 144413-22-9 | moderately irritating | 24 h | rabbit | OECD Guideline 405 (Acute Eye Irritation / Corrosion) |
| rosin 8050-09-7 | not irritating | | rabbit | OECD Guideline 405 (Acute Eye Irritation / Corrosion) |
| Copper 7440-50-8 | not irritating | | rabbit | OECD Guideline 405 (Acute Eye Irritation / Corrosion) |
| 2-hexyloxyethanol 112-25-4 | highly irritating | | rabbit | OECD Guideline 405 (Acute Eye Irritation / Corrosion) |

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Test type | Species | Method |
|---|-----------------|------------------------------------|------------|---|
| 2-(2-hexyloxyethoxy)ethanol 112-59-4 | not sensitising | Mouse local lymphnode assay (LLNA) | mouse | OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay) |
| Modified rosin 144413-22-9 | not sensitising | Guinea pig maximisation test | guinea pig | OECD Guideline 406 (Skin Sensitisation) |
| Copper 7440-50-8 | not sensitising | Guinea pig maximisation test | guinea pig | EU Method B.6 (Skin Sensitisation) |
| Dodecane-1-thiol 112-55-0 | sensitising | Mouse local lymphnode assay (LLNA) | mouse | OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay) |

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Type of study / Route of administration | Metabolic activation / Exposure time | Species | Method |
|---|----------|--|--|---------|---|
| Tin 7440-31-5 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| Tin 7440-31-5 | negative | in vitro mammalian chromosome aberration test | with and without | | OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) |
| Tin 7440-31-5 | negative | mammalian cell gene mutation assay | with and without | | OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) |
| 2-(2- hexyloxyethoxy)ethanol 112-59-4 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| 2-(2- hexyloxyethoxy)ethanol 112-59-4 | negative | sister chromatid exchange assay in mammalian cells | with and without | | OECD Guideline 479 (Genetic Toxicology: In Vitro Sister Chromatid Exchange Assay in Mammalian Cells) |
| 2-(2- hexyloxyethoxy)ethanol 112-59-4 | negative | mammalian cell gene mutation assay | with and without | | OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) |
| Modified rosin 144413-22-9 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| Modified rosin 144413-22-9 | negative | in vitro mammalian chromosome aberration test | with and without | | OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) |
| Silver >= 99,9 % Ag in powder (>100nm<1mm) 7440-22-4 | negative | in vitro mammalian cell micronucleus test | with and without | | OECD Guideline 487 (In vitro Mammalian Cell Micronucleus Test) |
| rosin 8050-09-7 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| Copper 7440-50-8 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| Dodecane-1-thiol 112-55-0 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| Dodecane-1-thiol 112-55-0 | negative | mammalian cell gene mutation assay | with and without | | OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) |
| 2-hexyloxyethanol 112-25-4 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| 2-hexyloxyethanol 112-25-4 | negative | in vitro mammalian chromosome aberration test | with and without | | OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) |
| 2-hexyloxyethanol 112-25-4 | negative | mammalian cell gene mutation assay | with and without | | OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) |
| 2-(2- hexyloxyethoxy)ethanol 112-59-4 | negative | oral: gavage | | rat | OECD Guideline 475 (Mammalian Bone Marrow Chromosome Aberration Test) |
| Copper 7440-50-8 | negative | oral: gavage | | mouse | EU Method B.12 (Mutagenicity) |
| Copper 7440-50-8 | negative | oral: gavage | | rat | equivalent or similar to OECD Guideline 486 (Unscheduled DNA Synthesis (UDS) Test with Mammalian Liver Cells in vivo) |
| Dodecane-1-thiol 112-55-0 | negative | oral: gavage | | mouse | OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test) |

Carcinogenicity

No data available.

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result / Value | Test type | Route of application | Species | Method |
|---|---|-----------------------------|----------------------------|---------|---|
| Tin 7440-31-5 | NOAEL P > 1.000 mg/kg | | oral: gavage | rat | OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test) |
| 2-(2- hexyloxyethoxy)ethanol 112-59-4 | NOAEL P >= 1.000 mg/kg NOAEL F1 >= 1.000 mg/kg | screening | oral: feed | rat | OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test) |
| Copper 7440-50-8 | NOAEL P 1500 ppm NOAEL F1 1000 ppm NOAEL F2 1000 ppm | two- generation study | oral: feed | rat | OECD Guideline 416 (Two- Generation Reproduction Toxicity Study) |
| Copper 7440-50-8 | NOAEL P 1000 ppm NOAEL F1 1000 ppm NOAEL F2 1000 ppm | two- generation study | oral: feed | rat | OECD Guideline 416 (Two- Generation Reproduction Toxicity Study) |
| 2-hexyloxyethanol 112-25-4 | NOAEL P 720 mg/kg NOAEL F1 720 mg/kg NOAEL F2 720 mg/kg | Two generation study | oral: drinking water | mouse | not specified |

STOT-single exposure:

No data available.

STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result / Value | Route of application | Exposure time / Frequency of treatment | Species | Method |
|---|---------------------|-------------------------|--|---------|---|
| Tin 7440-31-5 | NOAEL > 1.000 mg/kg | oral: gavage | 28 days daily | rat | OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents) |
| 2-(2- hexyloxyethoxy)ethanol 112-59-4 | NOAEL 300 mg/kg | oral: feed | 33-52 d daily | rat | OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test) |
| 2-(2- hexyloxyethoxy)ethanol 112-59-4 | NOAEL 41 ppm | inhalation: vapour | 14 w 6 h/d | rat | equivalent or similar to OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day) |
| Modified rosin 144413-22-9 | NOAEL 150 mg/kg | oral: gavage | 28 d daily | rat | OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents) |
| Copper 7440-50-8 | NOAEL 1000 ppm | oral: feed | 92 d 7 d/w | rat | EU Method B.26 (Sub- Chronic Oral Toxicity Test: Repeated Dose 90- Day Oral Toxicity Study in Rodents) |
| 2-hexyloxyethanol 112-25-4 | NOAEL 222 mg/kg | dermal | 11 d 6 h/d | rabbit | OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study) |
| 2-hexyloxyethanol 112-25-4 | NOAEL 41 ppm | inhalation: vapour | 14 w 6 h/d | rat | OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day) |

Aspiration hazard:

No data available.

SECTION 12: Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|--|---------------|--------------|---------------|---------------------|--|
| Tin 7440-31-5 | LC50 | | 96 h | Pimephales promelas | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| 2-(2-hexyloxyethoxy)ethanol 112-59-4 | LC50 | 200 mg/l | 96 h | Pimephales promelas | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| Modified rosin 144413-22-9 | LC50 | | 96 h | Oncorhynchus mykiss | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| Silver >= 99,9 % Ag in powder (>100nm<1mm) 7440-22-4 | LC50 | 0,0012 mg/l | 96 h | Pimephales promelas | other guideline: |
| Silver >= 99,9 % Ag in powder (>100nm<1mm) 7440-22-4 | EC10 | 0,00019 mg/l | 217 d | Salmo trutta | OECD Guideline 210 (fish early lite stage toxicity test) |
| rosin 8050-09-7 | LC50 | | 96 h | Pimephales promelas | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| Copper 7440-50-8 | LC50 | 0,193 mg/l | 96 h | Pimephales promelas | other guideline: |
| Copper 7440-50-8 | NOEC | 0,188 mg/l | 30 d | Perca fluviatilis | OECD Guideline 204 (Fish, Prolonged Toxicity Test: 14-day Study) |
| Dodecane-1-thiol 112-55-0 | LC50 | | 96 h | Oncorhynchus mykiss | EPA OTS 797.1400 (Fish Acute Toxicity Test) |
| 2-hexyloxyethanol 112-25-4 | LC50 | 140 mg/l | 96 h | Pimephales promelas | OECD Guideline 203 (Fish, Acute Toxicity Test) |

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|--|---------------|----------------|---------------|---------------|--|
| 2-(2-hexyloxyethoxy)ethanol 112-59-4 | EC50 | > 100 mg/l | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| Modified rosin 144413-22-9 | EC50 | | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| Silver >= 99,9 % Ag in powder (>100nm<1mm) 7440-22-4 | EC50 | 0,00022 mg/l | 48 h | Daphnia magna | other guideline: |
| rosin 8050-09-7 | EL50 | | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| Copper 7440-50-8 | EC50 | > 0,1 - 1 mg/l | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| Dodecane-1-thiol 112-55-0 | EC50 | | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| 2-hexyloxyethanol 112-25-4 | EC50 | 150 mg/l | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |

Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|---------------------------------|---------------|-------|---------------|--------------------|------------------|
| Tin 7440-31-5 | NOEC | | 7 d | Ceriodaphnia dubia | other guideline: |

| | | | | | |
|---|------|----------------|------|--------------------|--|
| 2-(2-hexyloxyethoxy)ethanol 112-59-4 | EC10 | 19,63 mg/l | 7 d | Ceriodaphnia dubia | other guideline: |
| Silver >= 99,9 % Ag in powder (>100nm<1mm) 7440-22-4 | NOEC | 0,00032 mg/l | 21 d | Daphnia magna | EPA OPPTS 850.1300 (Daphnid Chronic Toxicity Test) |
| Copper 7440-50-8 | NOEC | > 0,1 - 1 mg/l | 21 d | Daphnia magna | OECD 211 (Daphnia magna, Reproduction Test) |

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|---|---------------|----------------|---------------|---|--|
| Tin 7440-31-5 | EC50 | | 72 h | Pseudokirchneriella subcapitata | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Tin 7440-31-5 | NOEC | | 72 h | Pseudokirchneriella subcapitata | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| 2-(2-hexyloxyethoxy)ethanol 112-59-4 | EC50 | > 100 mg/l | 96 h | Scenedesmus subspicatus (new name: Desmodesmus subspicatus) | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Modified rosin 144413-22-9 | EC50 | | 72 h | Scenedesmus subspicatus (new name: Desmodesmus subspicatus) | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Modified rosin 144413-22-9 | NOEC | | 72 h | Scenedesmus subspicatus (new name: Desmodesmus subspicatus) | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Silver >= 99,9 % Ag in powder (>100nm<1mm) 7440-22-4 | EC10 | 0,00016 mg/l | 15 d | other: | other guideline: |
| rosin 8050-09-7 | EL50 | | 72 h | Pseudokirchneriella subcapitata | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| rosin 8050-09-7 | NOELR | | 72 h | Pseudokirchneriella subcapitata | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Copper 7440-50-8 | EC50 | > 0,1 - 1 mg/l | 72 h | not specified | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Copper 7440-50-8 | NOEC | > 0,1 - 1 mg/l | 72 h | not specified | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Dodecane-1-thiol 112-55-0 | EC50 | < 0,0145 mg/l | 72 h | Pseudokirchneriella subcapitata | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Dodecane-1-thiol 112-55-0 | EC10 | < 0,0145 mg/l | 72 h | Pseudokirchneriella subcapitata | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| 2-hexyloxyethanol 112-25-4 | EC50 | 70 mg/l | 72 h | Scenedesmus subspicatus (new name: Desmodesmus subspicatus) | OECD Guideline 201 (Alga, Growth Inhibition Test) |

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|---------------------------------|---------------|----------------|---------------|--|--|
| Tin 7440-31-5 | EC50 | | 3 h | activated sludge of a predominantly domestic sewage | OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test) |
| Modified rosin 144413-22-9 | NOEC | | 3 h | activated sludge | OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test) |
| rosin 8050-09-7 | EC20 | | 3 h | activated sludge of a predominantly domestic sewage | OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test) |
| Copper 7440-50-8 | EC50 | > 0,1 - 1 mg/l | 3 h | activated sludge | OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test) |

12.2. Persistence and degradability

The product is not biodegradable.

| Hazardous substances CAS-No. | Result | Test type | Degradability | Exposure time | Method |
|---|----------------------------|---------------|---------------|---------------|--|
| 2-(2-hexyloxyethoxy)ethanol 112-59-4 | readily biodegradable | aerobic | > 90 - 100 % | 15 d | OECD Guideline 301 A (new version) (Ready Biodegradability: DOC Die Away Test) |
| Modified rosin 144413-22-9 | not readily biodegradable. | aerobic | 25 % | 28 day | OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test) |
| rosin 8050-09-7 | readily biodegradable | aerobic | 71 % | 28 d | OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test) |
| Copper 7440-50-8 | Rapidly degradable | not specified | > 60 % | 28 d | OECD 301 A - F |
| Dodecane-1-thiol 112-55-0 | not readily biodegradable. | aerobic | 39,2 % | 28 d | OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test) |
| 2-hexyloxyethanol 112-25-4 | readily biodegradable | no data | 86 % | 28 d | OECD Guideline 301 E (Ready biodegradability: Modified OECD Screening Test) |
| 2-hexyloxyethanol 112-25-4 | | no data | 97 % | 28 d | OECD Guideline 302 B (Inherent biodegradability: Zahn-Wellens/EMPA Test) |

12.3. Bioaccumulative potential

| Hazardous substances CAS-No. | Bioconcentration factor (BCF) | Exposure time | Temperature | Species | Method |
|--|-------------------------------|---------------|-------------|-----------------|------------------|
| Silver >= 99,9 % Ag in powder (>100nm<1mm) 7440-22-4 | 70 | 42 d | 20 °C | Cyprinus carpio | other guideline: |

12.4. Mobility in soil

The product is insoluble and sinks in water.

| Hazardous substances CAS-No. | LogPow | Temperature | Method |
|---|-----------|-------------|---|
| 2-(2-hexyloxyethoxy)ethanol 112-59-4 | 1,7 | | not specified |
| Modified rosin 144413-22-9 | > 6 | | EU Method A.8 (Partition Coefficient) |
| rosin 8050-09-7 | > 3 - 6,2 | | OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method) |
| Dodecane-1-thiol 112-55-0 | > 6,5 | 25 °C | OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method) |

12.5. Results of PBT and vPvB assessment

| Hazardous substances CAS-No. | PBT / vPvB |
|--|---|
| Tin 7440-31-5 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| 2-(2-hexyloxyethoxy)ethanol 112-59-4 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| Silver >= 99,9 % Ag in powder (>100nm<1mm) 7440-22-4 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| rosin 8050-09-7 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| Copper 7440-50-8 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| 2-hexyloxyethanol 112-25-4 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Wherever possible unwanted solder pastes should be recycled for recovery of metal.
Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.
Dispose of as unused product.

Waste code

06 04 05 - wastes containing other heavy metals

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information**14.1. UN number**

| | |
|------|------|
| ADR | 3077 |
| RID | 3077 |
| ADN | 3077 |
| IMDG | 3077 |
| IATA | 3077 |

14.2. UN proper shipping name

| | |
|------|--|
| ADR | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (N-Dodecyl-Mercaptan) |
| RID | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (N-Dodecyl-Mercaptan) |
| ADN | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (N-Dodecyl-Mercaptan) |
| IMDG | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (N-Dodecyl-Mercaptan) |
| IATA | Environmentally hazardous substance, solid, n.o.s. (N-Dodecyl-Mercaptan) |

14.3. Transport hazard class(es)

| | |
|------|---|
| ADR | 9 |
| RID | 9 |
| ADN | 9 |
| IMDG | 9 |
| IATA | 9 |

14.4. Packing group

| | |
|------|-----|
| ADR | III |
| RID | III |
| ADN | III |
| IMDG | III |
| IATA | III |

14.5. Environmental hazards

| | |
|------|------------------|
| ADR | not applicable |
| RID | not applicable |
| ADN | not applicable |
| IMDG | Marine pollutant |
| IATA | not applicable |

14.6. Special precautions for user

| | |
|-----|----------------|
| ADR | not applicable |
|-----|----------------|

| | |
|------|----------------|
| | Tunnelcode: |
| RID | not applicable |
| ADN | not applicable |
| IMDG | not applicable |
| IATA | not applicable |

The transport classifications in this section apply generally to packed and bulk goods alike. For containers with a net volume of no more than 5 L for liquid substances or a net mass of no more than 5 kg for solid substances per individual or inner package, the exemptions SP 375 (ADR), 197 (IATA), 969 (IMDG) may be applied, which can result in a deviation from the transport classification for packed goods.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC content < 3 %
(2010/75/EC)

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

National regulations/information (Great Britain):

| | |
|---------|--|
| Remarks | <p>The Health & Safety at Work Act 1974. The Control of Substances Hazardous to Health Regulations. L5:General Approved Code of Practice to the COSHH Regulations. HS(G)97:A Step by Step Guide to the COSHH Regulations. HS(G)193: COSHH essentials: Easy steps to control chemicals. IND (G)248L:Solder fume and you. IND(G)249L:Controlling health risks from rosin (colophony) based solder fluxes. The Control of Lead at Work Regulations. L132:Control of Lead at Work: Approved Code of Practice and Guidance. Employees should be under medical surveillance if the risk assessment made under the Control of Lead at Work Regulations indicates they are likely to be exposed to significant concentrations of lead, or if an Employment Medical Advisor or appointed doctor so certifies. A woman employed on work which exposes her to lead should notify her employer as soon as possible if she becomes pregnant. The Employment Medical Advisor / Appointed Doctor should be informed of the pregnancy. Under the Management of Health and Safety at Work Regulations, employers are required to assess the particular risks to health at work of pregnant workers and workers who have recently given birth or who are breast feeding.</p> |
|---------|--|

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

- H302 Harmful if swallowed.
- H311 Toxic in contact with skin.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- H413 May cause long lasting harmful effects to aquatic life.

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.