

Within Series Adaptor 33_N-Q50-0-14/13-_N

Description

Adaptor plug/jack
N plug (male) / N Quick-mate jack (female)

Quick-mate coupling mechanism, pluggable without tightening
For Test & Measurement applications

Interface standards
Series N - IEC 61169-16_MIL-STD-348A/304_CECC 22210
Series N Quick-mate - HUBER+SUHNER Quick-mate



Technical Data

Electrical Data

Impedance	50 Ω	
Interface frequency max.	11 GHz	
Frequency range	DC to 4 GHz	4 to 8 GHz
Return loss	≥ 24 dB	≥ 20 dB

Mechanical Data

Number of matings	500
Weight	0.0427 kg

Environmental Data

Operating temperature	-65 °C to 165 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

Material Data

Interface - N plug (male)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer contact	Brass	SUCOPLATE (R) / SUCOPRO Plating
Body	Brass	SUCOPLATE (R) / SUCOPRO Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	VMQ (Silicone rubber)	

Interface - N Quick-mate jack (female)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer contact	Brass	SUCOPLATE (R) / SUCOPRO Plating
Body	Brass	SUCOPLATE (R) / SUCOPRO Plating
Insulator	PFA / PTFE	

Related Documents

Outline drawing	DOU-00013719
-----------------	--------------

Ordering Information

Single package	33_N-Q50-0-14/13-_NE
----------------	----------------------

Remarks

Durability of QUICK MATE interface: 5000 matings

Within Series Adaptor

33_N-Q50-0-14/13-_N