

Specifications

Connector Body Style **Coaxial Termination** Connector Mounting Coaxial Cable Types

- : Straight Jack
- : Solder
- : Cable
- : RG-405

Electrical Specifications

: Beryllium Copper per ASTM B196 UNS C17300 : PTFE per ASTM D1457 and ASTM D1710

Frequency Range Nominal Impedance Voltage Rating VSWR

: DC 26.5GHz : 50Ω : 335V Max. : 1.16 Max. @ 18GHz 1.2 Max. @ 26.5GHz

Material Specifications

Bodies Centre Contact Insulation

Mechanical Specifications

Interface in accordance with Cable Attachment

: MIL-STD-348A : Outer: Solder; Inner: Solder


Environmental Specification

Operating Temperature

: -65°C to +165°C

: Brass per JIS-C3604

Diagram



Dimensions : Millimetres (Inches)

No.	Description	Material	Finish
1	Body	Brass	Gold 3µ" Min.
2	Insulation	PTFE	-
3	Centre Contact	Beryllium Copper	Gold 50µ" Min.

Part Number Table

Description	Part Number
Straight Jack, Solder, 50Ω , RG-405	MC002925

6.600(.260)

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro

