

# TECHNICAL DATA

3821390

Manufacturers of a wide range of electrical and electronic servicing products, including cleaners, solvents, lubricants, greases, freezers, air dusters, lacquers, coatings and de-soldering aids.



## AERO-KLENE 50 ELECTRONIC CLEANING SOLVENT

AERO-KLENE 50 is an electronic cleaning solvent which is ideal for safe and effective cleaning of electronic, electrical and other delicate components.

### APPLICATIONS

Ideal for quick and efficient cleaning of:

- \* PCBs
- \* Relays
- \* Electrical and Electronic Assemblies
- \* Precision Instruments
- \* Tape Heads
- \* Communications Equipment
- \* Condensers
- \* Business Machines
- \* Transistors

Safe to use on all plastic and rubber surfaces, the rapid evaporation of Aero-Klene 50 ensures that no residues are left on the treated equipment.

N.B. Not for use on live equipment.

### TECHNICAL DATA

Appearance	: Clear, colourless liquid
Odour	: Hydrocarbon solvent
SG @ 25°C	: 0.67
Pressure @ 25°C	: 3 Bar
Discharge rate	: 1.1 g/sec
Solubility	: Miscible with most organic solvents
Compatibility	: Safe to use on plastics and rubber
Flammability	: Classified as extremely flammable under CHIP Regulations
Flashpoint	: Not applicable in sealed aerosol
Packaging	: 200 ml aerosol

# TECHNICAL DATA

Manufacturers of a wide range of electrical and electronic servicing products, including cleaners, solvents, lubricants, greases, freezers, air dusters, lacquers, coatings and de-soldering aids.



## AERO-KLENE 50 ELECTRONIC CLEANING SOLVENT

**AERO-KLENE 50** is an electronic cleaning solvent which is ideal for safe and effective cleaning of electronic, electrical and other delicate components.

### APPLICATIONS

Ideal for quick and efficient cleaning of:

- \* PCBs
- \* Electrical and Electronic Assemblies
- \* Tape Heads
- \* Condensers
- \* Transistors
- \* Relays
- \* Precision Instruments
- \* Communications Equipment
- \* Business Machines

Safe to use on all plastic and rubber surfaces, the rapid evaporation of Aero-Klene 50 ensures that no residues are left on the treated equipment.

**N.B. Not for use on live equipment.**

### TECHNICAL DATA

Appearance	:	Clear, colourless liquid
Odour	:	Hydrocarbon solvent
SG @ 25°C	:	0.67
Pressure @ 25°C	:	3 Bar
Discharge rate	:	1.1 g/sec
Solubility	:	Miscible with most organic solvents
Compatibility	:	Safe to use on plastics and rubber
Flammability	:	Classified as extremely flammable under CHIP Regulations
Flashpoint	:	Not applicable in sealed aerosol
Packaging	:	200 ml aerosol