

Tradesman 2 C/W Twin A1P2 Cartridges

Also Known As Filterjet

Unit Conformity	Meets the requirements of EN 405. EC Type Examination (CE) Certificate Number 1198 issued by BSi Product Certification, in accordance with the PPE Directive 89/686/EEC.
Cartridge Performance:	Offers an assigned protection factor (APF) of 10 x Occupational Exposure Standard (OES) for organic vapours, gases and very fine dusts, fibres, fumes and aqueous mists.
Materials:	Mask Body – Medical Grade PVC Harness Fittings – Nylon Harness Straps – Elastic Exhale Valve Holder – ABS Exhale Valve – Latex Rubber Cartridge Outer – High Impact Polystyrene Cartridge Inner – Activated Carbon Pre-Filter Material – Man Made Media Diaphragm – Rubber
Instructions For Use:	Ensure that the mask is fitted properly and in accordance with the instructions supplied. Ensure that the mask chosen is suitable for the intended purpose.
Cleaning Instructions:	Wipe with damp cloth soaked in mild detergent solution, being careful not to get any liquid inside the cartridge. DO NOT USE abrasive substances or solvents.
Maintenance:	Store in an airtight container, away from direct sunlight, chemicals or extremes of temperature. Dispose of unit after 28 days of use.
Limitations Of Use:	The mask, when in contact with the skin may cause allergic reactions to susceptible individuals. If this occurs leave the hazard area remove mask and seek medical advice. Protection will only be offered if the mask is fitted correctly. This mask is not designed to be worn by people with facial hair.