



Safety Data Sheet according to Regulation (EC) No 1907/2006

Page 1 of 15

LOCTITE SF 7458 known as Loctite 7458

SDS No. : 173251
V007.0

Revision: 18.04.2019

printing date: 14.07.2020

Replaces version from: 14.09.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE SF 7458 known as Loctite 7458

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Primer

1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Adhesives

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

Fax-no.: +44 (1442) 278071

ua-productsafety.uk@henkel.com

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Flammable liquids	Category 2
H225 Highly flammable liquid and vapor.	
Skin irritation	Category 2
H315 Causes skin irritation.	
Specific target organ toxicity - single exposure	Category 3
H336 May cause drowsiness or dizziness.	
Target organ: Central nervous system	
Aspiration hazard	Category 1
H304 May be fatal if swallowed and enters airways.	
Chronic hazards to the aquatic environment	Category 2
H411 Toxic to aquatic life with long lasting effects.	

|| **Serious eye irritation** **Category 2**

|| **H319 Causes serious eye irritation.**

2.2. Label elements

Label elements (CLP):

Hazard pictogram:**Contains**

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Signal word:

Danger

Hazard statement:

H225 Highly flammable liquid and vapor.
 H304 May be fatal if swallowed and enters airways.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.
 H411 Toxic to aquatic life with long lasting effects.

Precautionary statement:
Prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
 No smoking.
 P273 Avoid release to the environment.
 P261 Avoid breathing vapors.

Precautionary statement:
Response

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor.
 P331 Do NOT induce vomiting.
 P302+P352 IF ON SKIN: Wash with plenty of soap and water.
 P337+P313 If eye irritation persists: Get medical advice/attention.

Precautionary statement:
Storage

P403+P235 Store in a well-ventilated place. Keep cool.

2.3. Other hazards

None if used properly.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****General chemical description:**

Primer

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	265-151-9 01-2119475515-33	75- < 100 %	Asp. Tox. 1 H304 Skin Irrit. 2 H315 Flam. Liq. 2 H225 STOT SE 3; Inhalation H336 Aquatic Chronic 2 H411
Cyclohexanone 108-94-1	203-631-1 01-2119453616-35	2,5- < 10 %	Flam. Liq. 3 H226 Acute Tox. 4; Oral H302 Acute Tox. 4; Dermal H312 Acute Tox. 4 H332 Eye Dam. 1 H318 Skin Irrit. 2 H315
3,5-Dichloropyridine 2457-47-8	219-537-9	1- < 2,5 %	Eye Irrit. 2 H319 STOT SE 3 H335 Skin Irrit. 2 H315

**For full text of the H - statements and other abbreviations see section 16 "Other information".
Substances without classification may have community workplace exposure limits available.**

SECTION 4: First aid measures

4.1. Description of first aid measures**Inhalation:**

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.
Seek medical advice.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

Ingestion:

Rinse out mouth, drink 1-2 glasses of water, do not induce vomiting.
Seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

SKIN: Redness, inflammation.

EYE: Irritation, conjunctivitis.

Vapors may cause drowsiness and dizziness.

ASPIRATION: Coughing, shortness of breath, nausea. Delayed effect: bronchopneumonia or pulmonary oedema

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

Small amounts of liquid aspirated into the respiratory system during ingestion or from vomiting may cause bronchopneumonia or pulmonary oedema.

Do not induce vomiting.

Seek medical attention from a specialist.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media:**

Carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

None known

5.2. Special hazards arising from the substance or mixture

Cool aerosol containers with jet of water. Containers may explode.

Oxides of carbon.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Avoid skin and eye contact.

Keep away from sources of ignition.

6.2. Environmental precautions

Do not let product enter drains.

6.3. Methods and material for containment and cleaning up

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Use only in well-ventilated areas.

Avoid skin and eye contact.

Keep away from sources of ignition - no smoking.

See advice in section 8

Hygiene measures:

Good industrial hygiene practices should be observed.

Do not eat, drink or smoke while working.

Wash hands before work breaks and after finishing work.

7.2. Conditions for safe storage, including any incompatibilities

Store in a cool, well-ventilated place.

Do not expose to direct heat.

7.3. Specific end use(s)

Primer

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Great Britain

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Cyclohexanone 108-94-1 [CYCLOHEXANONE]			Skin designation:	Can be absorbed through the skin.	ECLTV
Cyclohexanone 108-94-1 [CYCLOHEXANONE]			Skin designation:	Can be absorbed through the skin.	EH40 WEL
Cyclohexanone 108-94-1 [CYCLOHEXANONE]	20	82	Short Term Exposure Limit (STEL):		EH40 WEL
Cyclohexanone 108-94-1 [CYCLOHEXANONE]	10	41	Time Weighted Average (TWA):		EH40 WEL
Cyclohexanone 108-94-1 [CYCLOHEXANONE]	10	40,8	Time Weighted Average (TWA):	Indicative	ECLTV
Cyclohexanone 108-94-1 [CYCLOHEXANONE]	20	81,6	Short Term Exposure Limit (STEL):	Indicative	ECLTV

Occupational Exposure Limits

Valid for
Ireland

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Cyclohexanone 108-94-1 [CYCLOHEXANONE]			Skin designation:	Can be absorbed through the skin.	ECLTV
Cyclohexanone 108-94-1 [CYCLOHEXANONE]	10	40,8	Time Weighted Average (TWA):	Indicative OELV	IR_OEL
Cyclohexanone 108-94-1 [CYCLOHEXANONE]			Skin designation:	Can be absorbed through the skin.	IR_OEL
Cyclohexanone 108-94-1 [CYCLOHEXANONE]	10	40,8	Time Weighted Average (TWA):	Indicative	ECLTV
Cyclohexanone 108-94-1 [CYCLOHEXANONE]	20	81,6	Short Term Exposure Limit (STEL):	Indicative	ECLTV
Cyclohexanone 108-94-1 [CYCLOHEXANONE]	20	81,6	Short Term Exposure Limit (STEL):	15 minutes Indicative OELV	IR_OEL

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Cyclohexanone 108-94-1	aqua (freshwater)		0,0329 mg/l				
Cyclohexanone 108-94-1	aqua (marine water)		0,00329 mg/l				
Cyclohexanone 108-94-1	sediment (freshwater)				0,095 mg/kg		
Cyclohexanone 108-94-1	Soil				0,0143 mg/kg		
Cyclohexanone 108-94-1	sewage treatment plant (STP)		10 mg/l				
Cyclohexanone 108-94-1	aqua (intermittent releases)		0,329 mg/l				
Cyclohexanone 108-94-1	sediment (marine water)				0,0512 mg/kg		

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	Workers	dermal	Long term exposure - systemic effects		300 mg/kg	
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	Workers	Inhalation	Long term exposure - systemic effects		2085 mg/m ³	
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	General population	dermal	Long term exposure - systemic effects		149 mg/kg	
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	General population	oral	Long term exposure - systemic effects		149 mg/kg	
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	General population	Inhalation	Long term exposure - systemic effects		447 mg/m ³	
Cyclohexanone 108-94-1	Workers	Inhalation	Acute/short term exposure - systemic effects		80 mg/m ³	
Cyclohexanone 108-94-1	Workers	dermal	Acute/short term exposure - systemic effects		4 mg/kg	
Cyclohexanone 108-94-1	Workers	Inhalation	Acute/short term exposure - local effects		80 mg/m ³	
Cyclohexanone 108-94-1	Workers	dermal	Long term exposure - systemic effects		4 mg/kg	
Cyclohexanone 108-94-1	Workers	Inhalation	Long term exposure - systemic effects		40 mg/m ³	
Cyclohexanone 108-94-1	Workers	Inhalation	Long term exposure - local effects		40 mg/m ³	
Cyclohexanone 108-94-1	General population	dermal	Acute/short term exposure - systemic effects		1 mg/kg	
Cyclohexanone 108-94-1	General population	Inhalation	Acute/short term exposure - systemic effects		20 mg/m ³	
Cyclohexanone 108-94-1	General population	oral	Acute/short term exposure - systemic effects		1,5 mg/kg	
Cyclohexanone 108-94-1	General population	Inhalation	Acute/short term exposure - local effects		40 mg/m ³	
Cyclohexanone 108-94-1	General population	dermal	Long term exposure - systemic effects		1 mg/kg	
Cyclohexanone 108-94-1	General population	Inhalation	Long term exposure - systemic effects		10 mg/m ³	
Cyclohexanone 108-94-1	General population	oral	Long term exposure - systemic effects		1,5 mg/kg	
Cyclohexanone 108-94-1	General population	Inhalation	Long term exposure - local effects		20 mg/m ³	
Cyclohexanone 108-94-1	Workers	dermal	Acute/short term exposure - local effects		10 mg/kg	

Biological Exposure Indices:

Ingredient [Regulated substance]	Parameters	Biological specimen	Sampling time	Conc.	Basis of biol. exposure index	Remark	Additional Information
Cyclohexanone 108-94-1 [CYCLOHEXANONE]	cyclohexanol	Creatinine in urine	Sampling time: End of shift.		UKEH40BMG V		

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Wear protective glasses.

Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	liquid liquid colourless
Odour threshold	No data available / Not applicable
pH	Not determined
Melting point	No data available / Not applicable
Solidification temperature	No data available / Not applicable
Initial boiling point	83,0 - 105,0 °C (181.4 - 221 °F)
Flash point	-5 °C (23 °F)
Evaporation rate	No data available / Not applicable
Flammability	No data available / Not applicable
Explosive limits	No data available / Not applicable

Vapour pressure (20 °C (68 °F))	35,5 mbar
Relative vapour density:	No data available / Not applicable
Density (ρ)	0,72 g/cm ³
Bulk density	No data available / Not applicable
Solubility	No data available / Not applicable
Solubility (qualitative) (Solvent: Water)	Insoluble
Partition coefficient: n-octanol/water	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Decomposition temperature	No data available / Not applicable
Viscosity	No data available / Not applicable
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Oxidising properties	No data available / Not applicable

9.2. Other information

No data available / Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

Acids.

Strong oxidizing agents.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Stable under normal conditions of storage and use.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

carbon oxides.

SECTION 11: Toxicological information

11.1. Information on toxicological effects**Acute oral toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	LD50	> 5.840 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Cyclohexanone 108-94-1	LD50	800 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	LD50	> 2.920 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Cyclohexanone 108-94-1	LD50	1.100 mg/kg	rabbit	not specified

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	LC50	> 23,3 mg/l	vapour	4 h	rat	equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity)
Cyclohexanone 108-94-1	LC50	11 mg/l	vapour	4 h	rat	not specified

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Cyclohexanone 108-94-1	irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	not irritating		rabbit	other guideline:
Cyclohexanone 108-94-1	corrosive	24 h	rabbit	BASF Test
Cyclohexanone 108-94-1	corrosive	3,5 min	Chicken, egg, in vitro assay	Hen's Egg Test – Chorioallantoic Membrane (HET-CAM)

Respiratory or skin sensitization:

No data available.

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Cyclohexanone 108-94-1	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		not specified

Carcinogenicity

No data available.

Reproductive toxicity:

No data available.

STOT-single exposure:

No data available.

STOT-repeated exposure::

No data available.

Aspiration hazard:

The mixture is classified based on Viscosity data.

Hazardous substances CAS-No.	Viscosity (kinematic) Value	Temperature	Method	Remarks
Hydrocarbons, C7, n- alkanes, isoalkanes, cyclics 64742-49-0	0,5 mm ² /s	20 °C	not specified	

SECTION 12: Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Cyclohexanone 108-94-1	LC50	527 - 732 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	EC50	3 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Cyclohexanone 108-94-1	EC50	820 mg/l	24 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	NOEC	0,17 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	EL50	29 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	NOELR	6,3 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Cyclohexanone 108-94-1	EC50	> 100 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
Cyclohexanone 108-94-1	NOEC	100 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Cyclohexanone 108-94-1	EC50	> 1.000 mg/l	30 min	activated sludge, domestic	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

12.2. Persistence and degradability

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	readily biodegradable	aerobic	98 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Cyclohexanone 108-94-1	readily biodegradable	aerobic	90 - 100 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

Hazardous substances CAS-No.	LogPow	Temperature	Method
Cyclohexanone 108-94-1	0,86	25 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)

12.5. Results of PBT and vPvB assessment

Hazardous substances CAS-No.	PBT / vPvB
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 64742-49-0	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Cyclohexanone 108-94-1	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

14 06 03 - other solvents and solvent mixtures

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information
--

14.1. UN number

ADR	1206
RID	1206
ADN	1206
IMDG	1206
IATA	1206

14.2. UN proper shipping name

ADR	HEPTANES
RID	HEPTANES
ADN	HEPTANES
IMDG	HEPTANES
IATA	Heptanes

14.3. Transport hazard class(es)

ADR	3
RID	3
ADN	3
IMDG	3
IATA	3

14.4. Packing group

ADR	II
RID	II
ADN	II
IMDG	II
IATA	II

14.5. Environmental hazards

ADR	Environmentally Hazardous
RID	Environmentally Hazardous
ADN	Environmentally Hazardous
IMDG	Marine pollutant
IATA	not applicable

14.6. Special precautions for user

ADR	not applicable Tunnelcode: (D/E)
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC content (2010/75/EC)	100 %
-----------------------------	-------

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

- H225 Highly flammable liquid and vapor.
- H226 Flammable liquid and vapor.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.