

LOCTITE 270

Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 17

SDS No.: 346906

V007.1 Revision: 12.05.2020

printing date: 21.07.2020

Replaces version from: 21.02.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE 270

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Adhesive

1.3. Details of the supplier of the safety data sheet

Henkel Ltd Adhesives

Great Britain

Wood Lane End HP2 4RQ Hemel Hempstead

Phone: +44 (1442) 278000 Fax-no.: +44 (1442) 278071

ua-productsafety.uk@henkel.com

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Skin irritation Category 2

H315 Causes skin irritation.

Serious eye irritation Category 2

H319 Causes serious eye irritation.

Skin sensitizer Category 1

H317 May cause an allergic skin reaction.

Specific target organ toxicity - single exposure Category 3

H335 May cause respiratory irritation.

Target organ: respiratory tract irritation

Chronic hazards to the aquatic environment Category 2

H411 Toxic to aquatic life with long lasting effects.

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Contains 3,3,5 Trimethylcyclohexyl methacrylate

2,2'-Ethylenedioxydiethyl dimethacrylate

maleic acid

Acetic acid, 2-phenylhydrazide

Signal word: Warning

Hazard statement: H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H335 May cause respiratory irritation.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statement: "***For consumer use only: P101 If medical advice is needed, have product

container or label at hand. P102 Keep out of reach of children. P501 Dispose of

contents/container in accordance with national regulation.***

Precautionary statement: P261 Avoid breathing vapors.

Prevention P273 Avoid release to the environment.

P280 Wear protective gloves.

Precautionary statement: P302+P352 IF ON SKIN: Wash with plenty of soap and water.

Response P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

2.3. Other hazards

None if used properly.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General chemical description:

Anaerobic adhesive

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	231-927-0 01-2120748527-45	25- 50 %	Aquatic Chronic 2 H411 Skin Sens. 1B H317 STOT SE 3 H335 Skin Irrit. 2 H315 Eye Irrit. 2 H319
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	203-652-6 01-2119969287-21	5-< 10 %	Skin Sens. 1B H317
Cumene hydroperoxide 80-15-9	201-254-7 01-2119475796-19	1-< 2,5 %	Acute Tox. 4; Dermal H312 STOT RE 2 H373 Acute Tox. 4; Oral H302 Org. Perox. E H242 Acute Tox. 3; Inhalation H331 Aquatic Chronic 2 H411 Skin Corr. 1B H314
maleic acid 110-16-7	203-742-5 01-2119488705-25	0,1-< 1 %	Acute Tox. 4; Oral H302 Acute Tox. 4; Dermal H312 Skin Irrit. 2 H315 Skin Sens. 1 H317 Eye Irrit. 2 H319 STOT SE 3 H335
Acetic acid, 2-phenylhydrazide 114-83-0	204-055-3	0,1-< 1 %	Acute Tox. 3; Oral H301 Skin Irrit. 2 H315 Skin Sens. 1 H317 Eye Irrit. 2 H319 STOT SE 3; Inhalation H335 Carc. 2 H351
1,4-Naphthalenedione 130-15-4	204-977-6	0,01-< 0,025 % (100 ppm- < 250 ppm)	Acute Tox. 3; Oral H301 Skin Irrit. 2; Dermal H315 Skin Sens. 1 H317 Eye Irrit. 2 H319 Acute Tox. 1; Inhalation H330 STOT SE 3; Inhalation H335 Aquatic Acute 1 H400 Aquatic Chronic 1 H410 M factor (Acute Aquat Tox): 10 M factor (Chron Aquat Tox): 10

Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

SKIN: Redness, inflammation.

SKIN: Rash, Urticaria.

EYE: Irritation, conjunctivitis.

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Carbon dioxide, foam, powder

Fine water spray

Extinguishing media which must not be used for safety reasons:

None known

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

Avoid contact with skin and eyes.

Wear protective equipment.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Use only in well-ventilated areas.

Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation.

Avoid skin and eye contact.

See advice in section 8

Hygiene measures:

Good industrial hygiene practices should be observed.

Do not eat, drink or smoke while working.

Wash hands before work breaks and after finishing work.

7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction.

Store in a cool, well-ventilated place.

Refer to Technical Data Sheet

Do not store together with food or other consumables (coffee, tea, tobacco, etc.).

7.3. Specific end use(s)

Adhesive

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for

Great Britain

None

Occupational Exposure Limits

Valid for

Ireland

None

$\label{eq:predicted} \textbf{Predicted No-Effect Concentration (PNEC):}$

Name on list	Environmental Compartment	Exposure period	Value				Remarks
		<u> </u>	mg/l ppm mg/kg of			others	
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	aqua (freshwater)		0,00059 mg/l				
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	aqua (marine water)		0,000059 mg/l				
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	aqua (intermittent		0,0059 mg/l				
	releases)						
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	sewage treatment plant (STP)		100 mg/l				
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	sediment (freshwater)				0,044 mg/kg		
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	sediment (marine water)				0,004 mg/kg		
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	Soil				0,008 mg/kg		
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	aqua (freshwater)		0,164 mg/l				
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	aqua (marine water)		0,0164 mg/l				
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	sewage treatment plant (STP)		10 mg/l				
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	aqua (intermittent releases)		0,164 mg/l				
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	sediment (freshwater)				1,85 mg/kg		
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	sediment (marine water)				0,185 mg/kg		
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	Soil				0,274 mg/kg		
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	Air						no hazard identified
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	Predator						no potential for bioaccumulation
.alpha.,.alphaDimethylbenzyl hydroperoxide 80-15-9	aqua (freshwater)		0,0031 mg/l				
.alpha.,.alphaDimethylbenzyl hydroperoxide 80-15-9	aqua (marine water)		0,00031 mg/l				
.alpha.,.alphaDimethylbenzyl hydroperoxide 80-15-9	aqua (intermittent releases)		0,031 mg/l				
.alpha.,.alphaDimethylbenzyl hydroperoxide 80-15-9	Sewage treatment plant		0,35 mg/l				
.alpha.,.alphaDimethylbenzyl hydroperoxide 80-15-9	sediment (freshwater)				0,023 mg/kg		
.alpha.,.alphaDimethylbenzyl hydroperoxide 80-15-9	sediment (marine water)				0,0023 mg/kg		
alpha., alphaDimethylbenzyl hydroperoxide 80-15-9	Soil				0,0029 mg/kg		
Maleic acid 110-16-7	aqua (freshwater)		0,1 mg/l				
Maleic acid 110-16-7	aqua (intermittent releases)		0,4281 mg/l				
Maleic acid 110-16-7	sediment (freshwater)				0,334 mg/kg		
Maleic acid 110-16-7	sewage treatment plant		44,6 mg/l		шуку		
	(STP)		0.01 "				
Maleic acid 110-16-7	aqua (marine water)		0,01 mg/l				

Maleic acid 110-16-7	sediment (marine water)	0,0334 mg/kg	
Maleic acid	Soil	0,0415	
110-16-7		mg/kg	

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	Workers	inhalation	Long term exposure - systemic effects		16,45 mg/m3	
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	Workers	dermal	Long term exposure - systemic effects		46,7 mg/kg	
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	General population	inhalation	Long term exposure - systemic effects		2,9 mg/m3	
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	General population	dermal	Long term exposure - systemic effects		16,7 mg/kg	
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	General population	oral	Long term exposure - systemic effects		1,67 mg/kg	
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	Workers	inhalation	Long term exposure - systemic effects		48,5 mg/m3	no hazard identified
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	Workers	dermal	Long term exposure - systemic effects		13,9 mg/kg	no hazard identified
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	General population	inhalation	Long term exposure - systemic effects		14,5 mg/m3	no hazard identified
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	General population	dermal	Long term exposure - systemic effects		8,33 mg/kg	no hazard identified
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	General population	oral	Long term exposure - systemic effects		8,33 mg/kg	no hazard identified
.alpha.,.alphaDimethylbenzyl hydroperoxide 80-15-9	Workers	inhalation	Long term exposure - systemic effects		6 mg/m3	
Maleic acid 110-16-7	Workers	dermal	Acute/short term exposure - local effects		0,55 mg/cm2	
Maleic acid 110-16-7	Workers	dermal	Long term exposure - local effects		0,04 mg/cm2	
Maleic acid 110-16-7	Workers	dermal	Acute/short term exposure - systemic effects		58 mg/kg	
Maleic acid 110-16-7	Workers	dermal	Long term exposure - systemic effects		3,3 mg/kg	
Maleic acid 110-16-7	Workers	inhalation	Acute/short term exposure - local effects		3 mg/m3	
Maleic acid 110-16-7	Workers	inhalation	Long term exposure - systemic effects		3 mg/m3	
Maleic acid 110-16-7	Workers	inhalation	Long term exposure - local effects		3 mg/m3	
Maleic acid 110-16-7	Workers	inhalation	Acute/short term exposure - systemic effects		3 mg/m3	

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly

ventilated area

Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing. Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance liquid liquid

green

Odor characteristic

Odour threshold No data available / Not applicable

pH No data available / Not applicable
Melting point No data available / Not applicable
Solidification temperature No data available / Not applicable

Initial boiling point > 65 °C (> 149 °F) Flash point 110 °C (230 °F)

Evaporation rate No data available / Not applicable Flammability No data available / Not applicable Explosive limits No data available / Not applicable

Vapour pressure 2,85 mbar

(25 °C (77 °F))

Relative vapour density: No data available / Not applicable

Density 1,10 g/cm³

(20 °C (68 °F))

Bulk density No data available / Not applicable Solubility No data available / Not applicable

Solubility (qualitative)

(23 °C (73.4 °F); Solvent: Water)

Solubility (qualitative)

(Solvent: Acetone) Partition coefficient: n-octanol/water

Decomposition temperature Viscosity Viscosity (kinematic)

No data available / Not applicable Auto-ignition temperature No data available / Not applicable Explosive properties Oxidising properties No data available / Not applicable

9.2. Other information

No data available / Not applicable

SECTION 10: Stability and reactivity

Insoluble

Soluble

10.1. Reactivity

Peroxides.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

No decomposition if used according to specifications.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

carbon oxides.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	LD0	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	LD50	10.837 mg/kg	rat	not specified
Cumene hydroperoxide 80-15-9	LD50	382 mg/kg	rat	other guideline:
maleic acid 110-16-7	LD50	708 mg/kg	rat	not specified
Acetic acid, 2- phenylhydrazide 114-83-0	LD50	270 mg/kg	rat	not specified
1,4-Naphthalenedione 130-15-4	LD50	190 mg/kg	rat	not specified

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Species	Method
CAS-No.	type			
3,3,5 Trimethylcyclohexyl	LD0	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
methacrylate 7779-31-9				
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	LD50	> 2.000 mg/kg	mouse	not specified
Cumene hydroperoxide 80-15-9	LD50	530 - 1.060 mg/kg	rat	other guideline:
Cumene hydroperoxide 80-15-9	Acute toxicity estimate (ATE)	1.100 mg/kg		Expert judgement
maleic acid 110-16-7	LD50	1.560 mg/kg	rabbit	not specified

Acute inhalative toxicity:

No data available.

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	not irritating	24 h	rabbit	Draize Test
Cumene hydroperoxide 80-15-9	corrosive		rabbit	Draize Test
maleic acid 110-16-7	irritating	24 h	human	Patch Test

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Result	Exposure	Species	Method
CAS-No.		time		
2,2'-Ethylenedioxydiethyl	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
dimethacrylate				
109-16-0				
maleic acid	highly		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
110-16-7	irritating			

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances	Result	Test type	Species	Method
CAS-No.				
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
maleic acid 110-16-7	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
maleic acid 110-16-7	sensitising	Mouse local lymphnode assay (LLNA)	guinea pig	OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	negative	in vitro mammalian cell micronucleus test	with and without		OECD Guideline 487 (In vitro Mammalian Cell Micronucleus Test)
Cumene hydroperoxide 80-15-9	positive	bacterial reverse mutation assay (e.g Ames test)	without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
maleic acid 110-16-7	negative	bacterial reverse mutation assay (e.g Ames test)	no data		Ames Test
maleic acid 110-16-7	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
maleic acid 110-16-7	not carcinogenic	oral: feed	2 y daily	rat	male/female	OECD Guideline 451 (Carcinogenicity Studies)

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances	Result / Value	Test type	Route of	Species	Method
CAS-No.			application		
2,2'-Ethylenedioxydiethyl	NOAEL P 1.000 mg/kg		oral: gavage	rat	OECD Guideline 422
dimethacrylate					(Combined Repeated Dose
109-16-0	NOAEL F1 1.000 mg/kg				Toxicity Study with the
					Reproduction /
					Developmental Toxicity
					Screening Test)
maleic acid	NOAEL F1 150 mg/kg	Two	oral: gavage	rat	OECD Guideline 416 (Two-
110-16-7		generation			Generation Reproduction
	NOAEL F2 55 mg/kg	study			Toxicity Study)

STOT-single exposure:

No data available.

STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	NOAEL 1.000 mg/kg	oral: gavage	28 d daily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	NOAEL 1.000 mg/kg	oral: gavage	daily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Cumene hydroperoxide 80-15-9		inhalation: aerosol	6 h/d 5 d/w	rat	not specified
maleic acid 110-16-7	NOAEL >= 40 mg/kg	oral: feed	90 d daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

Aspiration hazard:

No data available.

SECTION 12: Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	LC50	1,9 mg/l	96 h	Brachydanio rerio (new name: Danio rerio)	OECD Guideline 203 (Fish, Acute Toxicity Test)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	LC50	16,4 mg/l	96 h	Danio rerio	OECD Guideline 203 (Fish, Acute Toxicity Test)
Cumene hydroperoxide 80-15-9	LC50	3,9 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
maleic acid 110-16-7	LC50	> 245 mg/l	48 h	Leuciscus idus	DIN 38412-15

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
3,3,5 Trimethylcyclohexyl	EC50	14,43 mg/l	48 h	Daphnia magna	OECD Guideline 202
methacrylate					(Daphnia sp. Acute
7779-31-9					Immobilisation Test)
Cumene hydroperoxide	EC50	18 mg/l	48 h	Daphnia magna	OECD Guideline 202
80-15-9					(Daphnia sp. Acute
					Immobilisation Test)
maleic acid	EC50	42,81 mg/l	48 h	Daphnia magna	OECD Guideline 202
110-16-7					(Daphnia sp. Acute
					Immobilisation Test)

Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
2,2'-Ethylenedioxydiethyl	NOEC	32 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia
dimethacrylate					magna, Reproduction Test)
109-16-0					
maleic acid	NOEC	10 mg/l	21 d	Daphnia magna	other guideline:
110-16-7					

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	EC10	0,43 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	EC50	> 100 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	NOEC	18,6 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Cumene hydroperoxide 80-15-9	ErC50	3,1 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
maleic acid 110-16-7	EC50	74,35 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
maleic acid 110-16-7	EC10	11,8 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
1,4-Naphthalenedione 130-15-4	EC50	0,011 mg/l	72 h	Dunaliella bioculata	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Cumene hydroperoxide 80-15-9	EC10	70 mg/l	30 min		not specified
maleic acid 110-16-7	EC10	44,6 mg/l	18 h	Pseudomonas putida	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm- Test)

12.2. Persistence and degradability

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	not readily biodegradable.	aerobic	16,8 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	readily biodegradable	aerobic	85 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Cumene hydroperoxide 80-15-9		no data	0 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
maleic acid 110-16-7	readily biodegradable	aerobic	97,08 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
1,4-Naphthalenedione 130-15-4	not readily biodegradable.	no data	0 - 60 %		OECD 301 A - F

12.3. Bioaccumulative potential

Hazardous substances CAS-No.	Bioconcentratio n factor (BCF)	Exposure time	Temperature	Species	Method
Cumene hydroperoxide	9,1			calculation	OECD Guideline 305
80-15-9					(Bioconcentration: Flow-through
					Fish Test)

12.4. Mobility in soil

Cured adhesives are immobile.

Hazardous substances	LogPow	Temperature	Method
CAS-No.			
3,3,5 Trimethylcyclohexyl methacrylate 7779-31-9	5,25	20 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	2,3		OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
Cumene hydroperoxide 80-15-9	2,16		not specified
maleic acid 110-16-7	-1,3	20 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
Acetic acid, 2- phenylhydrazide 114-83-0	0,74		not specified
1,4-Naphthalenedione 130-15-4	1,71		not specified

12.5. Results of PBT and vPvB assessment

Hazardous substances	PBT / vPvB
CAS-No.	
3,3,5 Trimethylcyclohexyl methacrylate	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
7779-31-9	Bioaccumulative (vPvB) criteria.
2,2'-Ethylenedioxydiethyl dimethacrylate	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
109-16-0	Bioaccumulative (vPvB) criteria.
Cumene hydroperoxide	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
80-15-9	Bioaccumulative (vPvB) criteria.
maleic acid	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
110-16-7	Bioaccumulative (vPvB) criteria.
1,4-Naphthalenedione	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
130-15-4	Bioaccumulative (vPvB) criteria.

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Dispose of in accordance with local and national regulations.

Do not empty into drains / surface water / ground water.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

Waste code

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information

14.1. UN number

3082
3082
3082
3082
3082

14.2. UN proper shipping name

ADR	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (3,3,5-
-----	---

Trimethylcyclohexyl methacrylate)

RID ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (3,3,5-

Trimethylcyclohexyl methacrylate)

ADN ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (3,3,5-

Trimethylcyclohexyl methacrylate)

IMDG ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (3,3,5-

Trimethylcyclohexyl methacrylate)

IATA Environmentally hazardous substance, liquid, n.o.s. (3,3,5-Trimethylcyclohexyl

methacrylate)

14.3. Transport hazard class(es)

ADR	9
RID	9
ADN	ç
IMDG	9
IATA	Ç

14.4. Packing group

ADR	III
RID	III
ADN	III
IMDG	III
IATA	III

14.5. Environmental hazards

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	Marine pollutant
IATA	not applicable

14.6. Special precautions for user

ADR	not applicable
	Tunnelcode:
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

The transport classifications in this section apply generally to packed and bulk goods alike. For containers with a net volume of no more than 5 L for liquid substances or a net mass of no more than 5 kg for solid substances per individual or inner package, the exemptions SP 375 (ADR), 197 (IATA), 969 (IMDG) may be applied, which can result in a deviation from the transport classification for packed goods.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC content < 3 % (2010/75/EC)

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

H242 Heating may cause a fire.

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H330 Fatal if inhaled.

H331 Toxic if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.