

PRODUCT-DETAILS

JRA/S4.24.5.1

JRA/S4.24.5.1 Blind/Roller Shutter Act, Travel Det, 4-f, 24 V DC, Man Op, MDRC



General Information

Extended Product Type	JRA/S4.24.5.1
Product ID	2CDG110128R0011
EAN	4016779698474
Catalog Description	JRA/S4.24.5.1 Blind/Roller Shutter Act, Travel Det, 4-f, 24 V DC, Man Op, MDRC
Long Description	For the control of up to 4 independent 24 V DC drives via ABB i-bus® KNX. The device is designed for positioning blinds, roller shutters, awnings and other shading products as well as for controlling doors, windows and ventilation flaps. Additional auxiliary voltage is not needed. The travel times of the drive are detected automatically via current detection. Push buttons are located at the front of the device to control the outputs e.g. during commissioning. The current status of the output is displayed via LEDs.

Ordering

EAN	4016779698474
Customs Tariff Number	85371091
Minimum Order Quantity	1 piece
E-Number (Switzerland)	405430445
E-Number (Sweden)	1751252

Dimensions

Product Net Depth / Length	64.5 mm
Product Net Height	90 mm

Product Net Width	72 mm
Product Net Weight	0.22 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 EAN	4016779698474
Package Level 1 Depth / Length	77 mm
Package Level 1 Height	65 mm
Package Level 1 Width	92 mm
Package Level 1 Gross Weight	0.252 kg

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	2CDC506040D0201 2CDC506064D0202
Instructions and Manuals	2CDG941079P0005
Declaration of Conformity - CE	2CDK506043D2701
RoHS Information	2CDG510125-0100

Environmental

RoHS Status	Following EU Directive 2002/95/EC August 18, 2005 and amendment
-------------	---

Classifications

ETIM 5	EC001330 - Shutting actuator for bus system
ETIM 6	EC001330 - Shutting actuator for bus system
ETIM 7	EC001330 - Shutting actuator for bus system
eClass	7.0 27143128
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Home and Building Automation → KNX → Shading Control → Blind Actuators 24 V DC

