

According to EC directive 91/155/EEC and subsequent amendments

Version: 1.5

Revision Date: 03.11.2003

DOW CORNING(R) 732 FORMED IN PLACE GASKET SEALANT, WHITE

1. IDENTIFICATION OF THE SUBSTANCE AND OF THE COMPANY

Trade name : DOW CORNING(R) 732 FORMED IN PLACE GASKET SEALANT, WHITE

Company : Dow Corning S.A.

Parc Industriel - Zone C

B-7180 Seneffe

Belgium

Service : Dow Corning Central Europe Tel: +49 6112371

Fax: +49 611237609

Dow Corning Northern Europe Tel: +44 1676528000

Fax: +44 1676528001

Dow Corning Southern Europe Tel: +33 472841360

Fax: +33 472841379 Tel: +44 1446732350

Emergency Phone Number: Dow Corning (Barry U.K. 24h)

Dow Corning (Wiesbaden 24h)

Tel: +49 61122158

Dow Corning (Seneffe 24h)

Tel: +32 64 888240

2. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical characterization: Silicone elastomer

Hazardous Ingredients:

Name	CAS-No.	EINECS/ ELINCS No.	Conc. (% w/w)	Classification	
Methyltriacetoxysilane	4253-34-3	224-221-9	2.0	C Xn	R34 R22
Triacetoxy(ethyl)silane	17689-77-9	241-677-4	2.0	C Xn	R34 R22

3. HAZARDS IDENTIFICATION

Not hazardous according to Council Directive 1999/45/EC and its subsequent amendments.

4. FIRST AID MEASURES

On contact with eyes : Flush with water.

On skin contact : Wipe off and wash with soap and water.

If inhaled : Remove to fresh air.

On ingestion : Obtain medical attention if large amounts have been swallowed.



According to EC directive 91/155/EEC and subsequent amendments

Version: 1.5

Revision Date: 03.11.2003

DOW CORNING(R) 732 FORMED IN PLACE GASKET SEALANT, WHITE

5. FIRE FIGHTING MEASURES

Suitable extinguishing media : Carbon dioxide, foam, dry powder or fine water spray. Water can be used to cool fire

exposed containers.

Unsuitable extinguishing

media

None known.

Hazards during fire fighting: None known.

Special protective

equipment/procedures

A self-contained respirator and protective clothing should be worn. Keep containers cool with water spray until well after the fire is out. Determine the need to evacuate or isolate

the area according to your local emergency plan.

Hazardous Combustion

Products

Silica. Carbon oxides and traces of incompletely burned carbon compounds.

Formaldehyde.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Wear proper protective equipment.

Precautions to protect the

environment

Do not allow large quantities to enter drains or surface waters.

Methods for cleaning up : Scrape up and place in a container fitted with a lid. The spilled product produces an

extremely slippery surface.

7. HANDLING AND STORAGE

Advice on safe handling : General ventilation is recommended. Local ventilation is recommended. Avoid skin and

eye contact. Do not breathe vapour.

Advice on storage : Do not store with oxidizing agents. Keep container closed and store away from water or

moisture.

Specific uses : Refer to technical data sheet available on request.

Unsuitable packaging

materials

None known.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls : Ventilation : Refer to Section 7

Exposure controls for hazardous components

Name CAS-No. Exposure Limits

Methyltriacetoxysilane 4253-34-3 10 ppm TWA, 15ppm STEL as acetic acid.

2 of 6



According to EC directive 91/155/EEC and subsequent amendments

Version: 1.5

Revision Date: 03.11.2003

DOW CORNING(R) 732 FORMED IN PLACE GASKET SEALANT, WHITE

Triacetoxy(ethyl)silane 17689-77-9 10 ppm TWA, 15ppm STEL as acetic acid.

Personal protection equipment

Respiratory protection: Suitable respiratory protection should be worn if the product is used in large quantities,

confined spaces or in other circumstances where the OEL may be approached or

exceeded.

Hand protection: Chemical protective gloves should be worn: Butyl rubber. Nitrile rubber. Neoprene

rubber. Silver shield(TM). 4H(TM). Regarding glove's breakthrough time...,contact

your chemical protective glove supplier.

Eye protection : Safety glasses should be worn.

Skin protection: Wear impervious overalls in circumstances where significant skin contact can occur.

Hygiene measures : Exercise good industrial hygiene practice. Wash after handling, especially before eating,

drinking or smoking.

Environmental exposure

controls

Refer to section 6 and 12.

Additional information : None known.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Form: Paste Colour: White Odour: Acetic acid

Other data

Explosive properties : No

Specific Gravity : 1.04

Oxidizing properties : No

The above information is not intended for use in preparing product specifications. Contact Dow Corning before writing specifications.

10. STABILITY AND REACTIVITY

Stability : Stable under normal usage conditions.

Conditions to avoid : None established.

Materials to avoid : Can react with strong oxidising agents. Cures in the presence of water or moisture,

releasing a small amount of acetic acid.

Hazardous decomposition

products

See section 11.



According to EC directive 91/155/EEC and subsequent amendments

Version: 1.5

Revision Date: 03.11.2003

DOW CORNING(R) 732 FORMED IN PLACE GASKET SEALANT, WHITE

11. TOXICOLOGICAL INFORMATION

On contact with eyes : Vapours released during curing may cause eye irritation.

On skin contact : Can irritate on prolonged or repeated contact.

If inhaled : The vapour is irritating to the mouth, nose and throat.

On ingestion : Small amounts transferred to the mouth by fingers during use should not injure.

Swallowing large amounts may cause digestive discomfort.

Other Health Hazard

Information

Product may emit formaldehyde vapours at temperatures above 150°C in the presence of

air. Formaldehyde vapour is harmful by inhalation and irritating to eyes and respiratory system at breathing concentration less than one part per million (1 ppm).

Based on product test data.

Based on test data from similar products.

This information is based either on test data, extrapolation from tests on similar materials, review of component data, or a combination of these sources.

12. ECOLOGICAL INFORMATION

Environmental fate and distribution

Solid material, insoluble in water. No adverse effects are predicted.

Ecotoxicity effects

No adverse effects on aquatic organisms are predicted.

Bioaccumulation : No bioaccumulation potential.

Fate and effects in waste water treatment plants

No adverse effects on bacteria are predicted.

13. DISPOSAL CONSIDERATIONS

Product disposal : Dispose of in accordance with local regulations.

Packaging disposal : Dispose of in accordance with local regulations.



According to EC directive 91/155/EEC and subsequent amendments

Version: 1.5

Revision Date: 03.11.2003

DOW CORNING(R) 732 FORMED IN PLACE GASKET SEALANT, WHITE

14. TRANSPORT INFORMATION

Road / Rail (ADR/RID)

Not subject to ADR/RID.

Sea transport (IMDG)

Not subject to IMDG code.

Air transport (IATA)

Not subject to IATA regulations.

15. REGULATORY INFORMATION

Labelling according to EEC Directive

S-phrases : S24 Avoid contact with skin.

S51 Use only in well-ventilated areas.

National legislation / regulations

Ozone depleting

chemicals

: No ozone depleting chemicals are present or used in manufacture.

Status

TSCA : All chemical substances in this material are included on or exempted from listing on the

TSCA Inventory of Chemical Substances.

EINECS : All ingredients listed or exempt.



According to EC directive 91/155/EEC and subsequent amendments

Version: 1.5 Revision Date: 03.11.2003

DOW CORNING(R) 732 FORMED IN PLACE GASKET SEALANT, WHITE

16. OTHER INFORMATION

This product safety data sheet was prepared in compliance with Commission Directive 91/155/EEC, 67/548/EEC and 1999/45/EC as well as their relevant amendements, on the approximation of laws, regulations and administrative provisions relative to the classification, packaging and labelling of dangerous substances and preparations.

It is the responsibility of persons in receipt of this Product Safety Data Sheet to ensure that the information contained herein is properly read and understood by all people who may use, handle, dispose or in any way come in contact with the product. If the recipient subsequently produces a formulation containing the Dow Corning product, it is the recipient's sole responsibility to ensure the transfer of all relevant information from the Dow Corning Product Safety Data Sheet to their own Product Safety Data Sheet in compliance with Commission Directive 1999/45/EC.

All information and instructions provided in this Safety Data Sheet (SDS) are based on the current state of scientific and technical knowledge at the date indicated on the present SDS. Dow Corning shall not be held responsible for any defect in the product covered by this SDS, should the existence of such defect not be detectable considering the current state of scientific and technical knowledge.

As stated above, this Safety Data Sheet has been prepared in compliance with applicable European law. If you purchase this material outside Europe, where compliance laws may differ, you should receive from your local Dow Corning supplier a SDS applicable to the country in which the product is sold and intended to be used. Please note that the appearance and content of the SDS may vary - even for the same product - between different countries, reflecting the different compliance requirements. Should you have any question, please refer to your local Dow Corning supplier.

R22 Harmful if swallowed., R34 Causes burns.