#### Loctite Corporation

Environmental Health & Safety Affairs Health & Regulatory Affairs - Europe

## SAFETY DATA SHEET

4105 0190002 10.00 IE EA 21.07.2003 MSDS\_IE

This safety data sheet has been prepared in accordance with the requirements of EC Directives 1999/45/EC and 2001/58/EC and provides information relating to the safe handling and use of the product.

### 1. PRODUCT AND COMPANY INFORMATION

Product Code	0190002
Trade Name	4105
Manufacturer/Supplier	Henkel Loctite Adhesives Ltd.
Address	Watchmead, Welwyn Garden City, Herts., AL7IJB. UK
Phone Number	01 707 358800
Fax Number	01 707 358900
Emergency Phone Number	+353-1-4599301/+353-87-2629625/+353-1-4046444

### 2. COMPOSITION / INFORMATION ON INGREDIENTS

#### Nature

Cyanoacrylate adhesive.

#### Hazardous Components in Product for EC

Component Name Ethyl Cyanoacrylate **CAS / EINEC Concentration** 7085-85-0 230- 60.00 - 90.00 391-5

rationR Phrases00R36/37/38

Classification Xi

### 3. HAZARD IDENTIFICATION

Irritating to eyes, respiratory system and skin. Bonds skin and eyes in seconds. Highly reactive to water. (See Section 4 on first aid).

### 4. FIRST AID MEASURES

#### First Aid - Inhalation

Remove affected person to fresh air, and if still feeling unwell seek medical attention.

#### First Aid - Skin

Do not pull bonded skin apart. It may be gently peeled apart using a blunt object such as a spoon, preferably after soaking in warm soapy water. Cyanoacrylates give off heat on solidification. In rare cases a large drop will generate enough heat to cause a burn. Burns should be treated normally after the adhesive has been removed from the skin.

If lips are accidentally stuck together apply warm water to the lips and encourage maximum wetting and pressure from saliva inside the mouth. Peel or roll lips apart. Do not try to pull the lips apart with direct opposing action.

#### First Aid - Eyes

If the eye is bonded closed, release eyelashes with warm water by covering with wet pad. Cyanoacrylate will bond to eye protein and will cause periods of weeping which will help to debond the adhesive. Keep eye covered until debonding is complete, usually within 1-3 days. Do not force eye open. Medical advice should be sought in case solid particles of cyanoacrylate trapped behind the eyelid cause any abrasive damage.

#### **First Aid - Ingestion**

Ensure that breathing passages are not obstructed. The product will polymerise immediately in the mouth making it almost impossible to swallow. Saliva will slowly separate the solidified product from the mouth (several hours).

#### **Loctite Corporation**

Environmental Health & Safety Affairs Health & Regulatory Affairs - Europe

## SAFETY DATA SHEET

4105

0190002 10.00 IE EA 21.07.2003 MSDS\_IE

### 5. FIRE FIGHTING MEASURES

Non flammable product (flash point is greater than 80°C (CC)). If product is involved in fire extinguish with dry powder, foam or carbon dioxide. Trace amounts of toxic fumes may be released on incineration and the use of breathing apparatus is recommended.

## 6. ACCIDENTAL RELEASE MEASURES

Ventilate area. Do not use cloths for mopping up. Polymerise with water and scrape off floor.

### 7. HANDLING AND STORAGE

#### Handling

Ventilation (low level) is recommended when using large volumes. Use of dispensing equipment is recommended to minimise the risk of skin or eye contact.

#### Storage

For optimum shelf life store in original containers under refrigerated conditions at 2°C to 8°C.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Occupational exposure limits Ethyl Cyanoacrylate

ACGIH: TLV 0.2ppm 8h TWA.

HSA (1999) C.O.P : OEL 2ppm (8mg/m3) 8h TWA. HSA (1999) C.O.P : OEL 4ppm (16mg/m3) 15 min exposure limit.

Polyethylene or polypropylene gloves are recommended when using large volumes. Do not use PVC, rubber, nylon or cotton gloves. Eye protection should be used where there is any risk of splashing.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Liquid.
Colour	Black.
Odour	Sharp. Characteristic.
рН	Not applicable.
Boiling Range/Point (°C)	Boils above 100.
Flash Point (CC) (°C)	Exceeds 80.
Specific Gravity	1.1 g ccm at 20 °C.
Solubility in Water (kg/m³)	Immiscible. Reacts with water.
Solubility in Acetone	Soluble
Vapour Pressure (mmHg	Less than 0.5 at 25 °C.
@25°C)	
Explosion Limits (%)	Not applicable.

### **10. STABILITY AND REACTIVITY**

Polymerisation will occur in the presence of moisture.

### 11. TOXICOLOGICAL INFORMATION

#### Inhalation

Irritating to respiratory system. In dry atmosphere with < 50% humidity, vapours may irritate the eyes and respiratory system. Prolonged exposure to high concentrations of vapours may lead to chronic effects in sensitive individuals.

#### **Loctite Corporation**

Environmental Health & Safety Affairs Health & Regulatory Affairs - Europe

## SAFETY DATA SHEET

4105 0190002 10.00 IE EA 21.07.2003 MSDS\_IE

### 11. TOXICOLOGICAL INFORMATION

#### Skin

This product is classified as a skin irritant. Bonds skin in seconds. Considered to be of low toxicity: acute dermal LD50 (rabbit)>2000mg/kg. Due to polymerisation at the skin surface allergic reaction is not considered possible.

#### Eyes

This product is an irritant to the eyes. Liquid product will bond eyelids. In a dry atmosphere (RH<50%) vapours may cause irritation and lachrymatory effect.

#### Ingestion

Cyanoacrylates are considered to have relatively low toxicity. Acute oral LD50 is >5000mg/kg (rat). It is almost impossible to swallow as it rapidly polymerises in the mouth.

### **12. ECOLOGICAL INFORMATION**

Biodegradable product of low ecotoxicity.

### **13. DISPOSAL CONSIDERATIONS**

Dispose of in accordance with local and national regulations. Polymerise by adding slowly to water (10:1). Dispose of as water insoluble non-toxic solid chemical in authorised landfill or incinerate under controlled conditions.

### 14. TRANSPORT INFORMATION

UN Number		3334		
Air (IATA)		Aviation regulated liquids, n.o.s (Cyanoacrylate Ester). , Class 9, Packaging Group -		
		Maximum quantity, cargo aircraft: 220 I Maximum quantity, passenger aircraft: 100 I		
Sea (IMO)		Not classified.		
Road (ADR)/	Rail (RID)	Not classified.		
15. REGULATORY INFORMATION				
Contains		Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of children.		
Labelling Information	Irritant Irritant			
R phrases		R36/37/38 Irritating to eyes, respiratory system and skin.		
S phrases		S23 Do not breathe vapour. S24/25 Avoid contact with skin and eyes. S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.		

### **Loctite Corporation**

Environmental Health & Safety Affairs Health & Regulatory Affairs - Europe

# SAFETY DATA SHEET

4105

0190002 10.00 IE EA 21.07.2003 MSDS\_IE

### **15. REGULATORY INFORMATION**

### Voluntary Labelling

### **16. OTHER INFORMATION**

#### **MSDS** data revised

21 July 2003

#### Hazardous Components in Product for EC

Component Name Ethyl Cyanoacrylate R36/37/38

R36/37/38 R36/37/38 Irritating to eyes, respiratory system and skin.

**R** Phrases

Further Information may be obtained from:-

Loctite Corporation, Health and Regulatory Affairs - Europe, Tallaght Business Park, Whitestown, Dublin 24, Ireland.

Tel: +353-1-4046444. Fax: +353-1-4510806.

The information in this safety data sheet was obtained from reputable sources and to the best of our knowledge is accurate and current at the mentioned date.

Neither Loctite nor its subsidiary companies accept any liability arising out of the use of the information provided here or the use, application or processing of the product(s) described herein.

Attention of users is drawn to the possible hazards from improper use of the product(s).

Prepared by:

Dr Hanns Misiak HRA Specialist Health & Regulatory Affairs - Europe

This safety data sheet was prepared in accordance with Commission Directive 2001/59/EC adapting to technical progress for the 28th time Council Directive 67/548/EEC and Commission Directive 1999/45/EC.