## Crimp Terminal Female, Red





## **Specifications:**

Maximum Electric Current : AWG | 22 | 20 | 18 | 16 | Amperes | 3 | 4 | 7 | 10

Maximum Electrical Rating : 105°C 300V maximum

Insulation Material : Nylon
Insulation Colour : Red
Terminal Material : Brass

Wire Range : 26 to 16AWG (0.5 to 1.5mm<sup>2</sup>)

Terminals Surface Treatment : Tin plated : 0.45mm

Nema Tab : 0.032" × 0.25" (0.8 × 6.35mm)

Cable Diameter Min. : 0.57mm

Cable Diameter Max. : 1.65mm


Connector Type : Disconnect


Contact Material : Copper

Current Rating : 12A


Gender : Receptacle
Operating Temperature Min. : -20°C to +85°C
Voltage Rating : 415V AC

## **Diagram**





Dimensions : Millimetres



## **Part Number Table**

Description	Part Number
Crimp Terminal - Female, Nylon Insulation, Red	FDFNY1-250

Important Notice: This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro

