
multicomp PRO





Specifications:


Centre Contact	: Brass per JIS-C3604
Connector Type	: BNC Coaxial
Body Style	: Right Angle Plug
Coaxial Termination	: Clamp
Impedance	: 500
	: RG-174
Cable Type	
Contact Plating	: Gold
Frequency Max	: 11GHz
Connector Mounting	: Cable
Body Plating	: Nickel
Cable Diameter Max	: 2.8mm
Contact Resistance	: 1.5mΩ
DC Current Max	: 1A
Insulator Material	: PTFE
Material	: Brass with Silicone Gaskets
Operating Temperature	: -65°C to +165°C
Proof Voltage	: 2kV
VSWR	: 1.35
Working Voltage	: 500V


Connector interface per MIL-STD-348A Part to be clean and free of burrs











Dimensions : Millimetres (Inches)

Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro



Specification Table

Number	Description	Material	Finish
1	Shell	Zinc	Nickel 100µ" Minimum
2	Insulation	PTFE	None
3	Gasket	Rubber	
4	Washer	Brass	
5	Spring Washer	SK-5	
6	Washer	Brass	- Nickel 100µ" Minimum
7	Body I		
8	Centre Contact		Gold
9	Body II		
10	Nut I		Nickel 100µ" Minimum
11	Chassis		
12	Braid Clamp		
13	Gasket	Rubber	None
14	Washer	Brass	Niekol 100u" Minimum
15	Nut II		Nickel 100µ" Minimum

Part Number Table

Description	Part Number
Plug, BNC, Elbow, Clamp, 50R, RG174	13-06-4 TGN RG174

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro

