

Description

Joint sealing tape of polyurethane soft foam with acrylate dispersion impregnation, accessory agents and filling agents. 3-Level joint sealing system component.

Features

- ETA 06/0083 – LE/DoP 001/BG1/130625
- DIN 18542: 2009, stress group 1, materials testing agency for the building industry (Materials testing Agency)
- The heavy rain tightness and air permeability requirements of DIN EN 12207, Class 3 (former designation: DIN 18055, Group C), are exceeded.
- Very low emission Plus
- Externally monitored by the MPA Material Testing Agency for the Construction Industry

Applications

- Window construction
- Wood construction
- Prefabricated construction
- Masonry
- Framework construction
- Concrete construction

Specification

Colour		Grey
Stress Group	DIN 18542:2009	BG1, 090666.1 MPA
Fire Behaviour / Building material Class	DIN 4102-1	B1, Z-56.212-3501, DIBt, externally monitored by the MPA
Joint Permeability	DIN EN 12114	$a_n \leq 1$ (m ³ / h m dPa) ^{2/3} , 090666.1 MPA
Heavy Rain Tightness	DIN EN 1027	≥ 600 Pa, 090666.1 MPA
Temperature Resistant		Between - 30°C and 100°C, max. 130°C briefly
Rated Joint Noise Insulation Dimension	ift SC-01/2:2002-09	42 dB (One sealing tape without insulation and 2nd sealing level):
RST,ω		59 dB (Two sealing tapes without heat-insulating layer)
		167 37188, ift
Weathering Resistance	Artificial weathering:	> 10 years, test report No. 841.1219-5, MPA2
	Outdoor weathering:	> 15 years, test report No. 2009.1115, MPA2
Compatibility with Conventional Building Materials	DIN 18542:2009	Yes, 090666.1 MPA
Resistance to Alkaline Media	DIN 18542:2009	Yes, 090666.1 MPA
Tensile Strength	DIN EN ISO 1798	> 100 kPa
Elongation at Break	DIN EN ISO 1798	> 200 %
Compressive Strain Deformation Properties	DIN EN ISO 3386	3,4 kPa (± 15 %), 40 % deformation
Water Vapour Diffusion	DIN EN ISO 12572	sd < 0,5 m, 090666.1 MPA
Caloric Conductibility	DIN EN 12667	λ = 0,0429 W/mK, 083955.2, MPA
Emissions	EMICODE®	EC1Plus (2772/03.03.2010 GEV)
Storage Stability		18 months from the date of production

Part Number Table

Description	Part Number
Joint Sealing Tape, 5mm to 10mm × 20mm × 5.6m	MP005145
Joint Sealing Tape, 8mm to 15mm × 20mm × 3.3m	MP005146

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.