

MIKROELEKTRONIKA D.O.O, Batajnički drum 23, 11000 Belgrade, Serbia VAT: SR105917343 Registration No. 20490918

Phone: + 381 11 78 57 600 Fax: + 381 11 63 09 644 E-mail: office@mikroe.com www.mikroe.com

Clock Gen 3 Click





PID: MIKROE-4171

Clock Gen 3 Click features a low power self-contained digital frequency source providing a precision frequency from 1kHz to 68MHz, set through a serial port. This Click board™, an I2C configurable clock generator, features the LTC6904 from Linear Technology and requires no external components other than a power supply bypass capacitor, and it operates over a single wide supply voltage range of 2.7V to 5.5V. LTC6904 features a proprietary feedback loop that linearizes the relationship between digital control settings and frequency. It has many features that make it attractive for various applications such as a microcontroller clock source, clock source for a switched capacitor filter, or general replacement for a DAC/VCO combination.

Clock Gen 3 Click is supported by a mikroSDK compliant library, which includes functions that simplify software development. This Click board™ comes as a fully tested product, ready to be used on a system equipped with the mikroBUS[™] socket.

Mikroe produces entire development toolchains for all major microcontroller architectures. Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.







MIKROELEKTRONIKA D.O.O, Batajnički drum 23, 11000 Belgrade, Serbia VAT: SR105917343 Registration No. 20490918 Phone: + 381 11 78 57 600 Fax: + 381 11 63 09 644 E-mail: office@mikroe.com www.mikroe.com

Specifications

Туре	Clock generator
Applications	Can be used as a microcontroller clock source, clock source for a switched capacitor filter, or general replacement for a DAC/VCO combination.
On-board modules	LTC6904
Key Features	Precision frequency generator from 1KHz to 68MHz, minimal jitter and subharmonics at the output, on-board I2C address jumpers
Interface	I2C,GPIO
Compatibility	mikroBUS
Click board size	M (42.9 x 25.4 mm)
Input Voltage	3.3V,5V

Resources

mikroBUS™ Standard specification

LibStock: mikroSDK

Click board catalog

Click boards™ Standard Page

Downloads

Clock Gen 3 click 2D and 3D files

Clock Gen 3 click example on Libstock

LTC6904 datasheet

Clock Gen 3 click schematic

Mikroe produces entire development toolchains for all major microcontroller architectures.

Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.





health and safety management system.