

PRODUCT-DETAILS

TY400-50X

CBL TIE 50LB 14IN UV BLACK NYL



General Information

Extended Product Type	TY400-50X
Product ID	7TAG054360R0336
EAN	5414363064756
Catalog Description	CBL TIE 50LB 14IN UV BLACK NYL
Long Description	Cable Tie, Black Polyamide (Nylon 6.6) for Temperatures up to 105 Degrees Celsius (220 F), Weather and Ultraviolet Resistant for Indoor and Outdoor Applications, UL/EN/CSA62275 Type 2/215 Rated for AH-2 Plenum and as a Flexible Cable and Conduit Support, Length of 365.76mm (14.4 Inches), Width of 4.673mm (0.184 Inch), Thickness of 1.24mm (0.049 Inch), Tensile Strength Rating of 220 Newtons (50 Pounds), Bulk Pack

Ordering

EAN	5414363064756
Customs Tariff Number	3926909990

Dimensions

Product Net Weight	.005 lb 2.268 g
--------------------	--------------------

Container Information

Package Level 1 Units	1000 piece
-----------------------	------------

Package Level 1 Width	21 in 533 mm
Package Level 1 Height	4 in 102 mm
Package Level 1 Depth / Length	15 in 381 mm
Package Level 2 Units	5000 piece
Package Level 2 Width	13.1 in 333 mm
Package Level 2 Height	15.5 in 394 mm
Package Level 2 Depth / Length	19.6 in 498 mm

Additional Information

Brand / Label	Ty-Fast
Bundle Diameter	0.06 to 4.02 in 1.6 to 102 mm
Color	Black
Lock Type	Plastic Pawl
Material	Nylon/Polyamide 6.6 Weather Resistant
Number of Batteries	0
Product Name	PLASTIC CABLE TIE
Product Type	General Purpose
Special Functions	The integrally formed nylon pawl combines low insertion and high locking strength.
Standards	UL E49405
Tensile Strength	50 lb 220 N
Thickness	0.049 in 1.24 mm
UPC	786210898599

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	TY400-50X
Declaration of Conformity - CE	9AKK107492A9843
Instructions and Manuals	TY400-50X

Classifications

ETIM 6	EC000046 - Cable tie
ETIM 7	EC000046 - Cable tie
UNSPSC	39121703
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5034 >> Cable ties

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Cable Ties

