



Specifications:

Mechanical

Operating force	: 260 ±50gf Red (R)
Maximum stop strength	: 3kgf vertical static load continuously for 15 seconds
Stroke	: 0.25 + 0.2mm/ -0.1mm (6 × 6)
Operating temperature	: -25°C to +70°C
Storage temperature	: -30° to +80°C

Electrical


Electrical life	: 500,000 cycles for 260gf (6 × 6)
Rating	: 50mA, 12V DC
Maximum contact resistance	: 100MΩ
Minimum insulation resistance	: 100MΩ at 500V DC
Dielectric strength	: 250V AC/Minute
Maximum capacitance	: 5pF
Contact arrangement	: SPST

Materials

Cover	: Steel, tin plated
Base	: Nylon thermoplastic
Base colour	: Black
Stem	: Nylon thermoplastic
Stem colour	: Red (260gf)
Contact disc	: Phosphor bronze with silver cladding (standard) Stainless steel (v-option)
Terminal	: Brass with silver plated

Soldering Process:

- Wave soldering : Recommended solder temperature at 500°F (260°C) maximum 5 seconds subject to PCB 1.6mm thickness (for through hole type).
- Hand soldering : Use a soldering iron of 30 watts, controlled at 350°C approximately 5 seconds while applying solder.



Dimensions : Millimetres (Inches)

Part Number Table

Description	I (Maximum)	H	Part Number
Tactile Switch, R/A, 3.85mm 260G	0.4 (0.016)	3.85 (0.152)	MCDTSA6-2R

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.