

# Final Product/Process Change Notification

Document #:FPCN23545X Issue Date:24 Aug 2020

| Title of Change:                          | NCP1256 temperature range spec change  |  |
|---|--|--|
| Proposed First Ship date:                 | 30 Nov 2020 or earlier if approved by customer   |  |
| Contact Information:                      | Contact your local ON Semiconductor Sales Office or Jiri.Konarik@onsemi.com  |  |
| PCN Samples Contact:                      | Contact your local ON Semiconductor Sales Office or <pcn.samples@onsemi.com>.  Sample requests are to be submitted no later than 30 days from the date of first notification, Initial PCN or Final PCN, for this change.  Samples delivery timing will be subject to request date, sample quantity and special customer packing/label requirements.</pcn.samples@onsemi.com> |  |
| Additional Reliability Data:              | Contact your local ON Semiconductor Sales Office   |  |
| Type of Notification:                     | This is a Final Product/Process Change Notification (FPCN) sent to customers. FPCNs are issued 90 days prior to implementation of the change.  ON Semiconductor will consider this change accepted, unless an inquiry is made in writing within 30 days of delivery of this notice. To do so, contact PCN.Support@onsemi.com   |  |
| Marking of Parts/ Traceability of Change: | Affected products will be identified with date code WW48 2020  |  |
| Change Category:                          | Test Change  |  |
| Change Sub-Category(s):                   | Datasheet/Product Doc change   |  |

# **Sites Affected:**

| ON Semiconductor Sites              | External Foundry/Subcon Sites |
|-------------------------------------|-------------------------------|
| ON Semiconductor Seremban, Malaysia | HANA Semiconductor, Thailand  |

### **Description and Purpose:**

Temperature range for OPPgm parameter will be updated from -40°C ~ 125°C to 25°C~ 125°C. Relaxed min OPPgm to 101  $\mu$ S for whole temperature range.

| Parameter   | Symbol | Min | Тур | Max | Unit |
|---|--------|-----|-----|-----|------|
|   |        |     |     |     |      |
| Internal OTA for OPP current generation from BO (-40°C ~ 125°C)                                 | OPPgm  | 101 | 115 | 125 | μS   |
| Internal OTA for OPP current generation from BO $(25^{\circ}\text{C} \sim 125^{\circ}\text{C})$ |        | 103 | 115 | 123 | μ    |

There is no product marking change as a result of this change.

## **Reliability Data Summary:**

Reliability data summary not applicable as the only apply to the final test limit relaxation.

### **Electrical Characteristics Summary:**

Device specification changes can be found in section "Description and purpose"

TEM001793 Rev. C Page 1 of 2



# Final Product/Process Change Notification Document #:FPCN23545X

Issue Date:24 Aug 2020

#### **List of Affected Parts:**

**Note:** Only the standard (off the shelf) part numbers are listed in the parts list. Any custom parts affected by this PCN are shown in the customer specific PCN addendum in the PCN email notification, or on the <u>PCN Customized Portal</u>.

| Part Number      | Qualification Vehicle |  |  |
|------------------|-----------------------|--|--|
| NCP1256ASN100T1G | NA                    |  |  |
| NCP1256ASN65T1G  | NA                    |  |  |
| NCP1256BSN100T1G | NA                    |  |  |
| NCP1256BSN65T1G  | NA                    |  |  |
| NCP1256ESN65T1G  | NA                    |  |  |

TEM001793 Rev. C Page 2 of 2