TE Internal #: 2367286-2


Antenna, LTE, Chassis, Adhesive, Cable Assembly, MHF

Compatible, Cable Length 50 mm [1.969 in]

View on TE.com >



#### Antennas



Wireless Application: LTE

Mounts To: Chassis

Mounting Retention Type: Adhesive

Antenna Connection Type: Cable Assembly
Antenna Connector Type: MHF Compatible

### **Features**

### **Product Type Features**

Antenna Connection Type	Cable Assembly			
Antenna Connector Type	MHF Compatible			
Configuration Features				
Band Type	3 Band			
Antenna Protocol	LTE / UMTS / US DUAL / EU TRIVAND / WCDMA			
Number of Ports	1			
Antenna Style	Embedded			
Antenna Type	Thin PCB			
Electrical Characteristics				
VSWR (Max)	<4.0:1			
Impedance	50 Ω			
Active Antenna	No			

1710 – 2170 MHz, 2300 – 2700 MHz, 698 –

960 MHz

Signal Characteristics

Frequency Band



Gain (Max)	4 dB
Body Features	
Product Weight	2.6 g[.092 oz]
Mechanical Attachment	
Region	Global
Polarization	Linear
Mounts To	Chassis
Mounting Retention Type	Adhesive
Dimensions	
Product Diameter	1.13 mm[.044 in]
Cable Insulation Diameter (Max)	.7 mm[.028 in]
Cable Length	50 mm[1.969 in]
Product Length	65 mm[2.56 in]
Product Width	15 mm[.59 in]
Product Height	.19 mm[.007 in]
Usage Conditions	
Application by Region	LTE All Band - 1710 – 2700 MHz, LTE All Band - 698 – 960 MHz
Operation/Application	
Wireless Standard	LTE, UMTS, US Dual, EU Triband & WCDMA
Industry Standards	
Wireless Application	LTE
Packaging Features	
Packaging Method	Bag & Box

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUN 2020 (209)



Candidate List Declared Against: JAN 2020	
(205)	

Does not contain REACH SVHC

Halogen Content	Low Bromine/Chlorine - Br and Cl < 900
	ppm per homogenous material. Also BFR
	/CFR/PVC Free

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## Compatible Parts



# Customers Also Bought



TE Model / Part #1766600-2 INSULATION BOOT,#2,RED



TE Model / Part #T4151410004-002 M12 A-CODE FEMALE R/A SINGLE ENDED CABL




TE Model / Part #1062-16-0177
DEUTSCH STAMPED & FORMED
CONTACTS









RNF-100-1/16-8-SP









### **Documents**

### **Product Drawings**

LTE ANTENNA COTS FPC ASSEMBLY 50mm Cable

English

### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_2367286-2\_1.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2367286-2\_1.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2367286-2\_1.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

DS\_PN-2367286-X

English