



## Safety Data Sheet according to Regulation (EC) No 1907/2006

Page 1 of 14

LOCTITE SF 7414 known as LOCTITE 7414 50ML VE48

SDS No. : 310207  
V007.0

Revision: 24.05.2018

printing date: 26.11.2020

Replaces version from: 26.10.2016

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

LOCTITE SF 7414 known as LOCTITE 7414 50ML VE48

#### Contains:

Xylene - mixture of isomeres

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Tamper proofing.

#### 1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 1442 278000

Fax-no.: +44 1442 278071

ua-productsafety.uk@henkel.com

#### 1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (CLP):

Flammable liquids	Category 3
H226 Flammable liquid and vapor.	
Skin irritation	Category 2
H315 Causes skin irritation.	
Serious eye irritation	Category 2
H319 Causes serious eye irritation.	
Specific target organ toxicity - single exposure	Category 3
H335 May cause respiratory irritation.	
Target organ: respiratory tract irritation	
Specific target organ toxicity - repeated exposure	Category 2
H373 May cause damage to organs through prolonged or repeated exposure.	

#### 2.2. Label elements

##### Label elements (CLP):

**Hazard pictogram:****Signal word:**

Warning

**Hazard statement:**

H226 Flammable liquid and vapor.  
 H315 Causes skin irritation.  
 H319 Causes serious eye irritation.  
 H335 May cause respiratory irritation.  
 H373 May cause damage to organs through prolonged or repeated exposure.

**Precautionary statement:  
Prevention**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.  
 No smoking.  
 P261 Avoid breathing vapours.

**Precautionary statement:  
Response**

P302+P352 IF ON SKIN: Wash with plenty of soap and water.  
 P337+P313 If eye irritation persists: Get medical advice/attention.

**2.3. Other hazards**

None if used properly.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures****Declaration of the ingredients according to CLP (EC) No 1272/2008:**

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Xylene - mixture of isomeres 1330-20-7	215-535-7 01-2119488216-32	10- < 25 %	Asp. Tox. 1 H304 Acute Tox. 4; Inhalation H332 Acute Tox. 4; Dermal H312 Skin Irrit. 2 H315 Flam. Liq. 3 H226 Eye Irrit. 2 H319 STOT SE 3 H335 STOT RE 2 H373

For full text of the H - statements and other abbreviations see section 16 "Other information".

Substances without classification may have community workplace exposure limits available.

**SECTION 4: First aid measures****4.1. Description of first aid measures****Inhalation:**

Move to fresh air. If symptoms persist, seek medical advice.

**Skin contact:**

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

#### **4.2. Most important symptoms and effects, both acute and delayed**

SKIN: Redness, inflammation.

EYE: Irritation, conjunctivitis.

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

#### **4.3. Indication of any immediate medical attention and special treatment needed**

See section: Description of first aid measures

### **SECTION 5: Firefighting measures**

#### **5.1. Extinguishing media**

##### **Suitable extinguishing media:**

Carbon dioxide, foam, powder

##### **Extinguishing media which must not be used for safety reasons:**

High pressure waterjet

#### **5.2. Special hazards arising from the substance or mixture**

In case of fire, keep containers cool with water spray.  
carbon oxides.

#### **5.3. Advice for firefighters**

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

### **SECTION 6: Accidental release measures**

#### **6.1. Personal precautions, protective equipment and emergency procedures**

Avoid skin and eye contact.

Ensure adequate ventilation.

Wear protective equipment.

#### **6.2. Environmental precautions**

Do not empty into drains / surface water / ground water.

#### **6.3. Methods and material for containment and cleaning up**

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

Dispose of contaminated material as waste according to Section 13.

#### **6.4. Reference to other sections**

See advice in section 8

### **SECTION 7: Handling and storage**

#### **7.1. Precautions for safe handling**

Use only in well-ventilated areas.

Avoid skin and eye contact.

Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation.

See advice in section 8

Avoid open flames and sources of ignition.

Hygiene measures:

- Good industrial hygiene practices should be observed.
- Wash hands before work breaks and after finishing work.
- Do not eat, drink or smoke while working.

**7.2. Conditions for safe storage, including any incompatibilities**

Refer to Technical Data Sheet

**7.3. Specific end use(s)**

Tamper proofing.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational Exposure Limits

Valid for  
Great Britain

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Limestone 1317-65-3 [CALCIUM CARBONATE, INHALABLE DUST]		10	Time Weighted Average (TWA):		EH40 WEL
Limestone 1317-65-3 [CALCIUM CARBONATE, RESPIRABLE DUST]		4	Time Weighted Average (TWA):		EH40 WEL
Limestone 1317-65-3 [LIMESTONE, RESPIRABLE MARBLE, RESPIRABLE]		4	Time Weighted Average (TWA):		EH40 WEL
Limestone 1317-65-3 [LIMESTONE, TOTAL INHALABLE MARBLE, TOTAL INHALABLE]		10	Time Weighted Average (TWA):		EH40 WEL
Xylene 1330-20-7 [XYLENE, O-, M-, P- OR MIXED ISOMERS]			Skin designation:	Can be absorbed through the skin.	EH40 WEL
Xylene 1330-20-7 [XYLENE, O-, M-, P- OR MIXED ISOMERS]	100	441	Short Term Exposure Limit (STEL):		EH40 WEL
Xylene 1330-20-7 [XYLENE, O-, M-, P- OR MIXED ISOMERS]	50	220	Time Weighted Average (TWA):		EH40 WEL
Xylene 1330-20-7 [XYLENE, MIXED ISOMERS, PURE]	50	221	Time Weighted Average (TWA):	Indicative	ECTLV
Xylene 1330-20-7 [XYLENE, MIXED ISOMERS, PURE]	100	442	Short Term Exposure Limit (STEL):	Indicative	ECTLV
Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> ) 14807-96-6 [TALC, RESPIRABLE DUST]		1	Time Weighted Average (TWA):		EH40 WEL

#### Occupational Exposure Limits

Valid for  
Ireland

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Limestone 1317-65-3 [CALCIUM CARBONATE, RESPIRABLE DUST]		4	Time Weighted Average (TWA):		IR_OEL
Limestone 1317-65-3 [CALCIUM CARBONATE, TOTAL INHALABLE DUST]		10	Time Weighted Average (TWA):		IR_OEL
Xylene 1330-20-7 [XYLENE, MIXED ISOMERS]	100	442	Short Term Exposure Limit (STEL):	Indicative OELV	IR_OEL
Xylene 1330-20-7 [XYLENE, MIXED ISOMERS]			Skin designation:	Can be absorbed through the skin.	IR_OEL
Xylene 1330-20-7 [XYLENE, MIXED ISOMERS]	50	221	Time Weighted Average (TWA):	Indicative OELV	IR_OEL

Xylene 1330-20-7 [XYLENE, MIXED ISOMERS, PURE]	50	221	Time Weighted Average (TWA):	Indicative	ECTLV
Xylene 1330-20-7 [XYLENE, MIXED ISOMERS, PURE]	100	442	Short Term Exposure Limit (STEL):	Indicative	ECTLV
Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> ) 14807-96-6 [TALC, TOTAL INHALABLE DUST]		10	Time Weighted Average (TWA):		IR_OEL
Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> ) 14807-96-6 [TALC, RESPIRABLE DUST]		0,8	Time Weighted Average (TWA):		IR_OEL

**Predicted No-Effect Concentration (PNEC):**

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Xylene - mixture of isomeres 1330-20-7	aqua (freshwater)		0,327 mg/l				
Xylene - mixture of isomeres 1330-20-7	sediment (freshwater)				12,46 mg/kg		
Xylene - mixture of isomeres 1330-20-7	soil				2,31 mg/kg		
Xylene - mixture of isomeres 1330-20-7	aqua (marine water)		0,327 mg/l				
Xylene - mixture of isomeres 1330-20-7	aqua (intermittent releases)		0,327 mg/l				
Xylene - mixture of isomeres 1330-20-7	sewage treatment plant (STP)		6,58 mg/l				
Xylene - mixture of isomeres 1330-20-7	sediment (marine water)				12,46 mg/kg		

**Derived No-Effect Level (DNEL):**

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Xylene - mixture of isomeres 1330-20-7	Workers	Inhalation	Acute/short term exposure - systemic effects		289 mg/m <sup>3</sup>	
Xylene - mixture of isomeres 1330-20-7	Workers	Inhalation	Acute/short term exposure - local effects		289 mg/m <sup>3</sup>	
Xylene - mixture of isomeres 1330-20-7	Workers	dermal	Long term exposure - systemic effects		180 mg/kg	
Xylene - mixture of isomeres 1330-20-7	Workers	Inhalation	Long term exposure - systemic effects		77 mg/m <sup>3</sup>	
Xylene - mixture of isomeres 1330-20-7	General population	Inhalation	Acute/short term exposure - systemic effects		174 mg/m <sup>3</sup>	
Xylene - mixture of isomeres 1330-20-7	General population	Inhalation	Acute/short term exposure - local effects		174 mg/m <sup>3</sup>	
Xylene - mixture of isomeres 1330-20-7	General population	dermal	Long term exposure - systemic effects		108 mg/kg	
Xylene - mixture of isomeres 1330-20-7	General population	Inhalation	Long term exposure - systemic effects		14,8 mg/m <sup>3</sup>	
Xylene - mixture of isomeres 1330-20-7	Workers	Inhalation	Long term exposure - local effects		77 mg/m <sup>3</sup>	
Xylene - mixture of isomeres 1330-20-7	General population	oral	Long term exposure - systemic effects		1,6 mg/kg	

**Biological Exposure Indices:**

Ingredient [Regulated substance]	Parameters	Biological specimen	Sampling time	Conc.	Basis of biol. exposure index	Remark	Additional Information
Xylene 1330-20-7 [XYLENE O-, M-, P-, OR MIXED ISOMERS]	Methylhippuric acids	Creatinine in urine	Sampling time: End of shift.		UKEH40BMG V		

**8.2. Exposure controls:**

Engineering controls:  
Ensure good ventilation/extraction.

Respiratory protection:  
Ensure adequate ventilation.  
An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area  
Filter type: A (EN 14387)

Hand protection:  
Chemical-resistant protective gloves (EN 374).  
Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):  
nitrile rubber (NBR; >= 0.4 mm thickness)  
Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):  
nitrile rubber (NBR; >= 0.4 mm thickness)  
This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:  
Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.  
Protective eye equipment should conform to EN166.

Skin protection:  
Wear suitable protective clothing.  
Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Appearance	liquid liquid blue
Odor	characteristic
Odour threshold	No data available / Not applicable
pH	Not applicable
Melting point	No data available / Not applicable
Solidification temperature	No data available / Not applicable
Initial boiling point	137,0 °C (278.6 °F)
Flash point	30,00 °C (86 °F)
Evaporation rate	No data available / Not applicable

Flammability	No data available / Not applicable
Explosive limits	No data available / Not applicable
Vapour pressure	6,7000000 mbar
Vapour pressure	670 Pa
Relative vapour density:	No data available / Not applicable
Density	1,2000 g/cm <sup>3</sup>
( )	
Bulk density	No data available / Not applicable
Solubility	No data available / Not applicable
Solubility (qualitative)	Not miscible
(Solvent: Water)	
Partition coefficient: n-octanol/water	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Decomposition temperature	No data available / Not applicable
Viscosity	105.000 mPa.s
(; 20 °C (68 °F))	
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Oxidising properties	No data available / Not applicable

## 9.2. Other information

Ignition temperature 500,0 °C (932 °F)

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

None if used properly.

### 10.2. Chemical stability

Stable under recommended storage conditions.

### 10.3. Possibility of hazardous reactions

See section reactivity

### 10.4. Conditions to avoid

Stable under normal conditions of storage and use.

### 10.5. Incompatible materials

No data available.

### 10.6. Hazardous decomposition products

carbon oxides.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Xylene - mixture of isomeres 1330-20-7	LD50	3.523 mg/kg	rat	EU Method B.1 (Acute Toxicity (Oral))



**Acute dermal toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Xylene - mixture of isomeres 1330-20-7	LD50	1.700 mg/kg	rabbit	not specified

**Acute inhalative toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
Xylene - mixture of isomeres 1330-20-7	LC50	11 mg/l	vapour	4 h	rat	not specified

**Skin corrosion/irritation:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Xylene - mixture of isomeres 1330-20-7	moderately irritating		rabbit	not specified

**Serious eye damage/irritation:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Xylene - mixture of isomeres 1330-20-7	slightly irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

**Respiratory or skin sensitization:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Xylene - mixture of isomeres 1330-20-7	not sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)

**Germ cell mutagenicity:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Xylene - mixture of isomeres 1330-20-7	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Xylene - mixture of isomeres 1330-20-7	negative	in vitro mammalian chromosome aberration test	with and without		EU Method B.10 (Mutagenicity)
Xylene - mixture of isomeres 1330-20-7	negative	sister chromatid exchange assay in mammalian cells	with and without		EU Method B.19 (Sister Chromatid Exchange Assay In Vitro)
Xylene - mixture of isomeres 1330-20-7	negative	intraperitoneal		rat	OECD Guideline 478 (Genetic Toxicology: Rodent Dominant Lethal Test)

**Carcinogenicity**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
Xylene - mixture of isomeres 1330-20-7	not carcinogenic	oral: gavage	103 w 5 d/w	rat	male/female	EU Method B.32 (Carcinogenicity Test)

**Reproductive toxicity:**

No data available.

**STOT-single exposure:**

No data available.

**STOT-repeated exposure::**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Xylene - mixture of isomeres 1330-20-7	NOAEL 150 mg/kg	oral: gavage	90 d daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

**Aspiration hazard:**

No data available.

## SECTION 12: Ecological information

### General ecological information:

Do not empty into drains / surface water / ground water.

### 12.1. Toxicity

#### Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Xylene - mixture of isomers 1330-20-7	LC50	86 mg/l		Leuciscus idus	OECD Guideline 203 (Fish, Acute Toxicity Test)

#### Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Xylene - mixture of isomers 1330-20-7	EC50	3,1 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

#### Chronic toxicity to aquatic invertebrates

No data available.

#### Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Xylene - mixture of isomers 1330-20-7	EC50	2,2 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)

#### Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Xylene - mixture of isomers 1330-20-7	EC 50	> 1 - 10 mg/l			not specified

### 12.2. Persistence and degradability

The product is not biodegradable.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Xylene - mixture of isomers 1330-20-7	readily biodegradable	aerobic	> 60 %		OECD 301 A - F

### 12.3. Bioaccumulative potential

No data available for the product.

Hazardous substances CAS-No.	Bioconcentratio n factor (BCF)	Exposure time	Temperature	Species	Method
Xylene - mixture of isomers 1330-20-7	8,5	7 d		Oncorhynchus mykiss	not specified

**12.4. Mobility in soil**

Cured adhesives are immobile.

Hazardous substances CAS-No.	LogPow	Temperature	Method
Xylene - mixture of isomers 1330-20-7	3,12		not specified

**12.5. Results of PBT and vPvB assessment**

Hazardous substances CAS-No.	PBT / vPvB
Xylene - mixture of isomers 1330-20-7	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

**12.6. Other adverse effects**

No data available.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods**

Product disposal:

Dispose of in accordance with local and national regulations.

Contribution of this product to waste is very insignificant in comparison to article in which it is used

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

Waste code

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

**SECTION 14: Transport information****14.1. UN number**

ADR	1263
RID	1263
ADN	1263
IMDG	1263
IATA	1263

**14.2. UN proper shipping name**

ADR	PAINT
RID	PAINT
ADN	PAINT
IMDG	PAINT
IATA	Paint

**14.3. Transport hazard class(es)**

ADR	3
RID	3
ADN	3
IMDG	3
IATA	3

**14.4. Packing group**

ADR	III
RID	III
ADN	III
IMDG	III
IATA	III

**14.5. Environmental hazards**

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

**14.6. Special precautions for user**

ADR	not applicable Tunnelcode: (D/E)
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

not applicable

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

VOC content < 30,00 %  
(2010/75/EC)

**15.2. Chemical safety assessment**

A chemical safety assessment has not been carried out.

**SECTION 16: Other information**

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H226 Flammable liquid and vapor.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

**Further information:**

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

**Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.**