



Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 11

LOCTITE UK 1367B10/5452

SDS No. : 571800
V003.0

Revision: 31.03.2020

printing date: 26.11.2020

Replaces version from: 23.09.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE UK 1367B10/5452

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

2-Component polyurethane adhesive

1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 1442 278000

Fax-no.: +44 1442 278071

ua-productsafety.uk@henkel.com

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 0 8701 906777 - For further general health & safety, technical and practical advice on this product, please call +44 (0) 1606 593933 or write to: Technical Services; Henkel Limited; Road 5; Winsford Industrial Estate; Winsford; Cheshire; CW7 3QY- Email: technical.services@henkel.co.uk

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

2.2. Label elements

Label elements (CLP):

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

Supplemental information

Safety data sheet available on request.

2.3. Other hazards

None if used properly.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General chemical description:

2-Component polyurethane adhesive

Base substances of preparation:

Polyurethane prepolymer

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Glyceryl polypropylene glycol ether 25791-96-2		5- < 10 %	Acute Tox. 4; Oral H302
methyl 5-(dimethylamino)-2-methyl-5-oxopentanoate 1174627-68-9	01-2119497421-36	1- < 5 %	Eye Irrit. 2 H319

For full text of the H - statements and other abbreviations see section 16 "Other information".

Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air, consult doctor if complaint persists.

Skin contact:

Rinse with running water and soap. Apply replenishing cream. Change all contaminated clothing.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

All common extinguishing agents are suitable.

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In case of fire toxic gases can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus.

Wear protective equipment.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Wear protective equipment.

Danger of slipping on spilled product.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Allow to solidify.

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction.

Store in sealed original container.

< + 30 °C

> + 15 °C

7.3. Specific end use(s)

2-Component polyurethane adhesive

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Great Britain

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Calcium carbonate 471-34-1 [CALCIUM CARBONATE, INHALABLE DUST]		10	Time Weighted Average (TWA):		EH40 WEL
Calcium carbonate 471-34-1 [CALCIUM CARBONATE, RESPIRABLE DUST]		4	Time Weighted Average (TWA):		EH40 WEL
Calcium carbonate 471-34-1 [LIMESTONE, RESPIRABLE MARBLE, RESPIRABLE]		4	Time Weighted Average (TWA):		EH40 WEL
Calcium carbonate 471-34-1 [LIMESTONE, TOTAL INHALABLE MARBLE, TOTAL INHALABLE]		10	Time Weighted Average (TWA):		EH40 WEL
Zeolites 68989-22-0 [ALUMINIUM OXIDES, INHALABLE DUST]		10	Time Weighted Average (TWA):		EH40 WEL
Zeolites 68989-22-0 [ALUMINIUM OXIDES, RESPIRABLE DUST]		4	Time Weighted Average (TWA):		EH40 WEL
Dolomite 16389-88-1 [DUST, INHALABLE DUST]		10	Time Weighted Average (TWA):		EH40 WEL
Dolomite 16389-88-1 [DUST, RESPIRABLE DUST]		4	Time Weighted Average (TWA):		EH40 WEL

Occupational Exposure Limits

Valid for
Ireland

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Calcium carbonate 471-34-1 [CALCIUM CARBONATE, RESPIRABLE DUST]		4	Time Weighted Average (TWA):		IR_OEL
Calcium carbonate 471-34-1 [CALCIUM CARBONATE, TOTAL INHALABLE DUST]		10	Time Weighted Average (TWA):		IR_OEL
Dolomite 16389-88-1 [DUSTS, NON-SPECIFIC, RESPIRABLE]		4	Time Weighted Average (TWA):		IR_OEL
Dolomite 16389-88-1 [DUSTS, NON-SPECIFIC, TOTAL INHALABLE]		10	Time Weighted Average (TWA):		IR_OEL

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
methyl 5-(dimethylamino)-2-methyl-5-oxopentanoate 1174627-68-9	Workers	dermal	Long term exposure - systemic effects		42 mg/kg	
methyl 5-(dimethylamino)-2-methyl-5-oxopentanoate 1174627-68-9	Workers	inhalation	Long term exposure - systemic effects		29 mg/m ³	
methyl 5-(dimethylamino)-2-methyl-5-oxopentanoate 1174627-68-9	General population	dermal	Long term exposure - systemic effects		20,8 mg/kg	
methyl 5-(dimethylamino)-2-methyl-5-oxopentanoate 1174627-68-9	General population	inhalation	Long term exposure - systemic effects		7 mg/m ³	
methyl 5-(dimethylamino)-2-methyl-5-oxopentanoate 1174627-68-9	General population	oral			4,2 mg/kg	

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

In case of dust formation, we recommend wearing of appropriate respiratory protection equipment with particle filter P (EN 14387).

This recommendation should be matched to local conditions.

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; \geq 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; \geq 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Protective goggles

Protective eye equipment should conform to EN166.

Skin protection:

Wear protective equipment.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

Use only personal protection that's CE-labelled according to Directive 89/686/EEC (Europe) or to Regulation No. 819 of 19 August 1994 (Norway).

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	paste paste beige
Odor	characteristic
Odour threshold	No data available / Not applicable
pH	No data available / Not applicable
Melting point	No data available / Not applicable
Solidification temperature	No data available / Not applicable
Initial boiling point	No data available / Not applicable
Flash point	178 °C (352.4 °F)
Evaporation rate	No data available / Not applicable
Flammability	No data available / Not applicable
Explosive limits	No data available / Not applicable
Vapour pressure	No data available / Not applicable
Relative vapour density:	No data available / Not applicable
Density (20 °C (68 °F))	1,39 - 1,47 g/cm ³
Bulk density	No data available / Not applicable
Solubility	No data available / Not applicable
Solubility (qualitative)	No data available / Not applicable
Partition coefficient: n-octanol/water	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Decomposition temperature	No data available / Not applicable
Viscosity (Brookfield; Instrument: RVT; 20 °C (68 °F); speed of rotation: 5 min ⁻¹ ; Spindle No: 7)	350.000 - 550.000 mPa.s
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Oxidising properties	No data available / Not applicable

9.2. Other information

No data available / Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

None if used for intended purpose.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

None if used for intended purpose.

10.5. Incompatible materials

None if used properly.

10.6. Hazardous decomposition products

No decomposition if used according to specifications.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
methyl 5-(dimethylamino)-2-methyl-5-oxopentanoate 1174627-68-9	LD50	> 2.000 mg/kg	rat	OECD Guideline 423 (Acute Oral toxicity)

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
methyl 5-(dimethylamino)-2-methyl-5-oxopentanoate 1174627-68-9	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)

Acute inhalative toxicity:

No data available.

Skin corrosion/irritation:

No data available.

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
methyl 5-(dimethylamino)-2-methyl-5-oxopentanoate 1174627-68-9	irritating	1 h	rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

No data available.

Germ cell mutagenicity:

No data available.

Carcinogenicity

No data available.

Reproductive toxicity:

No data available.

STOT-single exposure:

No data available.

STOT-repeated exposure::

No data available.

Aspiration hazard:

No data available.

SECTION 12: Ecological information**General ecological information:**

Do not empty into drains, soil or bodies of water.

12.1. Toxicity**Toxicity (Fish):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
methyl 5-(dimethylamino)-2-methyl-5-oxopentanoate 1174627-68-9	LC50	> 100 mg/l	96 h	Brachydanio rerio (new name: Danio rerio)	OECD Guideline 203 (Fish, Acute Toxicity Test)

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
methyl 5-(dimethylamino)-2-methyl-5-oxopentanoate 1174627-68-9	EC50	> 100 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
methyl 5-(dimethylamino)-2-methyl-5-oxopentanoate 1174627-68-9	NOEC	> 100 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
methyl 5-(dimethylamino)-2-methyl-5-oxopentanoate 1174627-68-9	EC50	> 100 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
methyl 5-(dimethylamino)-2-methyl-5-oxopentanoate 1174627-68-9	NOEC	100 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
methyl 5-(dimethylamino)-2-methyl-5-oxopentanoate 1174627-68-9	NOEC	1.000 mg/l	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

12.2. Persistence and degradability

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
methyl 5-(dimethylamino)-2-methyl-5-oxopentanoate 1174627-68-9	not readily biodegradable.	aerobic	33,7 %	28 day	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
methyl 5-(dimethylamino)-2-methyl-5-oxopentanoate 1174627-68-9	inherently biodegradable	aerobic	95,8 %	28 day	OECD Guideline 302 B (Inherent biodegradability: Zahn-Wellens/EMPA Test)

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

Hazardous substances CAS-No.	LogPow	Temperature	Method
methyl 5-(dimethylamino)-2-methyl-5-oxopentanoate 1174627-68-9	0,39		OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)

12.5. Results of PBT and vPvB assessment

Hazardous substances CAS-No.	PBT / vPvB
methyl 5-(dimethylamino)-2-methyl-5-oxopentanoate 1174627-68-9	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

In consultation with the responsible local authority, must be subjected to special treatment.

Waste code

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

08 04 10 Waste adhesives and sealants other than those mentioned in 08 04 09.

SECTION 14: Transport information

- 14.1. UN number**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.2. UN proper shipping name**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.3. Transport hazard class(es)**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.4. Packing group**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.5. Environmental hazards**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.6. Special precautions for user**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**
not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

VOC content 0 %
(VOCV 814.018 VOC regulation
CH)

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H302 Harmful if swallowed.

H319 Causes serious eye irritation.

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.



Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 18

LOCTITE UK 1367B10/5452

SDS No. : 315035
V003.0

Revision: 31.03.2020

printing date: 26.11.2020

Replaces version from: 08.08.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE UK 1367B10/5452

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

2-Component polyurethane adhesive

1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 1442 278000

Fax-no.: +44 1442 278071

ua-productsafety.uk@henkel.com

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 0 8701 906777 - For further general health & safety, technical and practical advice on this product, please call +44 (0) 1606 593933 or write to: Technical Services; Henkel Limited; Road 5; Winsford Industrial Estate; Winsford; Cheshire; CW7 3QY- Email: technical.services@henkel.co.uk

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Acute toxicity H332 Harmful if inhaled. Route of Exposure: Inhalation	Category 4
Skin irritation H315 Causes skin irritation.	Category 2
Serious eye irritation H319 Causes serious eye irritation.	Category 2
Respiratory sensitizer H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.	Category 1
Skin sensitizer H317 May cause an allergic skin reaction.	Category 1
Carcinogenicity H351 Suspected of causing cancer.	Category 2
Specific target organ toxicity - single exposure H335 May cause respiratory irritation. Target organ: respiratory tract irritation	Category 3
Specific target organ toxicity - repeated exposure H373 May cause damage to organs through prolonged or repeated exposure.	Category 2

2.2. Label elements**Label elements (CLP):****Hazard pictogram:****Contains**

Diphenylmethane diisocyanate, isomers and homologues

Signal word:

Danger

Hazard statement:

H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H332 Harmful if inhaled.
 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 H335 May cause respiratory irritation.
 H351 Suspected of causing cancer.
 H373 May cause damage to organs through prolonged or repeated exposure.

**Precautionary statement:
Prevention**

P201 Obtain special instructions before use.
 P260 Do not breathe vapours.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.

**Precautionary statement:
Response**

P308+P313 IF exposed or concerned: Get medical advice/attention.

2.3. Other hazards

Persons suffering from allergic reactions to isocyanates should avoid contact with the product.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****General chemical description:**

Hardening component of a 2-component PU adhesive

Base substances of preparation:

Isocyanate

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9		40- 60 %	Carc. 2 H351 Acute Tox. 4; Inhalation H332 STOT RE 2 H373 Eye Irrit. 2 H319 STOT SE 3 H335 Skin Irrit. 2 H315 Resp. Sens. 1 H334 Skin Sens. 1 H317
4,4'- methylenediphenyl diisocyanate 101-68-8	202-966-0 01-2119457014-47	40- 60 %	Carc. 2 H351 Acute Tox. 4; Inhalation H332 STOT RE 2 H373 Eye Irrit. 2 H319 STOT SE 3 H335 Skin Irrit. 2 H315 Resp. Sens. 1 H334 Skin Sens. 1B H317
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	227-534-9 01-2119480143-45	1- < 5 %	STOT RE 2 H373 Carc. 2 H351 Acute Tox. 4; Inhalation H332 Eye Irrit. 2 H319 STOT SE 3 H335 Skin Irrit. 2 H315 Skin Sens. 1 H317 Resp. Sens. 1 H334
2,2'-Methylenediphenyl diisocyanate 2536-05-2	219-799-4 01-2119927323-43	0,1- < 1 %	STOT RE 2 H373 Carc. 2 H351 Acute Tox. 4; Inhalation H332 Eye Irrit. 2 H319 STOT SE 3 H335 Skin Irrit. 2 H315 Resp. Sens. 1 H334 Skin Sens. 1 H317

**For full text of the H - statements and other abbreviations see section 16 "Other information".
Substances without classification may have community workplace exposure limits available.**

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

Symptoms of poisoning may occur even after several hours, continue medical observation for at least 48 hours after the accident.

Inhalation:

Fresh air, oxygen supply, warmth; seek specialist medical attention.

Delayed effects possible after inhalation.

Skin contact:

IF ON SKIN: Wash with plenty of soap and water.

In case of adverse health effects seek medical advice.

Eye contact:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

SKIN: Redness, inflammation.

EYE: Irritation, conjunctivitis.

SKIN: Rash, Urticaria.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

All common extinguishing agents are suitable.

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In case of fire toxic gases can be released.

5.3. Advice for firefighters

Wear protective equipment.

Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear protective equipment.

Avoid contact with skin and eyes.

Keep unprotected persons away.

Danger of slipping on spilled product.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Remove with liquid-absorbing material (sand, peat, sawdust).

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Hygiene measures:

Do not eat, drink or smoke while working.

Wash hands before work breaks and after finishing work.

Take off contaminated clothing and wash before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction.

> + 15 °C

Avoid moisture.

< + 30 °C

Store in sealed original container.

7.3. Specific end use(s)

2-Component polyurethane adhesive

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Great Britain

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Diphenylmethane diisocyanate, isomers and homologs 9016-87-9 [ISOCYANATES, ALL (AS -NCO)]		0,07	Short Term Exposure Limit (STEL):		EH40 WEL
Diphenylmethane diisocyanate, isomers and homologs 9016-87-9 [ISOCYANATES, ALL (AS -NCO)]		0,02	Time Weighted Average (TWA):		EH40 WEL
4,4'-Methylenediphenyl diisocyanate 101-68-8 [ISOCYANATES, ALL (AS -NCO)]		0,07	Short Term Exposure Limit (STEL):		EH40 WEL
4,4'-Methylenediphenyl diisocyanate 101-68-8 [ISOCYANATES, ALL (AS -NCO)]		0,02	Time Weighted Average (TWA):		EH40 WEL
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1 [ISOCYANATES, ALL (AS -NCO)]		0,07	Short Term Exposure Limit (STEL):		EH40 WEL
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1 [ISOCYANATES, ALL (AS -NCO)]		0,02	Time Weighted Average (TWA):		EH40 WEL
Zeolites 68989-22-0 [ALUMINIUM OXIDES, INHALABLE DUST]		10	Time Weighted Average (TWA):		EH40 WEL
Zeolites 68989-22-0 [ALUMINIUM OXIDES, RESPIRABLE DUST]		4	Time Weighted Average (TWA):		EH40 WEL
2,2'-Methylenediphenyl diisocyanate 2536-05-2 [ISOCYANATES, ALL (AS -NCO)]		0,07	Short Term Exposure Limit (STEL):		EH40 WEL
2,2'-Methylenediphenyl diisocyanate 2536-05-2 [ISOCYANATES, ALL (AS -NCO)]		0,02	Time Weighted Average (TWA):		EH40 WEL

Occupational Exposure Limits

Valid for
Ireland

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Diphenylmethane diisocyanate, isomers and homologs 9016-87-9 [ISOCYANATES (ALL, AS -NCO)]		0,02	Time Weighted Average (TWA):		IR_OEL
Diphenylmethane diisocyanate, isomers and homologs 9016-87-9 [ISOCYANATES (ALL, AS -NCO)]		0,07	Short Term Exposure Limit (STEL):	15 minutes	IR_OEL
4,4'-Methylenediphenyl diisocyanate 101-68-8 [4,4'-METHYLENE-DIPHENYL DIISOCYANATE (AS -NCO)]	0,005		Time Weighted Average (TWA):		IR_OEL
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1 [ISOCYANATES (ALL, AS -NCO)]		0,02	Time Weighted Average (TWA):		IR_OEL
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1 [ISOCYANATES (ALL, AS -NCO)]		0,07	Short Term Exposure Limit (STEL):	15 minutes	IR_OEL

2,2'-Methylenediphenyl diisocyanate 2536-05-2 [ISOCYANATES (ALL, AS -NCO)]		0,02	Time Weighted Average (TWA):		IR_OEL
2,2'-Methylenediphenyl diisocyanate 2536-05-2 [ISOCYANATES (ALL, AS -NCO)]		0,07	Short Term Exposure Limit (STEL):	15 minutes	IR_OEL

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
4,4'- methylenediphenyl diisocyanate 101-68-8	aqua (freshwater)		1 mg/l				
4,4'- methylenediphenyl diisocyanate 101-68-8	aqua (marine water)		0,1 mg/l				
4,4'- methylenediphenyl diisocyanate 101-68-8	Soil				1 mg/kg		
4,4'- methylenediphenyl diisocyanate 101-68-8	sewage treatment plant (STP)		1 mg/l				
4,4'- methylenediphenyl diisocyanate 101-68-8	Air						no hazard identified
4,4'- methylenediphenyl diisocyanate 101-68-8	Predator						no potential for bioaccumulation
4,4'- methylenediphenyl diisocyanate 101-68-8	aqua (intermittent releases)		10 mg/l				
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	aqua (marine water)		0,1 mg/l				
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	sewage treatment plant (STP)		1 mg/l				
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	aqua (intermittent releases)		10 mg/l				
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	aqua (freshwater)		1 mg/l				
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	Soil				1 mg/kg		
2,2'-Methylenediphenyl diisocyanate 2536-05-2	aqua (freshwater)		1 mg/l				
2,2'-Methylenediphenyl diisocyanate 2536-05-2	aqua (marine water)		0,1 mg/l				
2,2'-Methylenediphenyl diisocyanate 2536-05-2	Soil				1 mg/kg		
2,2'-Methylenediphenyl diisocyanate 2536-05-2	sewage treatment plant (STP)		1 mg/l				
2,2'-Methylenediphenyl diisocyanate 2536-05-2	aqua (intermittent releases)		10 mg/l				

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
4,4'-methylenediphenyl diisocyanate 101-68-8	Workers	inhalation	Long term exposure - local effects		0,05 mg/m ³	no hazard identified
4,4'-methylenediphenyl diisocyanate 101-68-8	Workers	inhalation	Acute/short term exposure - local effects		0,1 mg/m ³	no hazard identified
4,4'-methylenediphenyl diisocyanate 101-68-8	General population	inhalation	Long term exposure - local effects		0,025 mg/m ³	no hazard identified
4,4'-methylenediphenyl diisocyanate 101-68-8	General population	inhalation	Acute/short term exposure - local effects		0,05 mg/m ³	no hazard identified
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	Workers	inhalation	Acute/short term exposure - local effects		0,1 mg/m ³	
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	Workers	inhalation	Long term exposure - local effects		0,05 mg/m ³	
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	General population	inhalation	Acute/short term exposure - local effects		0,05 mg/m ³	
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	General population	inhalation	Long term exposure - local effects		0,025 mg/m ³	
2,2'-Methylenediphenyl diisocyanate 2536-05-2	Workers	Inhalation	Acute/short term exposure - local effects		0,1 mg/m ³	
2,2'-Methylenediphenyl diisocyanate 2536-05-2	Workers	Inhalation	Long term exposure - local effects		0,05 mg/m ³	
2,2'-Methylenediphenyl diisocyanate 2536-05-2	General population	Inhalation	Acute/short term exposure - local effects		0,05 mg/m ³	
2,2'-Methylenediphenyl diisocyanate 2536-05-2	General population	Inhalation	Long term exposure - local effects		0,025 mg/m ³	

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Use only in well ventilated areas.

Draw off vapors directly at the point of generation or release.

Respiratory protection:

Suitable breathing mask when there is inadequate ventilation.

Filter: B - P3

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; \geq 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; \geq 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Goggles which can be tightly sealed.

Protective eye equipment should conform to EN166.

Skin protection:

Wear protective equipment.

Protective clothing that covers arms and legs.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

Use only personal protection that's CE-labelled according to Directive 89/686/EEC (Europe) or to Regulation No. 819 of 19 August 1994 (Norway).

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	paste pasty green
Odor	characteristic
Odour threshold	No data available / Not applicable
pH	Not applicable
Melting point	No data available / Not applicable
Solidification temperature	No data available / Not applicable
Initial boiling point	> 200 °C (> 392 °F)
Flash point	178 °C (352.4 °F)
Evaporation rate	No data available / Not applicable
Flammability	No data available / Not applicable
Explosive limits	No data available / Not applicable
Vapour pressure (50,0 °C (122 °F))	12,0000000 hPaNot available.
Relative vapour density:	No data available / Not applicable
Density (20 °C (68 °F))	1,21 - 1,26 g/cm3
Bulk density	No data available / Not applicable
Solubility	No data available / Not applicable
Solubility (qualitative) (20 °C (68 °F); Solvent: Water)	Not miscible or difficult to mix
Partition coefficient: n-octanol/water	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Decomposition temperature	No data available / Not applicable
Viscosity (Brookfield; 20 °C (68 °F); speed of rotation: 5 min-1; Spindle No: 7; Conc.: 100 % product)	400 - 550 Pa*s
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable

Oxidising properties

No data available / Not applicable

9.2. Other information

No data available / Not applicable

SECTION 10: Stability and reactivity**10.1. Reactivity**

Reaction with water, alcohols, amines.

Reacts with water: Pressure built up in closed vessel (CO₂).**10.2. Chemical stability**

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Humidity

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

At higher temperatures isocyanate may be released.

Carbon dioxide is generated under contact with moisture, leading to pressure in the cans. Danger of cans bursting!

SECTION 11: Toxicological information**General toxicological information:**

Persons suffering from allergic reactions to isocyanates should avoid contact with the product.

11.1. Information on toxicological effects**Acute oral toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	LD50	> 10.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
4,4'-methylenediphenyl diisocyanate 101-68-8	LD50	> 2.000 mg/kg	rat	other guideline:
o-(p- Isocyanatobenzyl)phenyl isocyanate 5873-54-1	LD50	> 2.000 mg/kg	rat	other guideline:
2,2'-Methylenediphenyl diisocyanate 2536-05-2	LD50	> 2.000 mg/kg	rat	EU Method B.1 (Acute Toxicity (Oral))

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	LD50	> 9.400 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
4,4'- methylenediphenyl diisocyanate 101-68-8	LD50	> 9.400 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	LD50	> 9.400 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
2,2'-Methylenediphenyl diisocyanate 2536-05-2	LD50	> 9.400 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)

Acute inhalative toxicity:

No substance data available.
No data available.

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
4,4'- methylenediphenyl diisocyanate 101-68-8	irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	sensitising	Skin sensitisation	guinea pig	OECD Guideline 406 (Skin Sensitisation)
4,4'-methylenediphenyl diisocyanate 101-68-8	sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	sensitising	Respiratory sensitisation	guinea pig	not specified
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
2,2'-Methylenediphenyl diisocyanate 2536-05-2	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
2,2'-Methylenediphenyl diisocyanate 2536-05-2	sensitising	Respiratory sensitisation	guinea pig	not specified

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		EU Method B.13/14 (Mutagenicity)
4,4'-methylenediphenyl diisocyanate 101-68-8	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		EU Method B.13/14 (Mutagenicity)
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
2,2'-Methylenediphenyl diisocyanate 2536-05-2	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
4,4'-methylenediphenyl diisocyanate 101-68-8	negative	inhalation		rat	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	negative	inhalation		rat	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
2,2'-Methylenediphenyl diisocyanate 2536-05-2	negative	inhalation		rat	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
4,4'- methylenediphenyl diisocyanate 101-68-8	carcinogenic	inhalation: aerosol	2 y 6 h/d	rat	male/female	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	carcinogenic	inhalation: aerosol	2 y 6 h/d, 5 d/w	rat	male/female	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
2,2'-Methylenediphenyl diisocyanate 2536-05-2	carcinogenic	inhalation: aerosol	2 y 6 h/d, 5 d/w	rat	male/female	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

Reproductive toxicity:

No data available.

STOT-single exposure:

No data available.

STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	NOAEL 0,0002 mg/l	inhalation: aerosol	2 y 6 h per d, 5 d per week	rat	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
4,4'- methylenediphenyl diisocyanate 101-68-8	NOAEL 0,0002 mg/l	inhalation: aerosol	main: 2 y; satellite:1 y 6 h/d; 5 d/w	rat	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	NOAEL 0,2 mg/m ³	inhalation: aerosol	2 y 6 h/d, 5 d/w	rat	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
2,2'-Methylenediphenyl diisocyanate 2536-05-2	NOAEL 0,2 mg/m ³	inhalation: aerosol	2 y 6 h/d, 5 d/w	rat	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

Aspiration hazard:

No data available.

SECTION 12: Ecological information

General ecological information:

Do not empty into drains, soil or bodies of water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	LC50	> 1.000 mg/l	96 h	Brachydanio rerio (new name: Danio rerio)	OECD Guideline 203 (Fish, Acute Toxicity Test)
4,4'-methylenediphenyl diisocyanate 101-68-8	LC50	> 1.000 mg/l	96 h	Danio rerio	OECD Guideline 203 (Fish, Acute Toxicity Test)
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	LC50	> 1.000 mg/l	96 h	Danio rerio	OECD Guideline 203 (Fish, Acute Toxicity Test)
2,2'-Methylenediphenyl diisocyanate 2536-05-2	LC50	> 1.000 mg/l	96 h	Danio rerio	OECD Guideline 203 (Fish, Acute Toxicity Test)

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	EC50	> 1.000 mg/l	24 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
4,4'-methylenediphenyl diisocyanate 101-68-8	EC50	129,7 mg/l	24 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	NOEC	10 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
4,4'-methylenediphenyl diisocyanate 101-68-8	NOEC	10 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	EC50	> 1.640 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
4,4'-methylenediphenyl diisocyanate 101-68-8	EC50	> 1.640 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
4,4'-methylenediphenyl diisocyanate 101-68-8	NOELR	1.640 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	EC50	> 100 mg/l	3 h	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
4,4'-methylenediphenyl diisocyanate 101-68-8	EC50	> 100 mg/l	3 h	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

12.2. Persistence and degradability

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	not inherently biodegradable	aerobic	0 %	28 d	OECD Guideline 302 C (Inherent Biodegradability: Modified MITI Test (II))
4,4'-methylenediphenyl diisocyanate 101-68-8	not readily biodegradable.	aerobic	0 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)

12.3. Bioaccumulative potential

Hazardous substances CAS-No.	Bioconcentration factor (BCF)	Exposure time	Temperature	Species	Method
Diphenylmethane diisocyanate, isomers and homologues 9016-87-9	200			Cyprinus carpio	OECD Guideline 305 (Bioconcentration: Flow-through Fish Test)
4,4'-methylenediphenyl diisocyanate 101-68-8	92 - 200	28 d		Cyprinus carpio	OECD Guideline 305 E (Bioaccumulation: Flow-through Fish Test)

12.4. Mobility in soil

Hazardous substances CAS-No.	LogPow	Temperature	Method
4,4'-methylenediphenyl diisocyanate 101-68-8	4,51	22 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	5,22		not specified

12.5. Results of PBT and vPvB assessment

Hazardous substances CAS-No.	PBT / vPvB
4,4'-methylenediphenyl diisocyanate 101-68-8	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
o-(p-Isocyanatobenzyl)phenyl isocyanate 5873-54-1	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
2,2'-Methylenediphenyl diisocyanate 2536-05-2	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

In consultation with the responsible local authority, must be subjected to special treatment.

Waste code

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

080409

SECTION 14: Transport information

14.1. UN number

ADR	Not dangerous goods
RID	Not dangerous goods
ADN	Not dangerous goods
IMDG	Not dangerous goods
IATA	Not dangerous goods

14.2. UN proper shipping name

ADR	Not dangerous goods
RID	Not dangerous goods
ADN	Not dangerous goods
IMDG	Not dangerous goods
IATA	Not dangerous goods

14.3. Transport hazard class(es)

ADR	Not dangerous goods
RID	Not dangerous goods
ADN	Not dangerous goods
IMDG	Not dangerous goods
IATA	Not dangerous goods

14.4. Packing group

ADR	Not dangerous goods
RID	Not dangerous goods
ADN	Not dangerous goods
IMDG	Not dangerous goods
IATA	Not dangerous goods

14.5. Environmental hazards

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

14.6. Special precautions for user

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC content 0 %
(VOCV 814.018 VOC regulation
CH)

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H351 Suspected of causing cancer.
- H373 May cause damage to organs through prolonged or repeated exposure.

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.