

Metal Degreasing Solvent

Product Code: MDS

PRODUCT DESCRIPTION

A special solvent for the most critical electro-mechanical applications. **MDS** is highly recommended for cold cleaning applications in conjunction with all types of electro-mechanical equipment. Contains Dichloromethane. Use in a well ventilated area.

PRODUCT USE

For safe, rapid cleansing of electric motors and all types of electro-mechanical equipment where the use of water-based chemicals or flammable solvents is inadvisable but the features below are required.

FEATURES

- * Powerful, penetrating action, works faster and more thoroughly than conventional solvents. Lower toxicity than other conventional halogenated solvents such as carbon tetrachloride.
- * Non-flammable, eliminates the risk of fire caused by flammable solvents such as Benzene, Xylene, Isopropyl Alcohol, White Spirit and Paraffin.
- * Non-conductive, therefore safe to use on electrical equipment.
- * Fast drying, leaving no residue and, therefore, suitable for use on very sophisticated equipment.

TYPICAL PROPERTIES

Form:	Clear, Colourless Liquid
Boiling Point:	40°C
Vapour Pressure @ 20°C:	355 mm/Hg
Specific Gravity @ 20°C:	1.32
Decomposition Temperature:	>200°C

Note 1: MDS is harmless to metals under normal conditions. However, it affects certain thermoplastics and fabrics and

TECHNICAL DATA SHEET



Copyright Electrolube 2003

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification. Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.



Metal Degreasing Solvent – Page 2

a small area must be tested before use.

Note 2: In common with other halogenated solvents, MDS should not be used for prolonged periods (e.g. overnight) in contact with aluminium or in circumstances under which the protective oxide film is removed.

PACKAGING

1 Litre Bulk

ORDER CODE

MDS01L

TECHNICAL DATA SHEET



Copyright Electrolube 2003

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification. Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.

