

Sealed Heat Shrink Butt Splice

multicomp PRO




Features:

- Heat shrinkable sealed splices providing a tough and long lasting environmental seal against immersion in solvents, oils, fluids and salt water.
- The wire insulation should be stripped to 8mm and then crimped into the ends of the butt splice.
- Hot air should then be applied to the sleeve until the tubing has shrunk to the cable size and the adhesive flows from the end of the splice, giving a fully sealed joint and additional strain relief.

Specifications:

Max. Electric Current	A.M.G.	26	24	22	20	18	16	14	12	10	8
	AMP.	5.5	7	9	12	17	18	30	35	50	70
Max. Electrical Rating	: 600 Volts										
Shrink Temperature	: 150°C										
Operating Temperature	: -40°C to +105°C										
Insulation Material	: High Density PE.										
Terminal Material	: Copper Tubular										
Terminal Surface Treatment	: Tin Plated										



Part Number Table

Description	Wire Range A.W.G. mm ²	Dimension inch(mm)		Insulated Colour	Part Number
		d2	L		
Sealed Heat Shrink Butt Splice	22-16 A.W.G. 0.5-1.5mm ²	0.067 (1.7)	1.417 (36)	Red	DHSB 1
	12-10 A.W.G. 4-6mm ²	0.134 (3.4)	1.614 (41)	Yellow	DHSB 5

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
Element14.com/multicomp-pro

multicomp PRO