

N-Channel Lateral DMOS FETs

SD211DE
SD213DE
SD215DE

SST211
SST213
SST215

Product Summary

Part Number	V _{(BR)DS} Min (V)	V _{GS(th)} Max (V)	r _{DS(on)} Max (Ω)	C _{rss} Max (pF)	t _{ON} Max (ns)
SD211DE	30	1.5	45 @ V _{GS} = 10 V	0.5	2
SD213DE	10	1.5	45 @ V _{GS} = 10 V	0.5	2
SD215DE	20	1.5	45 @ V _{GS} = 10 V	0.5	2
SST211	30	1.5	50 @ V _{GS} = 10 V	0.5	2
SST213	10	1.5	50 @ V _{GS} = 10 V	0.5	2
SST215	20	1.5	50 @ V _{GS} = 10 V	0.5	2

Features

- Ultra-High Speed Switching—t_{ON}: 1 ns
- Ultra-Low Reverse Capacitance: 0.2 pF
- Low Guaranteed r_{DS} @ 5 V
- Low Turn-On Threshold Voltage
- N-Channel Enhancement Mode

Benefits

- High Speed System Performance
- Low Insertion Loss at High Frequencies
- Low Transfer Signal Loss
- Simple Driver Requirement
- Single Supply Operation

Applications



- Fast Analog Switch
- Fast Sample-and-Holds
- Pixel-Rate Switching
- DAC Deglitchers
- High-Speed Driver

Description

The SD211DE/SST211 series consists of enhancement-mode MOSFETs designed for high speed low-glitch switching in audio, video, and high-frequency applications. The SD211 may be used for ±5-V analog switching or as a high speed driver of the SD214. The SD214 is normally used for ±10-V analog switching. These MOSFETs utilize lateral construction to achieve low capacitance and ultra-fast switching speeds. An

integrated Zener diode provides ESD protection. These devices feature a poly-silicon gate for manufacturing reliability.

For similar products see: quad array—SD5000/5400 series and non-Zener protection—SD210DE/214DE.



Updates to this data sheet may be obtained via facsimile by calling Siliconix FaxBack, 1-408-970-5600. Please request FaxBack document #70295. Applications information may also be obtained via FaxBack, request document #70607.

Absolute Maximum Ratings ($T_A = 25^\circ\text{C}$ Unless Otherwise Noted)

Gate-Drain, Gate-Source Voltage (SD211DE/SST211)	-30/25 V	Source-Substrate Voltage (SD211DE/SST211)	15 V
(SD213DE/SST213)	-15/25 V	(SD213DE/SST213)	15 V
(SD215DE/SST215)	-25/30 V	(SD215DE/SST215)	25 V
Gate-Substrate Voltage ^a	(SD211DE/SST211) -0.3/25 V	Drain Current	50 mA
(SD213DE/SST213) -0.3/25 V	Lead Temperature (1/16" from case for 10 seconds)	300°C
(SD215DE/SST215) -0.3/30 V	Storage Temperature	-65 to 150°C
Drain-Source Voltage	(SD211DE/SST211) 30 V	Operating Junction Temperature	-55 to 125°C
(SD213DE/SST213) 10 V	Power Dissipation ^a	300 mW
(SD215DE/SST215) 20 V		
Source-Drain Voltage	(SD211DE/SST211) 10 V		
(SD213DE/SST213) 10 V		
(SD215DE/SST215) 20 V		
Drain-Substrate Voltage	(SD211DE/SST211) 30 V		
(SD213DE/SST213) 15 V		
(SD215DE/SST215) 25 V		

Notes:

a. Derate 3 mW/°C above 25°C

Specifications^a

Parameter	Symbol ^b	Test Conditions ^b	Typ ^c	Limits						Unit	
				211 Series		213 Series		215 Series			
				Min	Max	Min	Max	Min	Max		
Static											
Drain-Source Breakdown Voltage	V _{(BR)DS}	V _{GS} = V _{BS} = 0 V, I _D = 10 μA	35	30						V	
		V _{GS} = V _{BS} = -5 V, I _D = 10 nA	30	10		10		20			
Source-Drain Breakdown Voltage	V _{(BR)SD}	V _{GD} = V _{BD} = -5 V, I _S = 10 nA	22	10		10		20			
Drain-Substrate Breakdown Voltage	V _{(BR)DBO}	V _{GB} = 0 V, I _D = 10 nA, Source Open	35	15		15		25			
Source-Substrate Breakdown Voltage	V _{(BR)SBO}	V _{GB} = 0 V, I _S = 10 μA, Drain Open	35	15		15		25			
Drain-Source Leakage	I _{DS(off)}	V _{GS} = V _{BS} = -5 V	V _{DS} = 10 V	0.4		10		10		nA	
			V _{DS} = 20 V	0.9					10		
Source-Drain Leakage	I _{SD(off)}	V _{GD} = V _{BD} = -5 V	V _{SD} = 10 V	0.5		10		10		nA	
			V _{SD} = 20 V	1					10		
Gate Leakage	I _{GBS}	V _{DB} = V _{SB} = 0 V, V _{GB} = 30V	0.01		100		100		100		
Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = 1 μA V _{SB} = 0 V	0.8	0.5	1.5	0.1	1.5	0.1	1.5	V	
Drain-Source On-Resistance	r _{DS(on)}	V _{SB} = 0 V I _D = 1 mA	V _{GS} = 5 V (SD Series)	58		70		70		Ω	
			V _{GS} = 5 V (SST Series)	60		75		75			
			V _{GS} = 10 V (SD Series)	38		45		45			
			V _{GS} = 10 V (SST Series)	40		50		50			
			V _{GS} = 15 V	30							
			V _{GS} = 20 V	26							
			V _{GS} = 25 V	24							

Specifications^a







Parameter	Symbol ^b	Test Conditions ^b	Typ ^c	Limits						Unit	
				211 Series		213 Series		215 Series			
				Min	Max	Min	Max	Min	Max		
Dynamic											
Forward Transconductance	g _{fs}	V _{DS} = 10 V V _{SB} = 0 V I _D = 20 mA, f = 1 kHz	SD Series	11	10		10		10		mS
	g _{os}		SST Series	10.5	9		9		9		
	All		All	0.9							
Gate Node Capacitance	C _(GS+GD+GB)	V _{DS} = 10 V f = 1 MHz V _{GS} = V _{BS} = -15 V	SD Series	2.5		3.5		3.5		3.5	pF
Drain Node Capacitance	C _(GD+DB)			1.1		1.5		1.5		1.5	
Source Node Capacitance	C _(GS+SB)			3.7		5.5		5.5		5.5	
Reverse Transfer Capacitance	C _{rss}		SST Series	4.2							
			SD Series	0.2		0.5		0.5		0.5	
Switching											
Turn-On Time	t _{d(on)}	SD Series Only V _{SB} = 0 V, V _{IN} 0 to 5 V, R _G = 25 Ω V _{DD} = 5 V, R _L = 680 Ω	0.5		1		1		1		ns
	t _r		0.6		1		1		1		
Turn-Off Time	t _{d(off)}		2								
	t _f		6								

Notes:







- a. T_A = 25°C unless otherwise noted.
- b. B is the body (substrate), and (BR) is breakdown.
- c. Typical values are for DESIGN AID ONLY, not guaranteed nor subject to production testing.

DMCBA





Typical Characteristics



Typical Characteristics (Cont'd)



Typical Characteristics



Switching Time Test Circuit

