


## Dual N-Channel 60-V, 175°C Rated MOSFET

### Product Summary

V <sub>DS</sub> (V)	r <sub>DS(on)</sub> (Ω)	I <sub>D</sub> (A)
60	0.055 @ V <sub>GS</sub> = 10 V	±4.5
	0.075 @ V <sub>GS</sub> = 4.5 V	±3.9

**175°C Rated**  
Maximum Junction Temperature  
**TrenchFET™**  
Power MOSFETs



N-Channel MOSFET

### Absolute Maximum Ratings (T<sub>A</sub> = 25°C Unless Otherwise Noted)

Parameter	Symbol	Limit	Unit
Drain-Source Voltage	V <sub>DS</sub>	60	V
Gate-Source Voltage	V <sub>GS</sub>	±20	
Continuous Drain Current (T <sub>J</sub> = 175°C) <sup>a</sup>	I <sub>D</sub>	±4.5	A
		±3.8	
Pulsed Drain Current	I <sub>DM</sub>	±30	
Continuous Source Current (Diode Conduction) <sup>a</sup>	I <sub>S</sub>	2	
Maximum Power Dissipation <sup>a</sup>	P <sub>D</sub>	2.4	W
		1.7	
Operating Junction and Storage Temperature Range	T <sub>J</sub> , T <sub>stg</sub>	-55 to 175	°C

### Thermal Resistance Ratings

Parameter	Symbol	Limit	Unit
Maximum Junction-to-Ambient <sup>a</sup>	R <sub>thJA</sub>	62.5	°C/W

Notes

a. Surface Mounted on FR4 Board, t ≤ 10 sec.

Updates to this data sheet may be obtained via facsimile by calling Siliconix FaxBack, 1-408-970-5600. Please request FaxBack document #70157.







**Specifications ( $T_J = 25^\circ\text{C}$  Unless Otherwise Noted)**

Parameter	Symbol	Test Condition	Min	Typ <sup>a</sup>	Max	Unit
<b>Static</b>						
Gate Threshold Voltage	$V_{GS(\text{th})}$	$V_{DS} = V_{GS}, I_D = 250 \mu\text{A}$	1			V
Gate-Body Leakage	$I_{GSS}$	$V_{DS} = 0 \text{ V}, V_{GS} = \pm 20 \text{ V}$			$\pm 100$	nA
Zero Gate Voltage Drain Current	$I_{DSS}$	$V_{DS} = 60 \text{ V}, V_{GS} = 0 \text{ V}$		2		$\mu\text{A}$
		$V_{DS} = 60 \text{ V}, V_{GS} = 0 \text{ V}, T_J = 55^\circ\text{C}$		25		
On-State Drain Current <sup>b</sup>	$I_{D(\text{on})}$	$V_{DS} = 5 \text{ V}, V_{GS} = 10 \text{ V}$	20			A
Drain-Source On-State Resistance <sup>b</sup>	$r_{DS(\text{on})}$	$V_{GS} = 10 \text{ V}, I_D = 4.5 \text{ A}$		0.045	0.055	$\Omega$
		$V_{GS} = 4.5 \text{ V}, I_D = 3.9 \text{ A}$		0.055	0.075	
Forward Transconductance <sup>b</sup>	$g_{fs}$	$V_{DS} = 15 \text{ V}, I_D = 4.5 \text{ A}$		13		S
Diode Forward Voltage <sup>b</sup>	$V_{SD}$	$I_S = 2 \text{ A}, V_{GS} = 0 \text{ V}$		0.9	1.2	V
<b>Dynamic<sup>a</sup></b>						
Total Gate Charge	$Q_g$	$V_{DS} = 30 \text{ V}, V_{GS} = 10 \text{ V}, I_D = 4.5 \text{ A}$		19	30	nC
Gate-Source Charge	$Q_{gs}$			4		
Gate-Drain Charge	$Q_{gd}$			3		
Turn-On Delay Time	$t_{d(\text{on})}$	$V_{DD} = 30 \text{ V}, R_L = 30 \Omega$ $I_D \approx 1 \text{ A}, V_{GEN} = 10 \text{ V}, R_G = 6 \Omega$		13	20	ns
Rise Time	$t_r$			11	20	
Turn-Off Delay Time	$t_{d(\text{off})}$			36	60	
Fall Time	$t_f$			11	20	
Source-Drain Reverse Recovery Time	$t_{rr}$	$I_F = 2 \text{ A}, di/dt = 100 \text{ A}/\mu\text{s}$		35	60	

## Notes

- a. For design aid only; not subject to production testing.
- b. Pulse test; pulse width  $\leq 300 \mu\text{s}$ , duty cycle  $\leq 2\%$ .

## Typical Characteristics (25°C Unless Otherwise Noted)



## Typical Characteristics (25°C Unless Otherwise Noted)

