

PRODUCT DATA SHEET

EVERBUILD® 702 Water Resistant Tile Adhesive

PREMIUM GRADE WATER RESISTANT TILE ADHESIVE

PRODUCT DESCRIPTION

EVERBUILD® 702 Water Resistant Tile Adhesive is a premium grade adhesive that can be used in areas subject to prolonged/permanent wet conditions and in areas of high humidity and condensation.

USES

- Kitchen/Bathroom walls.
- Shower areas when used in conjunction with Everbuild Powdered Wall Tile Grout.
- Communal and power showers
- Work tops subject to water contact.

CHARACTERISTICS / ADVANTAGES

- Excellent water resistance.
- Extremely high bond strength - over double the B.S. minimum requirement in wet shear (7 days drying, 7 days water immersion followed by shearing whilst wet).
- Ready mixed formula - no mixing, no mess. Apply straight from the tub.
- Easier to apply than most competitive adhesives.
- Excellent non slip characteristics - no movement on a 300 x 200 standard large format wall tile.
- Extended open time.

Shear Adhesion (typical)	12kN (wet shear)
Bed Thickness	3-6mm

APPROVALS / STANDARDS

Tested to EN12004 type D2T.

PRODUCT INFORMATION

Packaging	1.5kg, 3.75kg, 7.5kg & 16kg tubs
Appearance / Colour	Thick buff paste (dries off-white)
Shelf Life	12 months when stored according to manufacturer's instructions.
Storage Conditions	Store at moderate (5 - 30°C) temperatures. PROTECT FROM FROST
Density	1.7g/cm ³ (approx) @ 20°C
Thermal Resistance	Service Temp -30°C to 100°C once cured.

APPLICATION INFORMATION

Consumption	0.6m ² /kg for wet areas and 0.9m ² /kg for dry areas.
Ambient Air Temperature	Application Temp 5°C to 35°C
Open Time	30 - 40 mins @20°C

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY / PRE-TREATMENT

PLASTER

New plaster must be a minimum of 4 weeks old before tiling. Tile onto finishing coat only. Prime with EVERBUILD PVA diluted 1:3 with water.

PLASTERBOARD/PLYWOOD/CHIPBOARD

Must be braced with seasoned timber at 300mm vertically and horizontally. Use moisture resistant grades. All surfaces and edges must be sealed with EVERBUILD SBR diluted 1:4 with water.

SAND/CEMENT RENDER

Allow at least four weeks drying before tiling. Use a mix design of 3 to 4 parts sand to 1 part cement. Prime with EVERBUILD PVA.

BRICKWORK/BLOCKWORK/CONCRETE BLOCK

Allow at least 4 weeks drying time before rendering or plastering. Do not fix directly to blockwork.

EXISTING GLAZED TILES/FORMICA

Roughen surfaces with abrasive sander and prime with EVERBUILD PVA diluted 1:1 with water. Apply adhesive whilst still tacky. Allow at least 5 days before grouting.

PAINTED SURFACES

Not recommended for direct application to emulsion or limewash paints. Remove loose material and prime with EVERBUILD PVA Mix diluted 1:3 with water. For gloss paints, degrease and score with knife to provide key for adhesive. Allow at least five days drying before grouting.

APPLICATION

Surfaces to be tiled must be clean, dry and sound. Apply adhesive to wall at a depth of 3-6mm (no less than 3mm, no greater than 6mm) combing out an area of no greater than 1m² at a time. In dry situations, use a suitable notched trowel across the surface of the adhesive before placing the tiles into position and securing with a slight twist action to remove air voids. In areas subject to wet conditions, do not use a notched trowel. Bed the tiles directly into the surface of the adhesive and again, secure with a slight twist action. In both situations, it is good practice to periodically remove a tile and check that at least 75% of the tile is covered in adhesive. If this is not the case, apply fresh adhesive and reposition.

CLEANING OF TOOLS

All surplus adhesive must be removed whilst adhesive is still wet using a dampened cloth or sponge, particularly along grout lines.

LIMITATIONS

- Unsuitable for floors.
- Do not use for swimming pools. Use EVERBUILD 705 RAPID SET TILE MORTAR
- Do not use externally. Use EVERBUILD 705 RAPID SET TILE MORTAR

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

ECOLOGY, HEALTH AND SAFETY

Consult MSDS for full list of hazards.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

EVERBUILD BUILDING PRODUCTS LTD

Site 41, Knowsthorpe Way
Cross Green Industrial Estate
Leeds, LS9 0SW
Tel: 0113 240 3456
Web: www.everbuild.co.uk
Twitter: @everbuild

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited

SIKA IRELAND LIMITED

Ballymun Industrial Estate
Ballymun
Dublin 11, Ireland
Tel: +353 1 862 0709
Web: www.sika.ie
Twitter: @SikaIreland

EVERBUILD702WaterResistantTileAdhesive-en-GBEVER-(03-2018)-1-1.pdf

Product Data Sheet
EVERBUILD® 702 Water Resistant Tile Adhesive
March 2018, Version 01.01
020404020030000022