

NOTES: (UNLESS OTHERWISE SPECIFIED)

1. MATERIAL:

1.1 CONTACT BODY: COPPER ALLOY, SILVER PLATED.

2. SPECIFICATIONS:

2.1 CURRENT RATING: 32A(MAX).
2.2 TERMINATION TYPE: SCREWING.


3. SUITABLE CONTACT: SC000612&SC000624.


4. Rohs Compliant.

5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.

REVISIONS												
REV	ECO	DESCRIPTION	DATE	BY	APPR							
A1	-	RELEASED DRAWING	DEC-12-2019	BLINK	TOMMY							
A2	-	UPDATE DRAWING	MAR-18-2020	BLINK	TOMMY							

2.4MM, CONTACT, PIN





QUANTITY	PART NUMBER			DESCRIPTION			ITEM	
		MA	T	ERIA	ALS	S LI	ST	
UNLESS OTHERWISE SPECIFIED  1) All dimensions are in metric(mm). 2) Tolerances are as follows: 1 PL DEC +0.30. I Fractions +1/64		SIGNATURES		DATE	Amphenol			
		DRAWN: BLIN	K	MAR-18-2020	Amphenoi			
2 PL DEC ±0.15 3 PL DEC ±0.08	Fractions ±1/64 Angles ±1°	CHECKED: ORIO	N	MAR-20-2020	Sine Systems - www.amphenol-sine.co		e.com	
3) Note reference = XX  AP  MATERIAL SPECIFICATIONS:  CL		ENGINEER:			44724 Morley Drive Clinton Township, MI 48036			
		APPROVAL: TOM	ΛY	MAR-23-2020	Canada romany, mi rocco			
		CUSTOMER:			2.4MM, CONTACT, PIN			
		THIS DRAWING IS SUPPLIED FOR INFORMATION ONLY, DESIGN FEATURES.		WITH 4-40 UNC THREAD HOLE				
PROCESS SPECIFICATIONS:		SPECIFICATIONS AND PERFORMANCE DATA SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION. NO RIGHTS OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SUBJECT TO NORMAL		B	C-	SC000565	A2	
NEXT ASS'Y:				SCALE: N	ONE	QUEET 1 or	- 1	