

# Heat Shrink Tubing

## 16-Pc. Black Assortment

**multicomp** PRO

**RoHS  
Compliant**




### Description

This black polyethylene heat shrinkable tubing provides insulation protection for wire, cable and wire terminals. It has high temperature shrinkage, soft flame retardant, insulation corrosion functions. It is widely used in the insulation protection for all kinds of wire, welding point and inductance and the rust and corrosion for metal pipes.

### Specifications

Material	: Polyethylene
Working Temperature	: -55°C to +135°C
Longitudinal Shrinkage	: 5%
Shrink Temperature	: Starts at 70°C and shrinks totally at 120°C
Shrinking Ratio	: 2:1
Flammability	: VW-1
Colour	: Black
Tool	: Heat Gun

### Diagram



As Supplied		After Recovery		Cut Length (L)	No. of Pcs. (Total Pcs.)	
I.D. (D)	Wall Thickness (H)	I.D. (d)	Wall Thickness (h)			
6.5 ±0.2	0.3 ±0.05	≤3	0.56 ±0.1	152.4	5	16
13.5 ±0.4	0.35 ±0.1	≤7.5	0.7 ±0.1		5	
19 ±0.5	0.35 ±0.1	≤9	0.7 ±0.1		6	

Dimensions : Millimetres

### Part Number Table

Description	Part Number
Heat Shrink Tubing Assortment, 16 Pieces, Black	MC001766

**Important Notice** : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro  
Farnell.com/multicomp-pro  
Element14.com/multicomp-pro

**multicomp** PRO