

Lightning Surge Protector N-U.FL 200mm

multicomp PRO



**RoHS
Compliant**



Electrical Performance:

Impedance	: 50Ω
Frequency	: DC ~ 6 Ghz
Insulator Resistance	: 5000MΩ min.
Working Voltage	: 250Vrms Max.
Impulse Discharge Voltage	: 5kV min.
Operation and Storage Temperature	: -40°C to +90°C

Diagram



Sl.	Description	Qty.
1.	U.FL-LP-088 Halogen Free Shell for OD 1.37mm Cable	1
2.	U.FL-LP-088 Contact for OD 1.37mm Cable	
3.	OD 1.37mm Cable (Colour: Black)	
4.	Heat Shrink Tube F32 OD = 3mm, Colour : Black, L=20mm	
5.	N surge Jumper Connector	
6.	SMD Series Surge Arresters	
7.	N Surge Jumper Inner Ferrule & PTFE Spacer for OD 1.37mm Cable type	

Frequency	Vswr	Insertion Loss
2.4~2.5 GHz	1.4 Max. : 1	-1.2dB Max
5.15~5.875 GHz	1.65 Max.: 1	-1.6dB Max.

Dimensions : Millimetres

Part Number Table

Description	Part Number
Lightning Surge Protector N-U.FL 200mm	MC001782

Note:

Mounting Panel Thickness 3.5mm Max.

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
Element14.com/multicomp-pro

multicomp PRO