



CRC QUICKLEEN

Ref. : 10136

1. GENERAL DESCRIPTION

Quick dry non-chlorinated cleaner.

A fast drying, powerful degreasing solvent blend free of 1,1,1,-trichloroethane or other chlorinated solvents.

Quickleen penetrates and cuts through dirt, grime and contaminants to improve critical connections and enhance overall performance. Designed for applications where flammable solvents can be used.

2. FEATURES

- Quickly dissolves grease, oil, lubricants, tar and adhesives.
- Efficient wash-away of contaminants.
- Fast evaporation to minimise downtime.
- Ensures rapid turnaround.
- Leaves no residue.
- Stable, non-staining and non-corrosive to metals.
- Safe on most plastics, coatings and rubbers (test prior to use).
- Aerosol is equipped with a 360° (upside-down) spray valve and extension tube for added convenience.
- Aerosol is pressurised with non-flammable CO₂ propellant, giving an active product content of over 97%.

3. APPLICATIONS

Cleans and degreases all metal parts, machines and tools:

- | | | |
|-------------------|-----------------------|-------------------------------|
| • Gear boxes | • Motors | • Material handling equipment |
| • Chains & cables | • Engines | • Parts & tools |
| • Dies & moulds | • Pneumatic tools | |
| • Compressors | • Fork lifts | |
| • Pumps | • Brakes and clutches | |

4. DIRECTIONS

- Spray liberally and allow excess to run off. Air dry or dry with absorbent cloth. Repeat if necessary.
- Use extension tube for hard-to-reach areas.
- After application, re-lubricate moving parts with CRC 5-56.
- Check plastics and rubber compatibility before use. Do not use on sensitive electronic equipment such as tape decks, VCR's, computers, etc. Use one of CRC's precision cleaners for these applications.
- Use with adequate ventilation. Do not use on energised equipment. Allow to dry thoroughly and vent before reactivating system.
- A safety data sheet (MSDS) according EU directive 93/112 is available for all CRC products.



Manufactured by :
CRC Industries Europe NV
Touwslagerstraat 1 – 9240 Zele – Belgium
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34
www.crcind.com





CRC QUICKLEEN

Ref. : 10136

5. TYPICAL PRODUCT DATA (without propellant)

Appearance	: colourless liquid, typical odour
Specific gravity @ 20°C	: 0,72
Boiling range	: 55-120 °C
Vapour density (vs air = 1)	: 3
Freezing point	: < -30°C
Evaporation rate (vs ether = 1)	: 2,8
Flash point (closed cup)	: < 0°C
Dynamic viscosity @ 20°C	: 0,5 mPa.s
Surface tension @ 20°C (est.)	: 21 mN/m
Plastics compatibility	: to be checked (*)
Non-volatiles	: none

6. PACKAGING

aerosol :	12 x 500 ml
bulk :	4 x 5 l
	20 l
	60 l

* Sensitive plastics (e.g. polystyrenes and polycarbonates,) need to be checked, particularly when thermal or mechanical stress is involved.

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

This Technical Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com. We recommend you to register on this website for this product so you will be able to receive any future updated version automatically.

Version : 10136 03 0900 02
Date : 23 september 2003



Manufactured by :
CRC Industries Europe NV
Touwslagerstraat 1 – 9240 Zele – Belgium
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34
www.crcind.com

