

Triple Power Supply HM7042-5



2x 0-32V/0-2A 1x 0-5.5V/0-5A

Separate voltage and current displays for each output:
4 digits at Channel I+III; 3 digits at Channel II

Display resolution:
10 mV/1 mA at Channel I+III; 10 mV/10 mA at Channel II


Adjustable current limiting and electronic fuse for each output

Pushbutton for activating/deactivating all outputs

Low residual ripple, high output power, very good regulation

Temperature-controlled fan

HZ42 19" Rackmount kit 2RU



Silicone test cable HZ10



Triple Power Supply HM7042-5

Valid at 23 °C after a 30 minute warm-up period

Outputs

2 x 0 – 32V and 0..5.5V ON/OFF pushbutton control, SMPS followed by a linear regulator, floating outputs for parallel/serial operation, current limit and electronic fuse.

Channel I + III (32 V)

Range: 2 x 0 – 32V, continuously adjustable
2 knobs (coarse/fine)
Ripple: $\leq 100 \mu\text{V}_{\text{rms}}$ (3 Hz – 300 kHz)
Current: max. 2 A

Current limit/electronic fuse: 0 – 2A, continuously adjustable (knob)

Recovery time (10 % - 90 % load variation)

80 μs within ± 1 mV of nominal value
30 μs within ± 10 mV of nominal value
00 μs within ± 100 mV of nominal value

Max. transient deviation: typ. 75 mV

Recovery time (50 % basic load, 10 % load variation)

30 μs within ± 1 mV of nominal value
05 μs within ± 10 mV of nominal value
00 μs within ± 100 mV of nominal value

Max. transient deviation: typ. 17 mV

Display

7-segment LED: 32.00V (4 digit) / 2.000A (4 digit)

Resolution: 0.01 V / 1 mA

Display accuracy: ± 3 digit voltage / ± 4 digit current

LED: indicates current limit

Channel II (5.5 V)

Range: 0 – 5.5V, continuously adjustable (knobs)

Ripple: $\leq 100 \mu\text{V}_{\text{rms}}$ (3 Hz – 300 kHz)

Current: max. 5 A

Current limit / electronic fuse: 0 – 5A, continuously adjustable (knob)

Recovery time (10 % - 90 % load variation):

80 μs within ± 1 mV of nominal value
10 μs within ± 100 mV of nominal value

Max. transient deviation: typ. 170 mV

Recovery time (50 % basic load, 10 % load variation):

30 μs within ± 1 mV of nominal value

15 μs within ± 10 mV of nominal value

00 μs within ± 100 mV of nominal value

Max. transient deviation: typ. 60 mV

Display

7-segment LED: 5.50V (3 digit) / 5.00A (3 digit)

Resolution: 0.01 V/10 mA

Display accuracy: ± 3 digit voltage / ± 1 digit current

LED: indicates current limit

Maximum ratings

Max. voltage applicable to output terminals (ON/OFF):

CH I + CH III: 33V

CH II: 6V

Reverse voltage: max. 0.4 V

Reverse current: max. 5 A

Voltage to earth: max. 150V

Miscellaneous

Safety class: Safety class I (EN61010-1)

Mains supply: 115V/230V $\pm 10\%$; 50/60 Hz

Mains Fuse: 115V: 2 x 5 A slow blow 5 x 20 mm

230V: 2 x 2.5A slow blow 5 x 20 mm

Power consumption: max. 330 VA/250 W

Operating temperature: 0° to +40 °C

Storage temperature: -20 °C to +70 °C

Max. relative humidity: < 80% (without condensation)

Dimensions (W x H x D): 285 x 75 x 389 mm

Weight: approx. 7.4 kg

Accessories supplied: Operator's Manual and power cable

Optional accessories:

HZ10S/R Silicone test lead

HZ42 19" Rackmount Kit 2RU

www.hameg.com