Toggle Switch





Electrical

Max. Contact Rating : Silver : 5A at 120V AC or 28V DC, 2A at 250V AC

Max. Contact Resistance : $10M\Omega$

Min. Insulation Resistance : $1,000M\Omega$ at 500V DC

Dielectric Strength : 1,000V rms

Mechanical

Life : 40,000 cycles

Environmental

Operating Temperature : -30°C to +85°C

Material


Case : DAP

Housing : Stainless Steel


Actuator : Brass, Chrome Plated
Bushing : Brass, Nickel Plated
Support : Brass, Tin Plated
Contact / Terminals : Copper Alloy, Silver

Diagram


Actuator Option




Termination Option




Standard Nuts




Optional Nuts




Lock Washer



Locking Ring



Panel Mounting



Switching Position		
ON	NONE	ON

Dimensions: Inches (Millimetres)

Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro



Toggle Switch



Part Number Table

Description	Part Number
Toggle Switch, Non Illuminated, SPDT, (On)-None-(On), Panel, 5A	SPC21274

Important Notice: This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro



Page <2> 08/02/21 V1.0