# BNC Straight Bulkhead Jack, Crimp



RoHS

**Compliant** 

## **Specifications**

#### **Electrical**

 $\begin{array}{lll} \mbox{Frequency Range} & : DC - 1 \mbox{GHz} \\ \mbox{Nominal Impedance} & : 75 \Omega \\ \mbox{Voltage Rating} & : 500 \mbox{V Max}. \end{array}$ 

Material

Chassis : Brass, 100µ" Nickel Plated
Crimp Ferrule : Brass, Nickel Plated
Center Contact : Brass, Gold Plated

Insulation : PTFE

Body : Brass, 100µ" Nickel Plated
Washer : Steel, Nickel Plated
Nut : Brass, Nickel Plated

Gasket : Silicone

Mechanical

Cable Type : RG-179U or Equivalent


Cable Attachment : Outer: Crimp Inner: Solder


Crimp Size Required : Ferrule: 3.5(0.138) Hex Crimp Tool / 4.6(0.181) Hex Crimp Tool


**Environmental** 

Operating Temperature Range : -65°C to +165°C


# Diagram











### **Part Number Table**

Description	Part Number
BNC Straight Bulkhead Jack, Crimp, 75Ω, RG-179U	13-11-4 TGN RG179

Dimensions: Millimetres (Inches)

Important Notice: This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro



Page <1> 02/02/21 V1.0