## **50** $\Omega$ **BNC Coaxial** Connector


## multicomp PRO



## Specifications:

Impedance	: 50Ω
Frequency Range	: 0-4 GHz
Voltage Rating	: 500 V rms
Dielectric Withstanding Voltage	: 1,500

For RG-58, 58A, 58C, 141, 141A Belden 8240, 8259, 8262, 9201, 9203, 9310, 9311 & Comm/Scope 0268



QTY

1

1

1

1

1

1

1

1

1

Material

Brass

Brass

PTFE

Rubber

Brass

SK5

Brass

Brass

Brass

Description

Shell

Body

Insulator

Gasket

Retaining

Ring

Spring

Washer

Pin

Ferrule

Item

No.

1

2

3

4

5

6

7

8

9

Finish

Nickel, 100µ"

Nickel, 100µ"

Red


Nickel, 100µ"


Nickel, 100µ"

Nickel, 100µ"

Nickel, 100µ"


Nickel, 100µ"





RECOMMENDED CRIMP DIE .068

RECOMMENDED CRIMP DIE .213



RECOMMENDED STRIPPING DIMENSIONS

Dimensions : Inches (Millimeters)

## Part Number Table

Description	Part Number
BNC Plug, Crimp	SPC11224

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro

