

PRO-SIGNAL



Headphone Amplifier PSG03921

Please read these instructions carefully before use and retain for future reference.

IMPORTANT SAFETY INFORMATION

When using electrical appliances basic safety precautions should always be followed.

- To prevent fire or shock hazard, do not expose this product to rain or moisture.
- Only use the PSU supplied or one of identical specification.
- Beware that wearing headphones for long periods and at high volume levels may cause fatigue and hearing damage.

OVERVIEW

- Compact design with volume control with on/off facility and power on LED indicator.
- Supports stereo 3.5 jack and RCA input (not simultaneously).

OPERATION

- Connect the input source to either the two L and R RCA sockets or the 3.5mm stereo jack socket.
- Connect the headphones to the output jack socket.
- Connect the PSU to the power in socket and plug the PSU into the mains supply and switch it on. The power LED will illuminate.
- Adjust the output volume level using the rotary control.

SPECIFICATIONS

Output Connections	3.5mm stereo jack 6.35mm stereo jack (wired in parallel)
Total Harmonic Distortion	0.05% @ 16ohm,1kHz
Minimum load resistance	16 ohms
DC input voltage	5VDC via PSU
Dimensions (LxWxH)	97 x 64 x 30mm
Weight	70g

CLEANING & MAINTENANCE

- Clean the outside casing with a soft cloth lightly moistened with a mild detergent
- Never use any abrasive or solvents.



INFORMATION ON WASTE DISPOSAL FOR CONSUMERS OF ELECTRICAL & ELECTRONIC EQUIPMENT.

When this product has reached the end of its life it must be treated as Waste Electrical & Electronic Equipment (WEEE). Any WEEE marked products must not be mixed with general household waste, but kept separate for the treatment, recovery and recycling of the materials used. Contact your local authority for details of recycling schemes in your area.



Made in Taiwan
PR2 9PP
Man Rev 1.0