# CFP-KIT-9

# PRODUCTS FOR INDUSTRIAL AUTOMATION



Call For Parts Kit

Performance DXM700 900 MHz 1W Controller

**DIRECT SELECT Node** 

K70 Touch Button

(2) PSW-24-1 Power Supply

LMB30LP

Part Number: 810650







#### **SPECIFICATIONS**

Ships With Battery	Yes
Feature: Hazardous Area	No
Ether Net/IP	Yes
Modbus RTU	No
M o d b u s / T C P	Yes
R S - 232	No
R S - 4 8 5	Yes
Wireless	Yes
Wireless Radio Frequency	900 MHz
Voltage	24 V dc

Offline (Contact Us)

Power Supply	24 V dc 1.0 Amp
Point-to-Multipoint Topology	No
Star Topology	Yes
Tree Topology	No
Battery Type/Size	Lithium/C
Point-to-Point Topology	Yes
Max Op. Temperature (°C)	60
Min Op. Temperature (°C)	-40
Relative Humidity	95%

# **COMPATIBLE PRODUCTS**

# **BRACKET**

LMB30LP
Bracket: Right Angle, Low Profile
Fits M30 Base
12 Gauge 300 Series Stainless Steel (No Hardware)
LMBPTL110A45
Bracket: For Use with PTL110
45 Degree Angle Bracket
300 Series Stainless Steel (Hardware Included)

# **MODULAR TOWER LIGHT: TL70**

# TL70DXN9GYRQ

TL70 Wireless Tower Light, 900 MHz, Black Housing: 3-Color Indicator Voltage: 12-30 V dc; Environmental Rating: IP65

Colors: Green Yellow Red Euro 5-pin Quick-Disconnect

# 70 MM ILLUMINATED TOUCH BUTTONS: K70 SERIES

Offline (Contact Us)

# K70DXN9T2GRYQ

K70 Wireless Touch Sensor Gen 2, 900 MHz, Black Housing: 3-Color Indicator

Voltage: 12-30 V dc; Environmental Rating: IP65

Colors: Green Red Yellow Euro 5-pin Quick-Disconnect

#### PSW-24-1

DC Power Supply - Wall Mount

Input: 100 -240 V ac 50/60 Hz: Multi-blade outlet plug Output: 24 V dc 1A: 2 m (6.5 ft) Euro 4-pin Connector

UL Listed Class 2

#### **DIRECT SELECT**

#### DX80N9DSTS

Wireless Operator Interface Node 900 MHz 1W, LCD Display 0-999 Multicolor Capacitive Touch

# BWA-BK-020

80 LB Pull Rare Earth Magnetic Mounts Magnets to be Used on Multiple Mounting Brackets 1 inch Screw Pack Included

# BANNER

Banner Engineering Corp. | 9714 Tenth Avenue North | Minneapolis, MN 55441 | United States of America

Offline (Contact Us)