# **Technical Data Sheet**



# Aerowipes – ARW300

### **PRODUCT DESCRIPTION**

Electrolube Aerowipes are large, impregnated non-woven, lint free wipes for the removal of uncured and semi-cured adhesive and polysulphide sealants commonly found in the aerospace and automotive industries. They may also be used for general cleaning and degreasing applications. They are ideal for cleaning the tools used to apply sealants and adhesives.

### **FEATURES**

- The fluid used to impregnate Aerowipes is water based and entirely non hazardous
- The fluid evaporates quickly leaving a residue free finish
- Aerowipes are non-staining and have a very low odour

### DIRECTIONS FOR USE

Wear protective gloves, particularly if the operator has sensitive skin.

Pull out wipe and tear at perforation.

Remove the uncured polysuphide sealant or adhesive by wiping the surface until it is totally clean.

### Fluid Properties

 Specific Gravity (Density) @ 22°C:
 1.00 g/ml

 pH:
 5.5-6.5

#### **Wipe Properties**

41 gsm non woven fabric with excellent wet strength190 x 280 mm in size300 impregnated wipes per tub

### Packing

300 wipe tub

Order Code

ARW300

\_\_\_\_\_

Copyright Electrolube 2005 All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification. Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.

> Electrolube, A division of H K Wentworth, Kingsbury Park, Midland Road, Swadlincote, Derbyshire, DE11 0AN, UK Tel: +44(0) 1283-222111 Fax: +44(0) 1283-550177 www.electrolube.com BS EN ISO 9001:2002 Registered Firm. Certificate No. FM 32082