## **MMCX Plug**

# **multicomp** PRO

#### Specifications Electrical

Frequency Range	: DC-6 GHz
Nominal Impedance	: 50Ω
Maximum Working Voltage	: 250 V
Proof Voltage	: 500 V
Maximum VSWR	: 1.22
Material	
Bodies	: Brass per JIS-C3604
	Beryllium copper per ASTM B196 UNS C17300
Centre Contact	: Brass per JIS-C3604
Insulation	: PTFE per ASTM D1457 and ASTM D1710


#### Mechanical

Interface in accordance with BS EN 122340


#### Environmental

**Operating Temperature** : -55°C to +155°C

#### Diagram







No.	Description	Material	Finish	
1	Body	Brass	Gold 3µ″ Min.	
2	Washer	Beryllium copper		
3	Insulation	PTFE	None	
4	Centre Contact	Brass	Gold 30µ" Min.	

### Part Number Table

	Description	Part Number
sions : Millimetres (Inches)	MMCX Coaxial, Straight Bulkhead Plug, Solder, 50Ω, Beryllium Copper	MP-37-05-TGG

#### Dimens

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its resulting from its accuracy builting from its and the present liability of such as or damage arising) is excluded. negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro

