

Double Sided Polyethylene Foam Tape

multicomp^{PRO}

RoHS
Compliant

Description

A very strong high density closed cell polyethylene foam, coated on both sides with a very high performance cross linked rubber adhesive, and protected by a siliconized release liner.

Benefits

- Good gap-filling between slightly uneven materials
- Very high adhesion to most common materials
- Good tack copes well with difficult surfaces and conditions
- High shear and foam strength for mounting and holding
- Good long term ageing and resistance to water
- Outstandingly reliable general purpose product

Production Advantages



- Clean and simple to use
- Quick and efficient application
- Consistent adhesive coating thickness
- Consistent adhesion performance
- Instant adhesion
- No hazardous fumes
- No drying or curing times
- Ready for the next part of application process
- No contamination of other surfaces.

Limitations

Limited resistance to solvents, plasticisers, UV light and high temperatures.

Specification

Thickness : 0.8 mm
Temperature Range : -40°C to +60°C



Part Number Table

Description	Part Number
Double Sided Polyethylene Foam Pads, White, 0.8mm x 25mm x 12mm	PHSHTWXP0.8XX25XX12

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
Element14.com/multicomp-pro

multicomp^{PRO}