

Technical data sheet · Cablefix® Vario

Feed-through for all prefabricated cables and wires with connectors



Cable fittings and accessories

Identification	Type	AKLR 1
	Part-No.	606001
Use/Area of application		
Application	<ul style="list-style-type: none"> • Electrotechnology, pneumatics, hydraulics, robotics, general machine and plant construction 	
Properties	<ul style="list-style-type: none"> • Feed through and terminal frames from high-quality solid • Aluminium or polyamide GF30 with additional inner brass reinforcement • High flexibility in the application • Additional mounting to existing installation easily possible • Even pressure effect on the feed through round material yields good strain relief and sealing • Unneeded holes in the module can simply sealed with blank plugs • Compact design i.e. space-saving • 2 module sizes with slot and suspension principle • Very good weathering resistance • Resistant to UV radiation, ozone, oils, fuels, acids, bases, solvents and sea water 	
Technical data		
Burning behaviour	Flame-retardant	
Temperature range	-40 °C to +135 °C	
Material	Frame AKLR from smooth ground aluminium	
Protection class	IP 65	

10.05.2007 – Subject to technical modification

Part-No. 606001

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA

Tel. +1-704-504-02 22 • Fax +1-704-504-02 23

www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 4, Brabazon Court • Borman

Lichfield Road Industrial Estate • GB-Tamworth, Staffordshire B79 7TA

Tel. +44-18 27-3 13 33-0 • Fax +44-18 27-3 13 33-2

www.lutze.com • sales.gb@lutze.co.uk



Systematic Technology

Technical data sheet · Cablefix® Vario

Feed-through for all prefabricated cables and wires with connectors

Module type	VG=40×43.5 VK=40×22.9 for cable and wire diameters from 4 mm to 34.5 mm, see ordering information frame sizes, see ordering information
Height	68.0 mm
Depth	30.0 mm
Dimensions (W×H×D)	68.0×30.0
Maße (L×H×T)	108×68×30

Design

Length	108.00 mm
--------	-----------

General data

VE	1 piece
Unit	4/2
VK/VG	
With flat seal and drilling template	Yes
Note	Unit corresponds to the number of required rubber modules type VK or VG

10.05.2007 – Subject to technical modification

Part-No. 606001

USA: LUTZE INC.

13330 South Ridge Drive · Charlotte, NC 28273, USA

Tel. +1-704-504-02 22 · Fax +1-704-504-02 23

www.lutze.com · info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 4, Brabazon Court · Borman

Lichfield Road Industrial Estate · GB-Tamworth, Staffordshire B79 7TA

Tel. +44-18 27-3 13 33-0 · Fax +44-18 27-3 13 33-2

www.lutze.com · sales.gb@lutze.co.uk



Systematic Technology