Butt Splice Connectors

pro-**Power**

RoHS Compliant




Features

- · One or more conductors of varying gauges can be laid together and crimped.
- The "wire-stop" feature enables the inserted wire to be positioned optimally for crimping
- Conductor is made from brass strip

Specifications

Conductor Material	: Brass Strip		
Insulation Material	: PVC		
Plating	: Tin		
Heat Resistant	: -10°C to +75°C		

Diagram



Specification Table

Part Number	Colour	Wire Range	Dimension (mm)		Pack Size	
		mm² (AWG)	Length	D	d1	Fack Size
STBVW1	Red	0.5 to 1.5 (22 to 16)	24.5	4.3	1.7	
STBVW2	Blue	1.5 to 2.5 (16 to 14)	24.5	4.8	2.3	100
STBVW5	Yellow	4 to 6 (12 to 10)	27	6.7	3.4	

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for white any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the registered trademark of Premier Farnell Limited 2019.

Newark.com/exclusive-brands Farnell.com/exclusive-brands Element14.com/exclusive-brands

