CRC Industries UK Ltd. Castlefield Industial Estate, Wylds Rd, Bridgwater, Somerset, UK, TA64DD

Tel.: (+44)(0)1278 727200 Fax: (+44)(0)1278 425644



Material Safety Data Sheet Regulation EC No 1907/2006 Art.31

Productname :LEC-KLENECreationdate :12.01.09Ref.Nr.:UK10013-3-120109Replaces:15.02.08

1. IDENTIFICATION OF PRODUCT AND COMPANY

Productname: LEC-KLENE

Aerosol

Application : Cleaners - Precision

Company: CRC Industries UK Ltd.

Castlefield Industial Estate, Wylds Rd, Bridgwater,

Somerset, UK, TA64DD

Tel.: (+44)(0)1278 727200 Fax: (+44)(0)1278 425644 E-mail: hse.uk@crcind.com

In case of emergency: (+44)(0)1278727200

Subsidiaries		Tel	Fax
CRC Industries Europe	Touwslagerstraat 1 9240 Zele Belgium	(+32) (0) 52 / 45 60 11	(+32) (0) 52 / 45 00 34
CRC Industries Finland	Asemanrinne 13, 08500 Lohja AS	(+358)(0)19/32921	(+358)(0)19/383676
CRC Industries France	12, Bld des Martyrs de Chateaubriant F-95102 Argenteuil Cédex	(+33)(0)1/34112000	(+33)(0)1/34110996
CRC Industries Deutschland	Südring 9, 76473 Iffezheim	(+49)(0)7229/3030	(+49)(0)7229/303266
CRC Industries Iberia	Gremio del cuero S/N, 40195 Segovia	(+34)921/427546	(+34)921/436270
CRC Industries Sweden	Kryptongatan 14, 43153 Mölndal	(+46)(0)31/7068480	(+46)(0)31/273991

2. HAZARD IDENTIFICATION

Health and Safety: Extremely Flammable

Repeated exposure may cause skin dryness or cracking.

Other hazards: Pressurized container: protect from sunlight and do not

expose to temperatures exceeding 50°C.

3. COMPOSITION AND INFORMATION ON COMPONENTS

Hazardous ingredient	CAS-nr	EINECS	w/w %	symbol	R-phrases*	Notes
Hydrocarbons,C3-4-rich, petroleum						
distillate Petroleumgas (1,3-butadiene <	68512-91-4	270-990-9	30-60	F+	12	K
0.1%)						
Alkanes (C11-15, iso)	90622-58-5	292-460-6	30-60	Xn	65-66	
Explanation notes						
K: not classified as carcinogen, less than						
0.1% w/w 1,3-butadiene (Einecs-nr. 203-						
450-8)						

(* Explanation risk-phrases : see chapter 16)

4. FIRST AID MEASURES

General Advice : The usual precautions for handling chemicals should be

observed

If any symptoms should occur, seek medical advice.

Contact with eyes: If substance has got into eyes, immediately wash out

with plenty of water

Contact with skin: Wash with water and soap.

Seek medical attention if irritation persists

Inhalation: Fresh air, keep warm and at rest.
Ingestion: Ingestion is unlikely to occur

If swallowed accidentally, do not induce vomiting and

seek medical advice.

5. FIRE-FIGHTING MEASURES

Flash point (without propellant): $64 \, ^{\circ}\text{C}$ Explosion limits : upper limit : $9.4 \, \%$ lower limit : $1 \, \%$

Extinguishing media: foam, carbon dioxide or dry agent

Fire-fighting procedures : Keep container(s) exposed to fire cool, by spraying

with water

Unusual exposure hazard : Aerosols may explode if heated above 50°C

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Shut off all ignition sources

Ensure adequate ventilation

Environmental precautions: Do not allow to enter public sewers and watercourses

Cleaning methods: Absorb spillage in suitable inert material

7. HANDLING AND STORAGE

Handling procedures: Use only in well ventilated areas

Do not pierce or burn aerosols, even after use. Do not spray on a naked flame or incandescent

material.

Do not breathe aerosols or vapours. Avoid contact with skin and eyes.

Storage procedures: Pressurized container: protect from sunlight and do not

expose to temperatures exceeding 50°C. Keep in a cool, dry, well ventilated place

Keep out of reach of children.

8. EXPOSURE CONTROL AND PERSONAL PROTECTION

Control procedures : Ensure adequate ventilation

Keep away from heat and sources of ignition

Personal protection : It is advisable to take precautions to avoid contact with

skin and eyes when handling the product.

Use only in well ventilated areas

inhalation: In case of insufficient ventilation, wear suitable

respiratory equipment.

hands and skin: Wear suitable protective gloves

(nitrile)

eyes: Wear safety goggles.

9. PHYSICAL AND CHEMICAL PROPERTIES (for aerosols without propellant)

Apperance : physical state : propane/butane propelled liquid

colour : colourless

odour:

Characteristic odour

Boiling point/range: 185 °C

Relative density: 0.77 g/cm3 (@ 15°C)

pH: not applicable Vapour pressure: not available Relative vapour density: not available Solubility in water: Insoluble in water

Flash point: 64 °C **Auto-ignition:** 230 °C

Viscosity: not available **Evaporation rate:** not available

10. STABILITY AND REACTIVITY

Conditions to be avoided: Pressurized container: protect from sunlight and do not

> expose to temperatures exceeding 50°C. Keep away from heat and sources of ignition

No hazardous reactions known if used for its intended

Materials to be avoided: Strong oxidising agent

Hazardous decomposition compounds : carbon oxides

11. TOXICOLOGICAL INFORMATION

Inhalation: Inhalation of solvent vapours may give rise to nausea,

headaches and dizziness

Ingestion: Ingestion is unlikely to occur

After vomiting of swallowed product aspiration into lungs is likely. Solvents may induce chemical

pneumonia.

Skin contact: Prolonged skin contact will result in defatting of the

Eye contact: Irritating to eyes

Other information: No experimental data available

12. ECOLOGICAL INFORMATION

Other adverse effects: Do not allow to enter public sewers and watercourses

No experimental data available

13. WASTE DISPOSAL

National regulations: Disposal should be in accordance with local, state or

national legislation

14. TRANSPORT

UN-number: 1950

Road/Rail - ADR/RID: UN1950 Aerosols Class: 2, PG: NA, Class code: 5F,

Label : 2.1

Sea - IMDG: UN1950 Aerosols Ltd Qty Class: 2.1, PG: NA, Label:

2.1

EmS F-D,S-U

Air - IATA/ICAO: UN1950 Aerosols, flammable Class: 2.1, PG: NA,

Label: RFG

Packing instr. LQ Y203 PAX 203 CAO 203

15. REGULATORY INFORMATION

Warning symbol(s): F+

Risk-phrase(s): R12: Extremely flammable.

R66: Repeated exposure may cause skin dryness or

cracking.

Safety-phrase(s): S2: Keep out of the reach of children.

S16: Keep away from sources of ignition - No smoking.

S23: Do not breathe spray.S37: Wear suitable gloves.

S51: Use only in well-ventilated areas.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material.

16. OTHER INFORMATION

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It does not guarantee any specific properties.

Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.

REVISIONS IN CHAPTRE: 8,9

*Explanation risk-phrases: R12: Extremely flammable.

R65: Harmful: may cause lung damage if swallowed. R66: Repeated exposure may cause skin dryness or

cracking.

This Material Safety Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Material Safety Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com. We recommend you to register on this website for this product so you will be able to receive any future updated version automatically.