

## TECHNICAL DATA

1/2

### CRC GEAR & WIRE ROPE LUBE

Heavy duty lubricant

Ref. : 10026

#### 1. GENERAL DESCRIPTION

---

CRC Gear and Wire Rope Lube is formulated to provide protection and lubrication for open gears and wire ropes under all operating conditions.

#### 2. FEATURES

---

- Quick to dry.
- The product adheres strongly to all treated areas.
- Forms a dry, solids-enhanced, non-peeling film.
- Reduces wear and extends the operational life of the equipment.
- The tough, durable coating resists corrosion.
- Does resist dust absorption, water wash and extreme temperatures.
- Ideal for external use or for dust-laden atmospheres.

#### 3. APPLICATIONS

---

The product penetrates deeply for internal protection of open gears, wire ropes, racks and pinions, crown wheels and cams, driving mechanisms in the construction, shipyard, docks and marine, quarrying, plant hire, heavy engineering, automotive and manufacturing industries:

Tower Cranes	Hoists and Winches	Textile Machinery
Overhead Cranes	Excavators	Paper Making Machinery
Derrick Cranes	Agricultural Machinery	
Mobile Cranes	Printing Machinery	

#### 4. DIRECTIONS

---

- Apply a light, even coating from 25 - 30 cm and re-apply as necessary. Can be applied to running gear mechanisms if required. On wire ropes, allow 15 minutes for full penetration before use of equipment.
- A safety data sheet (MSDS) according to EU directive 91/155/EEC and amendments is available for all CRC products.

#### 5. TYPICAL PRODUCT DATA (without propellant)


---

Appearance	: Black liquid
Odour	: Hydrocarbon
Specific gravity	: 0.92
Temperature range	: - 25°C to +100°C
Solubility	: Soluble in most organic solvents, insoluble in water



Manufactured by :  
CRC Industries Europe BVBA  
Touwslagerstraat 1 – 9240 Zele – Belgium  
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34  
[www.crcind.com](http://www.crcind.com)





## TECHNICAL DATA

2/2

### CRC GEAR & WIRE ROPE LUBE

Heavy duty lubricant

Ref. : 10026

#### 6. PACKAGING

---

Aerosol 12 x 400 ml

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

This Technical Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: [www.crcind.com](http://www.crcind.com).

We recommend you to register on this website for this product so you will be able to receive any future updated version automatically.

Version : 10026 03 0805 01

Date : 15 May 2006



Manufactured by :

CRC Industries Europe BVBA

Touwslagerstraat 1 – 9240 Zele – Belgium

Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34

[www.crcind.com](http://www.crcind.com)

