

# White uPVC Trunking



## Features:

- Complies to BS4678 part 4.
- Double locking clip-on lid.
- Self-extinguishing.
- Corrosion resistant.

## Specifications:

### Subject:

Mini trunking and cable trunking.

### Material:

High impact white uPVC.

### Strength:

Meets the distortion and impact test requirements of BS4678 part 4 - specification for cable trunking manufactured from insulating material (medium mechanical stress, -5°C).

### Fire Behaviour:

uPVC meets all the requirements of the 1997 building regulations in relation to flame spread and propagation.

Meets the requirements of resistance to flame propagation defined in BS4678 part 4.

nPVC is self extinguishing and does not drip flaming particles.

### Chemical Properties:

uPVC has excellent resistance to many chemical solutions including those of weak acids, strong and weak alkalis, alcohols, aliphatic hydrocarbons and oils. Effects of strong acids are only slight. It will swell in aromatic hydrocarbons and is soluble or will swell in ketones.

uPVC is impervious to damp conditions and will not corrode.

### Electrical Characteristics:

uPVC is non-conductive and therefore will not become live due to accidental contact with live conductors. It has a typical volume resistance of more than  $1 \times 10^{14}$  ohms.

## Specification Table

Width	Depth	Length	Part Number
50	50	3	NFCT22
75	75		NFCT33
100	50		NFCT42

Dimensions : Millimetres

**Disclaimer** This data sheet and its contents (the "Information") belong to the Premier Farnell Group (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. SPC Multicomp is the registered trademark of the Group. © Premier Farnell plc 2009.

<http://www.farnell.com>  
<http://www.newark.com>  
<http://www.cpc.co.uk>

