

9903 Paired - 10 Base 5 Transceiver

	<p>For more information please call 1-800-Belden1</p> <p><u>See Put-ups and Colors</u></p>
---	---

Description:

4 Pairs, 3 - 28 AWG (7x32) tinned copper conductors, 1 - 24 AWG (7x36), all individually shielded, overall isolated Duofoil® plus tinned copper braid shield, PVC jacket.

SUITABLE APPLICATIONS:

Suitable Applications	IEEE 802.3 Transceiver Cable
-----------------------	------------------------------

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Pairs	4
Total Number of Conductors	8

AWG :

Number of Pairs	AWG	Stranding	Conductor Material	Conductor Diameter (in.)
3	28	7x36	TC - Tinned Copper	
1	24	7x32	TC - Tinned Copper	

Stranding	7x36, 7x32
Conductor Material	TC - Tinned Copper

INSULATION:

Insulation Material	PP - Polypropylene
---------------------	--------------------

PAIR:

Pair Shield Material Trade Name	Beldfoil® (Z-Fold®)
Pair Shield Type	Tape
Pair Shield Material	Aluminum Foil-Polyester Tape
Pair Shield % Coverage	100 %

Pair Color Code Chart :

Number	Color	Number	Color
78 Ohm	Gray & White	78 Ohm	Blue & Green
78 Ohm	Yellow & Orange	Power	Black & Red

INNER SHIELD:

INNER SHIELD DRAIN WIRE :

Inner Shield Drain Wire AWG	24
Inner Shield Drain Wire Stranding	7x32
Inner Shield Drain Wire Conductor Material	TC - Tinned Copper

9903 Paired - 10 Base 5 Transceiver

OVERALL CABLING:

Overall Cabling Separator Material	Polyester Tape
------------------------------------	----------------

OUTER SHIELD:

Outer Shield Material Trade Name	Duofoil®
----------------------------------	----------

Outer Shield Type	Tape/Braid
-------------------	------------

Outer Shield Material :

Layer Number	Material Trade Name	Type	Material	% Coverage (%)
1	Duofoil®	Tape	Aluminum Foil-Polyester Tape-Aluminum Foil	100
2		Braid	TC - Tinned Copper	92

Outer Shield % Coverage	100 %
-------------------------	-------

OUTER JACKET:

Outer Jacket Material	PVC - Polyvinyl Chloride
-----------------------	--------------------------

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	.250 in.
--------------------------	----------

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-20°C To +80°C
-----------------------------	----------------

UL Temperature Rating	80°C (UL AWM Style 2919)
-----------------------	--------------------------

Bulk Cable Weight	41 lbs/1000 ft.
-------------------	-----------------

Max. Recommended Pulling Tension	68 lbs.
----------------------------------	---------

Min. Bend Radius (Install)	2.5 in.
----------------------------	---------

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

NEC/(UL) Specification	CMG
------------------------	-----

CEC/C(UL) Specification	CMG
-------------------------	-----

AWM Specification	2919 (30 V 80°C)
-------------------	------------------

IEEE Specification	IEEE802.3
--------------------	-----------

FLAME TEST:

UL Flame Test	UL1685 UL Loading
---------------	-------------------

CSA Flame Test	FT4
----------------	-----

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
--------------	---

ELECTRICAL CHARACTERISTICS:

Nom. Characteristic Impedance	78 ± 5 Ohms
-------------------------------	-------------

Nom. Capacitance Conductor to Conductor @ 1 KHz	19.7 pF/ft
---	------------

Nom. Cap. Cond. to Other Cond. & Shield @ 1 KHz	34.8 pF/ft
---	------------



9903 Paired - 10 Base 5 Transceiver

Nominal Velocity of Propagation	66 %
Nominal Delay	1.54 ns/ft
Nom. Conductor DC Resistance @ 20 Deg. C :	
Description	Nom. Conductor DC Resistance @ 20 Deg. C (Ohms/1000 ft)
28 AWG	65
24 AWG	24
Nominal Outer Shield DC Resistance @ 20 Deg. C	2.9 Ohms/1000 ft
Max. Operating Voltage - UL	30 V RMS
Other Maximum Continuous Currents	.875 Amps per conductor at 25°C (28 AWG); 1.5 Amps per conductor at 25°C (24 AWG)

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
9903 E4X1000	1#24,3#28 SHPR PP SH PVC	1000	43	GRAY, LIGHT DEC	C
9903 E4X500	1#24,3#28 SHPR PP SH PVC	500	21.5	GRAY, LIGHT DEC	

C = CRATE REEL PUT-UP.

Revision Number: 1 Revision Date: 11-10-2003

© 2003 Belden Wire & Cable Company
All Rights Reserved.

Although Belden Electronics Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.