

ZHD-CT

TE Internal #: EL8114-000

ZHD-CT, Printable Tubing, Continuous Printable Tubing Type, Fluid

Resistant & Low Fire Hazard Printable Tubing Grade

View on TE.com >



Identification & Labeling > Printable Tubing > ZHD-CT LFH & FLUID RESISTANT TUBE



Printable Tubing Type: Continuous

Printable Tubing Grade: Fluid Resistant & Low Fire Hazard

Printable Tubing Shrink Ratio: 2:1
Primary Product Color: White

Supplied Inner Diameter: 6.4 mm [.25 in]

All ZHD-CT LFH & FLUID RESISTANT TUBE (18)

Features

Product Type Features

Product Type Features	
Printable Tubing Type	Continuous
Printable Tubing Grade	Fluid Resistant & Low Fire Hazard
Body Features	
Printable Tubing Shrink Ratio	2:1
Primary Product Color	White
Dimensions	
Supplied Inner Diameter	6.4 mm[.25 in]
Recovered Inside Diameter	3.2 mm[.125 in]
Compatible Cable Diameter Range	3.8 – 5.4 mm[.15 – .215 in]
Usage Conditions	
Operating Temperature Range	-55 – 135 °C[-67 – 275 °F]
Operation/Application	
Recommended Ribbon	See TE Document 411-121005 the Printer Product Ribbon Matrix
Printer/Label Features	

See TE Document 411-121005 the Printer

Product Ribbon Matrix

Recommended Printer



Printer Technology	Thermal Transfer
Packaging Features	
Packaging Quantity	50

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUL 2021 (219) Candidate List Declared Against: JAN 2021 (211) SVHC > Threshold: Not Yet Reviewed
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



















Also in the Series | ZHD-CT



Customers Also Bought









TE Part #6787634001 ZH-100-3/8-0-SP







TE Part #270225-000

B-150-07





Documents

Product Drawings
ZHD-CT-50M-6.4-OUT-9

English

Datasheets & Catalog Pages

ZHD-CT, Continuous Zero Low Fire Hazard, Diesel Resistant Heat Shrink Identification Tube

English

ZHD-CT, Printable Tubing, Continuous Printable Tubing Type, Fluid Resistant & Low Fire Hazard Printable Tubing Grade



Product Specifications

Product Specification

English

Instruction Sheets

Instruction Sheet (non U.S.)

English