

multicomp	PART NO.		REVISIONS								
	4409SM-08-A-CP	ECN #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE	
		-	А	RELEASED	Geetha	24/4/08	Suresh	24/4/08	G. C	09/5/08	






Dimensions : Millimetres

5.25

Recommended PCB Layout



Dimensions : Millimetres

This data sheet and its contents (the "Information") belong to the Premier Farnell Group (the "Group") or are licensed to it. No licence is granted for the use of it other than for	TOLERANCES:	DRAWN BY:	DATE:	DRAWI	NG TITLE:				
information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change with- out notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the prod- ucts for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or	UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.	Geetha	24/04/08	SMD Socket - Locking 8 Way				8 Way	
		CHECKED BY:	DATE:	SIZE	DWG NO.	M10000940	ELECTRONIC FILE 4409AS & SM_30_DWG		REV
		Suresh	24/04/08	Δ					
		APPROVED BY:	DATE:]		U.O.M.: mm			
		G.Cook	09/05/08	SCALE	E: NTS			SHEET: 1 OF	- 2

Specifications:

Current rating Voltage rating Maximum contact resistance Minimum insulation resistance Withstanding voltage Operating temperature range **Material and Finish** Insulator Contact Plating


- : 1.0A ac/dc.
- : 30V ac/dc.
- : 20m ohm.
- : 1000M ohm.
- : 500V ac for one minute.
- : -40°C to +105°C.
- : High tempature plastic.
- : Copper alloy.
- : Selective plated.

	PART NO.		REVISIONS								
	4409SM-08-A-CP	ECN #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE	
		-	А	RELEASED	Geetha	24/4/08	Suresh	24/4/08	G. C	09/5/08	

Part Number Table

Description	Part Number
Socket, SMD, Locking 8 Way	4409SM-08-A-CP

Part Number Explanation:



Number of Contacts : 08 = 8 contacts.

http://www.farnell.com

http://www.newark.com

http://www.cpc.co.uk

				1					
believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the prod- ucts for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or	TOLERANCES:	DRAWN BY:	DATE:	DRAWING TITLE:					
	UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.	Geetha	24/04/08	SMD Socket - Locking 8 Way					
		CHECKED BY:	DATE:	SIZE DWG NO.	M10000940	ELECTRONIC FILE	REV		
		Suresh	24/04/08	Δ		4409AS & SM_30_DWG			
		APPROVED BY:	DATE:		I				
or rest	the possibility of such loss of damage arising is excluded. Inits will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. SPC MULTICOMP is the registered trademark of the Group. © Premier Farnell plc 2008.		G.Cook	09/05/08	SCALE: NTS	U.O.M.: mm	SHEET: 2 OF	F 2	