2-1761679-3 ACTIVE

AMP-LATCH

TE Internal #: 2-1761679-3

Ribbon Cable Connectors, Wire-to-Board, 10 Position, 2.54mm [.

1in] Centerline, Vertical, Through Hole - Solder, Row-to-Row

Spacing 2.54 mm [.1 in]

View on TE.com >





Connectors > PCB Connectors > Wire-to-Board Connectors > FFC, FPC & Ribbon Connectors > Ribbon Cable Connectors











Connector System: Wire-to-Board

Number of Positions: 10

Centerline (Pitch): 2.54 mm [.1 in]
PCB Mount Retention: Without
PCB Mount Orientation: Vertical

Features

Product Type Features

Connector Type	Header
Ribbon Cable Connector Header Type	Pin Header
Connector Product Type	Connector Assembly
Connector System	Wire-to-Board
Connector & Housing Type	Plug
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Number of Positions	10
PCB Mount Orientation	Vertical
Number of Rows	2
Electrical Characteristics	
Insulation Resistance	5000 MΩ

250 VAC

Body Features

Operating Voltage



Daisy Chain	With
Connector Profile	Low
Contact Features	
Mating Square Post Dimension	.64 mm[.025 in]
PCB Contact Termination Area Plating Material Thickness	2.54 μm[100 μin]
Mating Pin Diameter	.64 mm[.025 in]
Contact Type	Pin
	30 µin
Contact Mating Area Plating Material	Gold
Contact Shape & Form	Square
Contact Underplating Material	Nickel
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Phosphor Bronze
Contact Current Rating (Max)	1 A
Termination Features	
Square Termination Post & Tail Dimension	.5 mm[.02 in]
Round Termination Post & Tail Diameter	.64 mm[.025 in]
Termination Post & Tail Length	4.19 mm[.165 in]
Termination Method to Printed Circuit Board	Through Hole - Solder
Mechanical Attachment	
Mating Alignment	With
PCB Mount Alignment	Without
Panel Mount Feature	Without
PCB Mount Retention	Without
Mating Alignment Type	Center
Mating Retention	Without
Connector Mounting Type	Board Mount
Housing Features	
Mating Entry Location	Тор
Housing Material	PBT
Housing Color	Blue
Centerline (Pitch)	2.54 mm[.1 in]



Dimensions

Shrouded End Dimension	3.81 mm[.15 in]
Connector Length	20.32 mm[.8 in]
Connector Height	8.89 mm[.35 in]
Row-to-Row Spacing	2.54 mm[.1 in]

Usage Conditions

Housing Temperature Rating	High
Operating Temperature Range	-65 – 105 °C[-85 – 221 °F]

Operation/Application

Circuit Application	Signal	
---------------------	--------	--

Industry Standards

L Flammability Rating	UL 94V-0	

Packaging Features

Packaging Quantity	50
Packaging Method	Package

Other

Comment	For Use With AMP-Latch Receptacle
33111113111	1 01 000 111111 201011 11000 01010

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU EU ELV Directive 2000/53/EC Compliant China RoHS 2 Directive MIIT Order No 32, 2016 No Restricted Materials Above Threshold EU REACH Regulation (EC) No. 1907/2006 Current ECHA Candidate List: JUL 2021 (219) Candidate List Declared Against: JAN 2021 (211) SVHC > Threshold: Not Yet Reviewed Halogen Content Not Low Halogen - contains Br or Cl > 900 ppm. Solder Process Capability Wave solder capable to 265°C		
China RoHS 2 Directive MIIT Order No 32, 2016 EU REACH Regulation (EC) No. 1907/2006 Current ECHA Candidate List: JUL 2021 (219) Candidate List Declared Against: JAN 2021 (211) SVHC > Threshold: Not Yet Reviewed Not Low Halogen - contains Br or Cl > 900 ppm.	EU RoHS Directive 2011/65/EU	Compliant
EU REACH Regulation (EC) No. 1907/2006 Current ECHA Candidate List: JUL 2021 (219) Candidate List Declared Against: JAN 2021 (211) SVHC > Threshold: Not Yet Reviewed Not Low Halogen - contains Br or Cl > 900 ppm.	EU ELV Directive 2000/53/EC	Compliant
(219) Candidate List Declared Against: JAN 2021 (211) SVHC > Threshold: Not Yet Reviewed Not Low Halogen - contains Br or Cl > 900 ppm.	China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
ppm.	EU REACH Regulation (EC) No. 1907/2006	(219) Candidate List Declared Against: JAN 2021 (211) SVHC > Threshold:
Solder Process Capability Wave solder capable to 265°C	Halogen Content	- Control of the cont
	Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





Customers Also Bought















Documents

Product Drawings

IDC LOW PRO HDR 10P VERT BLUE

English

CAD Files

3D PDF



3D

Customer View Model

ENG_CVM_CVM_2-1761679-3_B.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2-1761679-3_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2-1761679-3_B.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Product Specification

English

Product Environmental Compliance

MD_2-1761679-3_12042012110

English

MD_2-1761679-3_12042012110

English

Agency Approvals

UL Report

English