

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Conformal Coating

Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

Anti Corrosion Products

1.3. Details of the supplier of the safety data sheet

Premier Farnell 150 Armley Road Leeds LS12 2QQ

Tel.: +44 (0) 8701 202530

1.4. Emergency telephone number

+44 1865 407333

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Physical : Aerosols, category 1

Extremely flammable aerosol.

Pressurised container: May burst if heated

Classification is based on test data.

Health : Eye irritation, category 2

Causes serious eye irritation.

Specific target organ toxicity - single exposure, category 3

May cause drowsiness or dizziness.

Classification based on calculation method.

Environment : Not classified

Classification based on calculation method.

2.2. Label elements

Hazard pictogram(s)

Labelling according to Regulation (EC) No 1272/2008

Product identifier : Contains:

n-butyl acetate ethyl acetate

. <

Signal word : Danger

Hazard statement(s): : H222 : Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

H319 : Causes serious eye irritation. H336 : May cause drowsiness or dizziness.

Precautionary statement(s) : P102 : Keep out of reach of children.

P210 : Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

P211 : Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.





P271: Use only outdoors or in a well-ventilated area.

P410/412 : Protect from sunlight. Do not expose to temperatures exceeding

50°C/122°F.

P501-2: Dispose of contents/container to an authorised waste collection point.

Supplemental Hazard information : Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

No information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable.

3.2. Mixtures

Hazardous ingredient	Registration number	CAS- nr.	EC-nr	w/w %	Hazard Class and Category	Hazard statement	Notes
n-butyl acetate	01-2119485493- 29	123- 86-4	204- 658-1	25-50	Flam. Liq. 3, STOT SE 3	H226,H336	
Hydrocarbons,C3-4-rich, petroleum distillate Petroleumgas (1,3-butadiene < 0.1%)	01-2119485926- 20	68512- 91-4	270- 990-9	25-50	Press. Gas, Flam. Gas 1	H280,H220	K,G
1-methoxy-2-propanol; monopropylene glycol methyl ether	01-2119457435- 35	107- 98-2	203- 539-1	10-25	Flam. Liq. 3, STOT SE 3	H226,H336	А
ethyl acetate	01-2119475103- 46	141- 78-6	205- 500-4	10-25	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3	H225,H319, H336	В

Explanation notes

Contact with skin

A: substance with Community workplace exposure limit

B: substance with national established workplace exposure limit

G: exempted from the obligation to register in accordance with art.2(7)of REACH Regulation No 1907/2006

K: not classified as carcinogen, less than 0.1% w/w 1,3-butadiene (Einecs-nr. 203-450-8)

(*Explanation phrases : see chapter 16)

SECTION 4: First aid measures

4.1. Description of first aid measures

Contact with eyes : IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention.

: Take off contaminated clothing and wash before reuse.

IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention.

Inhalation : IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER or doctor/physician if you feel unwell.

Ingestion : If swallowed accidentally, do not induce vomiting and seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation : Excessive inhalation of solvent vapours may give rise to nausea, headaches and dizziness





Ingestion : May cause gastrointestinal disturbances.

Symptoms: sore throat, abdominal pain, nausea, vomiting

Skin contact : May cause irritation.

Symptoms: redness and pain

Eye contact : Irritating to eyes

Symptoms: redness and pain

4.3. Indication of any immediate medical attention and special treatment needed

General Advice : If you feel unwell, seek medical advice show the label where possible

If symptoms persist always call a doctor

SECTION 5: Firefighting measures

5.1. Extinguishing media

Foam, carbon dioxide or dry agent

Do not use water jet extinguishing media, due to the risk of spreading fire.

5.2. Special hazards arising from the substance or mixture

Aerosols may explode if heated above 50°C Forms hazardous decomposition products CO.CO₂

5.3. Advice for firefighters

Keep container(s) exposed to fire cool, by spraying with water In case of fire, do not breathe fumes

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Shut off all ignition sources

Ensure adequate ventilation; Wear suitable protective clothing and gloves.

6.2. Environmental precautions

Do not allow to enter public sewers and watercourses

6.3. Methods and material for containment and cleaning up

Absorb spillage in suitable inert material

Place in appropriate container

6.4. Reference to other sections

For further information see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep away from heat and sources of ignition

Take precautionary measures against static discharges

Equipment should be earthed

Use explosion-proof electrical/ventilating/lighting/.../equipment.

Use only non-sparking tools.

Do not breathe aerosols or vapours.

Ensure adequate ventilation

Avoid contact with skin and eyes.

Wash thoroughly after use





Wear protective gloves/protective clothing/eye protection/face protection. Eyewash bottles should be available

7.2. Conditions for safe storage, including any incompatibilities

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Keep out of reach of children.

7.3. Specific end use(s)

Anti Corrosion Products

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits:

Hazardous ingredient	CAS-nr.	method	
EU established exposure limits:	•		
1-methoxy-2-propanol; monopropylene glycol methyl ether	107-98-2	TWA	100 ppm
		STEL	150 ppm
ethyl acetate	141-78-6	TWA	200 ppm
		STEL	400 ppm
National established exposure limits, United Kingdom	•		
1-methoxy-2-propanol; monopropylene glycol methyl ether	107-98-2	TWA	100 ppm
		STEL	150 ppm
n-butyl acetate	123-86-4	TWA	150 ppm
		STEL	200 ppm
ethyl acetate	141-78-6	TWA	200 ppm
		STEL	400 ppm

8.2. Exposure controls

Control procedures : Ensure adequate ventilation

Keep away from heat and sources of ignition

Take precautionary measures against static discharges

Personal protection : Take precautions to avoid contact with skin and eyes when handling the product

Ensure adequate ventilation

Inhalation : In case of insufficient ventilation, wear suitable respiratory equipment

Recommended respiratory protection : Air purifying respirator equiped with organic gas/vapor cartridge (type A)

Hands and Skin : When handling the product wear chemical-resistant gloves (standard EN 374).

The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be

changed part-way through.

Recommended gloves : Polyvinylalcohol

Eyes : Wear safety eyewear according to EN 166.

Environmental protection : Avoid release to the environment.

Collect spillage.







SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

(for aerosols data for the product without propellant)

Appearance : physical state : Propane/butane propelled liquid

Colour : Colourless Odour : Solvent. рΗ : Not applicable Boiling point/range : Not available. Flash point : - 4°C (Closed Cup) Evaporation rate : Not available Explosion limits: upper limit : Not available. Lower limit : Not available. : Not available Vapour pressure

Relative density : 0.919 g/cm3 (@ 20°C) Solubility in water : Insoluble in water

Auto-ignition : > 200°C
Viscosity : Not available

9.2. Other information

VOC = volatile organic compounds : 700 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reactions known if used for its intended purpose

10.2. Chemical stability

Stable

10.3. Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose

10.4. Conditions to avoid

Avoid overheating

10.5. Incompatible materials

Strong oxidising agent

10.6. Hazardous decomposition products

CO, CO₂

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Based on available data the classification criteria are not met

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitisation: Based on available data the classification criteria are not met Germ cell mutagenicity: Based on available data the classification criteria are not met Carcinogenicity: Based on available data the classification criteria are not met Toxicity for reproduction: Based on available data the classification criteria are not met





STOT-single exposure : May cause drowsiness or dizziness.

STOT repeated exposure : Based on available data the classification criteria are not met : Based on available data the classification criteria are not met

Information on likely routes of exposure:

Inhalation : Inhalation of solvent vapours may give rise to nausea, headaches and dizziness

Ingestion : May cause gastrointestinal disturbances

Skin contact : May cause irritation.
Eye contact : Irritating to eyes

Toxicological data:

Hazardous ingredient	CAS-nr.	method	
1-methoxy-2-propanol; monopropylene glycol methyl ether	107-98-2	LD50 oral rat	4016 mg/kg
		LC50 inhal.rat	27596 mg/l
		LD50 derm.rabit	2000 mg/kg
n-butyl acetate	123-86-4	LD50 oral rat	10760 mg/kg
		LC50 inhal.rat	> 20 mg/l
		LD50 derm.rabit	> 1400 mg/kg
ethyl acetate	141-78-6	LD50 oral rat	5620 mg/kg
		LC50 inhal.rat	30 mg/l
		LD50 derm.rabit	> 20000 mg/kg

SECTION 12: Ecological information

12.1. Toxicity

Not classified

Ecotoxicological data:

Hazardous ingredient	CAS-nr.	method	
1-methoxy-2-propanol; monopropylene glycol methyl ether	107-98-2	LC50 fish	6812 mg/l
		EC50 daphnia	23300 mg/l
n-butyl acetate	123-86-4	IC50 algae	647 mg/l
		LC50 fish	18 mg/l
		EC50 daphnia	44 mg/l
ethyl acetate	141-78-6	IC50 algae	5600 mg/l
		LC50 fish	230 mg/l
		EC50 daphnia	610 mg/l

12.2. Persistence and degradability

No information available

12.3. Bioaccumulative potential

No information available

12.4. Mobility in soil

Insoluble in water





12.5. Results of PBT and vPvB assessment

No information available

12.6. Other adverse effects

No information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product : This material and its container must be disposed of in a safe way.

Do not discharge into drains or the environment, dispose to an authorised

waste collection point.

National regulations : Disposal should be in accordance with local, state or national legislation

SECTION 14: Transport information

14.1. UN number

UN-number : 1950

14.2. UN proper shipping name

Proper shipping name : AEROSOLS

14.3. Transport hazard class(es)

Class : 2.1 ADR/RID - Classification code : 5F

14.4. Packing group

Packing group : Not applicable

14.5. Environmental hazards

ADR/RID - Environmentally

hazardous : No IMDG - Marine pollutant : No

IATA/ICAO - Environmentally

hazardous : No

14.6. Special precautions for user

 ADR/RID - Tunnelcode
 : (D)

 IMDG - Ems
 : F-D, S-U

 IATA/ICAO - PAX
 : 203

 IATA/ICAO - CAO
 : 203

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The Safety Data Sheet is compiled according to the current European requirements.

Regulation (EC) No 1907/2006 (REACH)

Regulation (EC) No 1272/2008 (CLP)

Dir. 2013/10/EU, 2008/47/EC amendment of the aerosol dispenser directive 75/324/EEC.







15.2. Chemical safety assessment

No information available

SECTION 16: Other information

*Explanation hazard statements: H220: Extremely flammable gas.

H225 : Highly flammable liquid and vapour. H226 : Flammable liquid and vapour.

H280: Contains gas under pressure; may explode if heated.

H319 : Causes serious eye irritation. H336 : May cause drowsiness or dizziness.

Acronyms and synonyms : TWA = time weight average

STEL = short time exposure limit VOC = volatile organic compounds PBT = persistant bioaccumulative toxic vPvB = very persitant very bioaccumulative

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation. The information contained herewith is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It does not guarantee any specific properties.

Part Number

PPC121

Important Notice: This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

